





Declaration of performance

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

Declaration of conformity

according Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359

for the product			
	SP Top rapid		
No.	GBI-P 48-4		
Unique identification code of the product-type	0404		
Intended use/es	Designed rendering/plastering mortar used on moist masonry walls containing water soluble salts		
Manufacturer	Remmers GmbH Bernhard-Remmers-Str. 13 49624 Löningen (DE)		
	Distributor UKCA: Remmers (UK) Limited 1 & 2 Garden Suites, Coleshill Manor Campus, Birmingham B46 1DL (GB)		
System/s of AVCP	System 4 (for internal and external uses, in walls, columns + partitions) System 4 (for reaction to fire regulations)		
Harmonised standard	EN 998-1: 2017-02		
Notified body/ies	not relevant		

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire class:	A1	System 4	EN 998-1: 2017-02
Adhesion:	≥ 0,08 N/mm² (fracture pattern B)		
Water absorption:	≥ 0,3 kg/m² after 24 h		
Water vapour permeability (µ):	≤ 15		
Thermal conductivity $(\lambda_{10,dry, mat})$ for P = 50 %	≤ 0,27 W/(mK) (tab. value EN 1745)		
Durability (against freeze-thaw):	Resistant, by use acc. TDS		
Dangerous substances:	NPD		







The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance & conformity is issued, in accordance with Regulation (EU) No 305/2011 and Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Remme	rs GmbH
R & D Building	g protection IV
i.V. Dr. Magnus Greiwe	i.A. Thomas Anneken
(Department manager)	(Laboratory staff)

The declaration of performance was created electronically and is also valid without signature.

Löningen, 2024-03-28