





## **Declaration of performance**

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

for the product	<b>FM TK PH</b> Variants: 1018, 1024		
No.	GBI-P 39-5		
Unique identification code of the product-type	1024		
Intended use/es	Designed general purpose masonry mortar for internal and external use in elements subject to structural requirements		
Manufacturer	Remmers GmbH Bernhard-Remmers-Str. 13 49624 Löningen (DE)		
System/s of AVCP	System 2+ (for internal and external uses, in walls, columns and partitions) System 4 (for reaction to fire regulations)		
Harmonised standard	EN 998-2: 2016-11		
Notified body/ies	GG-CERT e.V., Annastraße 67-71, 50968 Köln, Notified Body 0785		

Certificate of conformity of the factory production control  $\mathbf{0.785}$  -  $\mathbf{CPR}$  -  $\mathbf{21}$  -  $\mathbf{104}$  -  $\mathbf{13}$ 

## Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Compressive strength:	M5	System 2+ EN 998-2: 2016-11	
Bond strength:	≥ 0,08 N/mm² (Characteristic initial shear strength (adhesive shear strength) tested acc. to EN 1052-3 (method B) in conjunction with sand-lime brick acc. to EN 771 at a moisture content of 3-7 M-%)		
Contents of chlorides:	≤ 0,01 M-%		
Water absorption:	≤ 0,10 kg/(m²•min <sup>0,5</sup> )		EN 998-2: 2016-11
Water vapour permeability (μ):	15/35 (tab. value EN 1745)		
Thermal conductivity $(\lambda_{10,dry,mat})$ for P = 50 %	≤ 0,82 W/(m•K) (tab. value EN 1745)		
Thermal conductivity $(\lambda_{10,dry, mat})$ for P = 90 %	≤ 0,89 W/(m•K) (tab. value EN 1745)		
Durability (against freeze-thaw):	Resistant, by use acc. TDS		
Reaction to fire class:	A1 (System 4)		
Dangerous substances:	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.





Signed for and on behalf of the manufacturer by	
Remmers	s GmbH
R & D Building	protection IV
i.V. Dr. Magnus Greiwe	i.A. Thomas Anneken
(Department manager)	(Laboaratory staff)
The declaration of performance was created electronically and is also valid w	vithout signature.

Löningen, 2024-05-21