





Declaration of performance

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

for the product	FM TK		
	Variants 1022, 1023, 1026		
No.	GBI-P 56-5		
Unique identification code of the product-type	1026		
Intended use/es	Designed general purpose masonry mortar for internal and external use in elements subject to structural requirements		
Manufacturer	Remmers GmbH Bernhard-Remmers-Str. 13 49624 Löningen (DE)		
System/s of AVCP	System 2+ (for internal and external uses, in walls, columns and partitions) System 4 (for reaction to fire regulations)		
Harmonised standard	EN 998-2: 2016-11		
Notified body/ies	GG-CERT e.V., Annastraße 67-71, 50968 Köln, Notified Body 0785		

Certificate of conformity of the factory production control ${\tt 0785-CPR-21-104-13}$

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Compressive strength:	M5		
Bond strength:	≥ 0,08 N/mm² (Characteristic initial shear strength (adhesive shear strength) tested acc. to EN 1052-3 (method B) in conjunction with sand-lime brick acc. to EN 771 at a moisture content of 3-7 M-%)	System 2+ EN 998-2: 2016-11	
Contents of chlorides:	≤ 0.1 M-%		
Water absorption:	$\leq 0.54 \text{ kg/(m}^2 \cdot \text{min}^{0,5})$		EN 998-2: 2016-11
Water vapour permeability (µ):	15/35 (tab. value EN 1745)		2.1.000 2.12010 1.1
Thermal conductivity ($\lambda_{10,dry,mat}$) for P = 50 %	≤ 0.82 W/(m•K) (tab. value EN 1745)		
Thermal conductivity ($\lambda_{10,dry,mat}$) for P = 90 %	≤ 0.89 W/(m•K) (tab. value EN 1745)		
Durability (against freeze-thaw):	Resistant, by use acc. TDS		
Reaction to fire class:	A1 (System 4)		
Dangerous substances:	NPD		

FMTK





The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Remmers Gm	nbH
R & D Building prote	ection IV
i.V. Dr. Magnus Greiwe	i.A. Thomas Anneken
(Department manager)	(Laboaratory staff)

The declaration of performance was created electronically and is also valid without signature.

Löningen, 2024-05-10