

## **DECLARATION OF PERFORMANCE**

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014 + UK

Name of the product Kompressenputz No. GBI P 45-3

Unique identificatior	code of	the	product-type:
-----------------------	---------	-----	---------------

1077

Intended use/es:

Designed rendering/plastering mortar with a dry hardened density

≤ 1300 kg/m<sup>3</sup>

Manufacturer:

Remmers GmbH

Bernhard-Remmers-Straße 13

D-49624 Löningen

**Distributor UKCA:** 

Remmers (UK) Limited, Unit 4, Lloyds Court, Manor Royal Crawley,

**RH10 9QU** 

System/s of AVCP:

System 4 (for internal and external uses, in wall, column, partition and

ceiling finishes)

**System 4** (for reaction to fire regulations)

Harmonised standard:

not relevant

Notified body/ies:

not relevant



**GBI-P 45-3** 

## Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Reaction to fire	class A1		
Adhesion	≥ 0,08 N/mm² (fracture pattern B)		EN 998-1: 2017-02
Water absorption	W0		
Water vapour permeability	µ ≤ 15	Sunday A	
Thermal conductivity (λ10,dry)	≤ 0,21 W/(mK) for P = 50 %	System 4	
Durability (against freeze- thaw)	Resistant, by use acc. TDS		
Dangerous substances	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 and 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Remmers GmbH R&D Building protection

Löningen, 01.07.2022

(place and date of issue )

i.V. Dr. Amir Asgharzadeh

(Senior Manager)

ppa. Carsten Nagel

(Director)