

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

Name of the product
FL fix white
Nr. GBI-P 22-4

Unique identification code of the product-type:
2850

Intended use/es:
**Cementitious mortar for elevated requirements with reduced
slippage and extended open time (class C2 FTE S1)**

Manufacturer:
**Remmers GmbH
Bernhard-Remmers-Straße 13
49624 Lönigen / Germany**

System/s of AVCP:
**System 3 (for internal and external uses)
System 3 (for reaction to fire regulations)**

Harmonised standard:
EN 12004: 2017-05

Notified body/ies:
**IBMB MPA
Materialprüfanstalt (MPA) Braunschweig
Beethovenstr. 52
38106 Braunschweig
Identification number 0761**

has conducted the type testing of the product and the following is
displayed: **test report no. 1202/991/20**

Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Reaction to fire:	class E	System 3	EN 12004: 2017-05
Initial tensile adhesion strength	≥ 1,0 MPa (C2)		
Tensile adhesion strength after water immersion	≥ 1,0 MPa (C2)		
Tensile adhesion strength after thermal aging	≥ 1,0 MPa (C2)		
Tensile adhesion strength after heat freeze/thaw cycles	≥ 1,0 MPa (C2)		
Open time: Tensile adhesion strength	≥ 0,5 MPa		
Extended open time: Tensile adhesion strength	≥ 0,5 MPa		
Early adhesive pull strength	≥ 0,5 MPa		
Slipping	≤ 0,5 mm		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Remmers GmbH
i.V. Dirk Wöltering, Bereichsleiter F&E Bautenschutz IV

Löningen, 09.03.2021
 (place and date of issue)



(signature)