



## Declaration of performance

according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

## Declaration of conformity

according Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359

<b>for the product</b>	<b>FL fix</b> [basic]
<b>No.</b>	<b>GBI-P 93-2</b>
<b>Unique identification code of the product-type</b>	2859
<b>Intended use/es</b>	Cementitious mortar for elevated requirements with reduced slippage and extended open time
<b>Manufacturer</b>	Remmers GmbH Bernhard-Remmers-Str. 13 49624 Lönningen (DE)
<b>System/s of AVCP</b>	<b>System 3</b> (for internal and external uses) <b>System 3</b> (for uses subject to reaction to fire regulations)
<b>Harmonised standard</b>	EN 12004-1: 2017-05
<b>Notified body/ies</b>	Materialprüfanstalt (MPA) Braunschweig Beethovenstr. 52, 38106 Braunschweig Notified Body No 0761

**Declared performances:**

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Reaction to fire:	class E	System 3	EN 12004: 2017-05
Initial adhesive pull strength	≥ 1,0 MPa (C 2)		
Tensile adhesion strength after water immersion	≥ 1,0 MPa (C 2)		
Tensile adhesion strength after thermal ageing	≥ 1,0 MPa (C 2)		
Tensile adhesion strength after heat freeze and thaw cycles	≥ 1,0 MPa (C 2)		
Open time: tensile adhesion strength	≥ 0,5 MPa		
Extended open time: tensile adhesion strength	≥ 0,5 MPa		
Slipping:	≤ 0,5 mm		



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance & conformity is issued, in accordance with Regulation (EU) No 305/2011 and Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

**Remmers GmbH**  
R & D Building protection IV

.....  
i.V. Dr. Amir Asgharzadeh  
(Department manager)

.....  
i.A. Peter Murawski  
(Laboratory staff)

**The declaration of performance was created electronically and is also valid without signature.**

Löningen, 2024-02-08