

# DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

Name of the product  
**FL fix rapid**  
**Nr. GBI-P 94**  
**EN 12004 C2 FTE S1**

Unique identification code of the product-type:

**2866**

Intended use/es:

**Cementitious mortar for elevated requirements with reduced  
slippage and extended open time**

Manufacturer:

**Remmers GmbH**  
**Bernhard-Remmers-Straße 13**  
**49624 Lönningen / Germany**

System/s of AVCP:

**System 3** (for internal and external uses)  
**System 3** (for reaction to fire regulations)

Harmonised standard:

**EN 12004: 2017-05**

Notified body/ies:

**IBMB MPA**  
**Materialprüfanstalt (MPA) Braunschweig**  
**Beethovenstr. 52**  
**38106 Braunschweig / Germany**  
**Identification number 0761**

has conducted the type testing of the product and the following is  
displayed: **test report no. 1203/048/21**

Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Reaction to fire:	class E	System 3	EN 12004: 2017-05
Initial tensile adhesion strength	≥ 1,0 MPa (C2)		
Tensile adhesion strength after water immersion	≥ 1,0 MPa (C2)		
Tensile adhesion strength after thermal aging	≥ 1,0 MPa (C2)		
Tensile adhesion strength after heat freeze/thaw cycles	≥ 1,0 MPa (C2)		
Open time: tensile adhesion strength	≥ 0,5 MPa		
Extended open time: tensile adhesion strength	≥ 0,5 MPa		
Slipping	≤ 0,5 mm		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Remmers GmbH**  
**i.V. Dirk Wöltering, Bereichsleiter F&E Bautenschutz IV**

Löningen, 30.04.2021  
(place and date of issue)

  
 .....  
 (signature)