



## Declaration of performance



according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

## Declaration of conformity

according Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359

<b>for the product</b>	<b>MultiSil</b> (Variants: 027378-027382, 027385-027389, 027390-027392, 027395)
<b>No.</b>	<b>GBI F 040-4</b>
<b>Unique identification code of the product-type</b>	7380
<b>Intended use/es</b>	<p><b>EN 15651-1: F-EXT-INT-CC:</b> Sealant for facade for interior and exterior application (intended for use in cold climates)</p> <p><b>EN 15651-2: G-CC:</b> Sealant used for sealing glazing applications (intended for use in cold climates)</p> <p><b>EN 15651-3:S:</b> Sealant for joints for application in sanitary areas</p> <p><b>EN 15651-4: PW-EXT-INT-CC:</b> Sealant for movement joints in floors for interior and exterior application (intended for use in cold climates)</p>
<b>Manufacturer</b>	<p>Remmers GmbH Bernhard-Remmers-Str. 13 49624 Lönigen (DE)</p> <p><b>Distributor UKCA:</b> Remmers (UK) Limited 1 &amp; 2 Garden Suites, Coleshill Manor Campus, Birmingham B46 1DL (GB)</p>
<b>System/s of AVCP</b>	<b>System 3</b> (for uses subject to reaction to fire regulations)
<b>Harmonised standard</b>	<p>EN 15651-1:2012 EN 15651-2:2012 EN 15651-3:2012 EN 15651-4:2012</p>
<b>Notified body/ies</b>	<p>SKZ-Testing GmbH Friedrich-Bergius-Ring 22, 97076 Würzburg Notified Body 1213</p>

Conditioning: Method B  
Substrate: Mortar M1/ glass  
Pre-treatment: Glass without pre-treatment



Declared performance/s:

Essential characteristics	Performance	System zur System of assessment and verification of constancy of performance	Harmonised Technical specification
Reaction to fire	Class B-s1, d0	System 3	EN 15651-1:2012 EN 15651-2:2012 EN 15651-3:2012 EN 15651-4:2012
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 10 %		
Tensile behavior (i.e. elongation behavior) after pre-tensioning after immersion	NF		
Adhesion/cohesion properties after exposure to heat, water and artificial light	NF		
Elastic recovery	≥ 60 %		
Tensile properties at maintained extension	NF		
Tear resistance	NF		
Haft-/ Adhesion/cohesion properties at maintained extension after 28 days water immersion	NF		
Tensile properties (i.e. secant modulus) at -30°C	≤ 0,9 MPa		
Tensile properties (i.e. at maintained extension) at -30°C	NF		
Microbiological growth	1		
Durability	passed		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance & conformity is issued, in accordance with Regulation (EU) No 305/2011 and Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

**Remmers GmbH**  
R & D Building protection I

.....  
i.A. Ralf Janknecht  
(Department Manager)

.....  
i.A. Matthias Mählmann  
(Technician)

The declaration of performance was created electronically and is also valid without signature.

Löningen, 2023-10-27