

## **DECLARATION OF PERFORMANCE**

according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

## **DECLARATION OF CONFORMITY**

according Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359

Name of the product

**MultiSil NUW**

No. GBI F 041-3

Unique identification code of the product-type:

**7525**

Intended use/es:

**Sealant for facade for interior and exterior application (intended for use in cold climates) - EN 15651-1: F-EXT-INT-CCM;**

**Sealant for joints for application in sanitary areas - EN 15651-3: S;**

**Sealant for movement joints in floors for interior and exterior application (intended for use in cold climates) - EN 15651-4: PW-EXT-INT-CC**

Manufacturer:

**Remmers GmbH  
Bernhard-Remmers-Str. 13  
49624 Lönningen / Germany**

**Distributor UKCA:**

**Remmers (UK) Limited, Unit 4, Lloyds Court, Manor Royal Crawley,  
RH10 9QU**

System/s of AVCP:

**System 3**

**System 3 for reaction to fire**

Harmonised standard:

**EN 15651-1: 2012**

**EN 15651-3: 2012**

**EN 15651-4: 2012**

Notified body/ies:

**Kiwa Polymer Institut GmbH**  
**Quellenstraße 3**  
**65439 Flörsheim-Wicker/Germany**  
**Notified Body 1119**

Declared performance/s:

Conditioning: Method A

Substrate: Mortar M1/ glass

Pre-treatment: Glass without pre-treatment / Mortar M1 with Silicone Primer P

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012 EN 15651-3:2012 EN 15651-4:2012
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 10 %		
Tensile properties at maintained extension	NF		
Tensile properties at maintained extension after water immersion	NF		
Tensile properties (i.e. elongation) after immersion in water at 23°C	≥ 25 %		
Tensile properties (i.e. secant modulus) at -30°C	≤ 0,9 MPa		
Tensile properties (i.e. at maintained extension) at -30°C	NF		
Tear resistance	NF		
Adhesion/cohesion properties at maintained extension after 28 days water immersion	NF		
Adhesion/cohesion properties at maintained extension after 28 days salt water immersion	NF		
Microbiological growth	2		
Durability	passed		


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance and conformity is issued, in accordance with Regulation (EU) No 305/2011 and Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Remmers GmbH**  
F&E Bautenschutz I

Löningen, den 19/12/2022  
(place and date of issue)

  
.....  
i. V. Dr. Markus Boos  
(Senior Manager)

  
.....  
ppa. Carsten Nagel  
(Director R&D)