



Declaration of performance

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

Declaration of conformity

according Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359

for the product	SP Top rapid
No.	GBI-P 48-4
Unique identification code of the product-type	0404
Intended use/es	Designed rendering/plastering mortar used on moist masonry walls containing water soluble salts
Manufacturer	Remmers GmbH Bernhard-Remmers-Str. 13 49624 Lönningen (DE) Distributor UKCA: Remmers (UK) Limited 1 & 2 Garden Suites, Coleshill Manor Campus, Birmingham B46 1DL (GB)
System/s of AVCP	System 4 (for internal and external uses, in walls, columns + partitions) System 4 (for reaction to fire regulations)
Harmonised standard	EN 998-1: 2017-02
Notified body/ies	not relevant

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire class:	A1	System 4	EN 998-1: 2017-02
Adhesion:	≥ 0,08 N/mm ² (fracture pattern B)		
Water absorption:	≥ 0,3 kg/m ² after 24 h		
Water vapour permeability (μ):	≤ 15		
Thermal conductivity (λ _{10,dry,mat}) for P = 50 %	≤ 0,27 W/(mK) (tab. value EN 1745)		
Durability (against freeze-thaw):	Resistant, by use acc. TDS		
Dangerous substances:	NPD		



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance & conformity is issued, in accordance with Regulation (EU) No 305/2011 and Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Remmers GmbH
R & D Building protection IV

.....
i.V. Dr. Magnus Greiwe
(Department manager)

.....
i.A. Thomas Anneken
(Laboratory staff)

The declaration of performance was created electronically and is also valid without signature.

Löningen, 2024-03-28