



## Declaration of performance

according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

<b>for the product</b>	<b>WP Sulfatex rapid</b>
<b>No.</b>	<b>GBI-P 143</b>
<b>Unique identification code of the product-type</b>	0429
<b>Intended use/es</b>	Lightweight rendering / plastering mortar LW (CS II)
<b>Manufacturer</b>	Remmers GmbH Bernhard-Remmers-Str. 13 49624 Lönigen (DE)
<b>System/s of AVCP</b>	<b>System 4</b> (for internal and external uses, in walls, columns + partitions) System 4 (for reaction to fire regulations)
<b>Harmonised standard</b>	EN 998-1: 2017-02
<b>Notified body/ies</b>	Not relevant

**Declared performance/s:**

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire class:	B2 or E	System 4	EN 998-1: 2017-02
Adhesion	≥ 0,5 N/mm <sup>2</sup> (fracture pattern B)		
Water absorption	W <sub>c2</sub>		
Water vapour permeability (μ)	≤ 200		
Thermal conductivity (λ <sub>10, dry, mat.</sub> ) for P = 50%	1,11 W/(m*K)		
Durability (against freeze-thaw)	≥ 0,5 N/mm <sup>2</sup> (fracture pattern B)		
Dangerous substances	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

**Remmers GmbH**  
R & D Building protection I

.....  
i.V. Dr. Magnus Greiwe  
(Department manager)

.....  
i.A. Maren Jeske-Marquardt  
(Laboratory staff)

**The declaration of performance was created electronically and is also valid without signature.**

Lönigen, 2025-03-21

