





Declaration of performance

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

for the product	MB Fix 2K		
No.	GBI-P 123		
Unique identification code of the product-type	0855		
Intended use/es	Designed rendering/plastering mortar without special characteristics		
Manufacturer	Remmers GmbH Bernhard-Remmers-Str. 13 49624 Löningen (DE)		
System/s of AVCP	System 4 (for internal and external uses, in walls, columns + partitions) System 4 (for reaction to fire regulations)		
Harmonised standard	EN 998-1: 2017-02		
Notified body/ies	not relevant		

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire class:	E	System 4	EN 998-1: 2017-02
Adhesion:	≥ 0.3 N/mm² (fracture pattern B)		
Capillary water absorption:	approx. 0.13 kg/(m ² *h ^{0,5})		
Water vapour permeability (Sd):	approx. 0,67 m		
Thermal conductivity $(\lambda_{10,dry, mat})$	≤ 0.14 W/(m*K)		
for P = 50 %	(Table value acc. EN 1745)		
Durability (against freeze-thaw):	Resistant, by use acc. TDS		
Dangerous substances:	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by



The declaration of performance was created electronically and is also valid without signature.

Löningen, 2024-12-13





0855 DoP-4 12/24 HNo_ArM_DiM 2/2