



Declaration of performance

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

for the product	FM TK PH Variants: 1018, 1024
No.	GBI-P 39-5
Unique identification code of the product-type	1024
Intended use/es	Designed general purpose masonry mortar for internal and external use in elements subject to structural requirements
Manufacturer	Remmers GmbH Bernhard-Remmers-Str. 13 49624 Lönigen (DE)
System/s of AVCP	System 2+ (for internal and external uses, in walls, columns and partitions) System 4 (for reaction to fire regulations)
Harmonised standard	EN 998-2: 2016-11
Notified body/ies	GG-CERT e.V., Annastraße 67-71, 50968 Köln, Notified Body 0785

Certificate of conformity of the factory production control: **0785 - CPR - 21 - 104 - 13**

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Compressive strength:	M5	System 2+	EN 998-2: 2016-11
Bond strength:	≥ 0,08 N/mm ² (Characteristic initial shear strength (adhesive shear strength) tested acc. to EN 1052-3 (method B) in conjunction with sand-lime brick acc. to EN 771 at a moisture content of 3-7 M-%)		
Contents of chlorides:	≤ 0,01 M-%		
Water absorption:	≤ 0,10 kg/(m ² •min ^{0,5})		
Water vapour permeability (μ):	15/35 (tab. value EN 1745)		
Thermal conductivity (λ _{10,dry,mat}) for P = 50 %	≤ 0,82 W/(m•K) (tab. value EN 1745)		
Thermal conductivity (λ _{10,dry,mat}) for P = 90 %	≤ 0,89 W/(m•K) (tab. value EN 1745)		
Durability (against freeze-thaw):	Resistant, by use acc. TDS		
Reaction to fire class:	A1 (System 4)		
Dangerous substances:	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.



Signed for and on behalf of the manufacturer by

Remmers GmbH
R & D Building protection IV

.....
i.V. Dr. Magnus Greiwe
(Department manager)

.....
i.A. Thomas Anneken
(Laboratory staff)

The declaration of performance was created electronically and is also valid without signature.

Löningen, 2024-05-21