



Declaration of performance

according Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/2014

for the product	FM Hanse B-Fill		
No.	GBI-P 27-1		
Unique identification code of the product-type	1451		
Intended use/es	Designed general purpose masonry mortar for internal and external use in elements subject to structural requirements		
Manufacturer	Remmers GmbH Bernhard-Remmers-Str. 13 49624 Löningen (DE)		
System/s of AVCP	System 2+ (for internal and external uses, in walls, columns and partitions) System 4 (for reaction to fire regulations)		
Harmonised standard	EN 998-2: 2016-11		
Notified body/ies	GG-CERT e.V., Annastraße 67-71, 50968 Köln, Notified Body 0785		

Certificate of conformity of the factory production control 0785-CPR-21-104-13

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Compressive strength:	M5		EN 998-2: 2016-11
Bond strength:	≥ 0,08 N/mm ² (Characteristic initial shear strength (adhesive shear strength) tested acc. to EN 1052-3 (method B) in conjunction with sand-lime brick acc. to EN 771 at a moisture content of 3-7 M-%)	System 2+	
Contents of chlorides:	≤ 0,1 M-%		
Water absorption:	≤ 0.70 kg/(m²•min ^{0,5})		
Water vapour permeability (µ):	15/35 (tab. value EN 1745)		
Thermal conductivity $(\lambda_{10,dry,mat})$ for P = 50 %	≤ 0.82 W/(m∙K) (tab. value EN 1745)		
Thermal conductivity $(\lambda_{10,dry,mat})$ for P = 90 %	≤ 0.92 W/(m•K) (tab. value EN 1745)		
Durability (against freeze-thaw):	Resistant, by use acc. TDS		
Reaction to fire class:	A1 (System 4)		
Dangerous substances:	NPD		

Declaration of performance Product number 1451





The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Remmers GmbH

R & D Building protection IV

i.V. Dr. Magnus Greiwe (Department manager) i.A. Thomas Anneken (Laboaratory staff)

The declaration of performance was created electronically and is also valid without signature.

FM HANSE B-FILL

Löningen, 2024-05-10