



Declaration of performance

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

Declaration of conformity

according Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359

for the product	Epoxy BS 4000
No.	GBIII 058_5
Unique identification code of the product-type	6320
Intended use/es	<p>EN 1504-2: Surface protection products – Coating Protection against ingress (1.3) Physical resistance (5.1) Resistance to chemicals (6.1)</p> <p>EN 13813: Synthetic resin screed for internal uses</p>
Manufacturer	<p>Remmers GmbH Bernhard-Remmers-Str. 13 49624 Lönningen (DE)</p> <p>Distributor UKCA: Remmers (UK) Limited 1 & 2 Garden Suites, Coleshill Manor Campus, Birmingham B46 1DL (GB)</p>
System/s of AVCP	<p>EN 1504-2: System 2+ (for uses in buildings and civil engineering works) System 3 (for uses subject to reaction to fire regulations)</p> <p>EN 13813: System 4 (for internal uses)</p>
Harmonised standard	<p>EN 13813:2002 EN 1504-2:2004</p>
Notified body/ies	<p>Kiwa Polymer Institut GmbH Quellenstraße 3, 65439 Flörsheim-Wicker Notified Body 1119</p> <p>TFI Aachen GmbH Notified Body 1658</p> <p>British Board of Agrément 1st Floor Buliding 3, Hatters Lane, Croxley Park, Watford, WD 18 8YG Approved Body No 0836</p>



EN 1504-2:

The product is used in the surface protection systems :

Remmers Deck OS 8 WD / WD-LE:

consisting of components: Epoxy BS 4000 - Epoxy BS 3000 SG or Epoxy BS 3000 M

Table 1: Performance in the systems Remmers Deck OS 8 WD / WD-LE

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Linear shrinkage	NPD	System 2+	EN 1504-2:2004
Compressive strength	NPD		
Coefficient of thermal expansion	NPD		
Abrasion resistance	weight loss < 3000 mg		
Cross cut	NPD		
Permeability to CO2	s _D > 50 m		
Water vapour permeability	class II		
Capillary absorption and permeability to water	w < 0.1 kg/(m ² x h ^{0.5})		
Thermal compatibility	≥ 2.0 (1.5) ¹⁾ N/mm ²		
Resistance to thermal shock	NPD		
Chemical resistance	NPD		
Resistance to severe chemical attack	reduction in hardness < 50 %		
Crack bridging ability	NPD		
Impact resistance	class I		
Adhesion strength by pull off test	≥ 2.0 (1.5) ¹⁾ N/mm ²		
Reaction to fire	class B _{fl} -s1	System 3	
Skid resistance	class III	System 2+	
Artificial weathering	NPD		
Antistatic behaviour	NPD		
Adhesion on wet concrete	NPD		
Release of dangerous substances	NPD		

¹⁾ The value in brackets is the lowest accepted value of any reading



EN 13813:

Table 2: Performance according to EN 13813

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	E _{fi}	System 4	EN 13813:2002
Release of corrosive substances	SR		
Water permeability	NPD		
Wear resistance	≤ AR0.5		
Bond strength	≥ B1.5		
Impact resistance	≥ IR4		
Sound insulation	NPD		
Sound absorption	NPD		
Thermal resistance	NPD		
Chemical resistance	NPD		

Appropriate Technical Documentation and/or Specific Technical Documentation:

Appropriate Technical Documentation: **No. 6320-058**

Performance without further testing: **reaction to fire class E_{fi}**

Fulfilled requirements:

Maximum layer thickness: 10 mm

Organic content: < 75 % in weight

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance & conformity is issued, in accordance with Regulation (EU) No 305/2011 and Statutory Instruments (UK) 2019 No. 465; 2020 No. 1359 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Remmers GmbH
R&D Floor Coatings

.....
i. V. Dr. Ralph Bergs
(Department Manager)

.....
i. A. Sandra Funke
(Technican)

The declaration of performance was created electronically and is also valid without signature.

Löningen, 2025-01-07