



## Declaration of performance

according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

<b>for the product</b>	<b>IR Epoxy 360</b>
<b>No.</b>	<b>GBIII 088_3</b>
<b>Unique identification code of the product-type</b>	6872
<b>Intended use/es</b>	Concrete crack fillers Injection of concrete components for the frictional filling of cracks, cavities and defects U (F1) W (2) (1) (8/30) (1)
<b>Manufacturer</b>	Remmers GmbH Bernhard-Remmers-Str. 13 49624 Lönigen (DE)
<b>System/s of AVCP</b>	<b>System 2+</b> (for uses in buildings and civil engineering works)
<b>Harmonised standard</b>	EN 1504-5:2024
<b>Notified body/ies</b>	Materialprüfanstalt (MPA) Braunschweig Beethovenstr. 52, 38106 Braunschweig Notified Body No 0761

**Performance according to EN 1504-5:**

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Adhesion through adhesive strength	> 2 N/mm <sup>2</sup>	System 2+	EN 1504-5:2004
Adhesion through oblique shear strength	NPD		
Linear shrinkage	< 3 %		
Glass transition temperature	> 40 °C		
Injectability in dry medium	filling grade > 95 % adhesion with crack width 0.2 mm		
Durability	cohesive failure in concrete		
Corrosion behavior	it is assumed that there are no corrosive effects		
Release of dangerous substances	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

**Remmers GmbH**  
R&D Floor Coatings



---

The declaration of performance was created electronically and is also valid without signature.

Löningen, 2024-12-16