



Epoxy Color Top

Pigmented roll-on coating or topcoat

Constituents

VOC content

48 g/l (in accordance with ASTM-D 2369, SCAQMD-RULE 1113)

Directive 2004/42/EC ("Decopaint" Directive)

EU limit value for the product (Cat. A/j): max. 500 g/l (2010).
This product contains < 500 g/l VOC.

SVHC as per Regulation 1907/2006/EC ("REACH")

Does not contain (<0.1%)

Heavy metals pursuant to VdL Guideline 01

Not contained as constitutive ingredients

Total solids (Deutsche Bauchemie test method)

compliant

Legal requirements

Construction Products Regulation

CE marking as per EN 13813:2002 present
CE marking according to EN 1504-2:2004 available

GISCODE

RE 90

Eco-labels, certificates, declarations

Food contact

Material is suitable for use as a floor coating in indirect contact with foodstuffs in food-processing establishments. This suitability was examined and tested by an independent external body in accordance with Regulation (EC) No. 1935/2004.

Suitability for use as per LEED

Category as per Credit IEQc4.2 - 2009:
Primers, Sealers and Undercoaters:
VOC-Limit: 100 g/l without water: compliant
Traffic coatings:
VOC limit: 100 g/l without water: compliant

[nh_zusaetzliche_info]

Sample EPD from Deutsche Bauchemie e.V. available: Products based on epoxy-resin, group 4 (EPD-DBC-20220177-IBF1-EN)

Production site

Remmers GmbH
Bernhard-Remmers-Straße 13
DE - 49624 Lönningen

24.09.2024 / DK