

Page 1/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 24.02.2023 Version number 14 (replaces version 13) Revision: 24.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name HK-Lasur 3in1 Grey-Protect

Article number: 2257, 2265, 2291, 2294

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Product category PC9a Coatings and paints, thinners, paint removers

Application of the substance / the mixture Coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH Remmers (UK) Limited Bernhard-Remmers-Str. 13 Unit 4 , Lloyds Court

D-49624 Löningen / Germany Manor Royal, Crawley – West Sussex RH10 9QU

Tel.: +49(0)5432/83-0 fon +44 (0) 1293 594 010 Fax: +49(0)5432/3985 fax +44 (0) 1293 594 037

Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS08

Signal word Danger

Hazard-determining components of labelling:

Alkanes, C10-13

hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics

Hazard statements

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2023 Version number 14 (replaces version 13) Revision: 24.02.2023

Trade name HK-Lasur 3in1 Grey-Protect

(Contd. of page 1)

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Attention please! This product may cause a self ignition of the material, such as brushes or textiles, if contaminated with the product. Those materials and textiles should be dipped into water after use and before waste treatment. Do not use this product in application cabins, if there are NC - or PUR-coatings are used too, because retarded self-ignitions are possible!

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:				
EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39- XXXX	Alkanes, C10-13 Asp. Tox. 1, H304, EUH066	≥30-<40%		
EC number: 920-360-0 Reg.nr.: 01-2119448343-41- XXXX	hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics Asp. Tox. 1, H304	≥20-<30%		
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17- XXXX	titanium dioxide Carc. 2, H351	≥2.5-<5%		
CAS: 55406-53-6 EINECS: 259-627-5 Index number: 616-212-00-7	3-iodo-2-propynyl butylcarbamate Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317	≥0.25-≤0.5%		
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60- XXXX	(2-methoxymethylethoxy)propanol substance with a Community workplace exposure limit	≥0.1-≤0.25%		

Additional information

Benzene content: < 0,1% Note P is applicable. It is not necessary to classify nor to mark the product as carcinogenic.

For the wording of the listed hazard phrases refer to section 16.

* SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation Seek medical treatment in case of complaints.

After skin contact If skin irritation continues, consult a doctor.

After eye contact Rinse opened eye for several minutes under running water.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 14 (replaces version 13) Printing date 24.02.2023 Revision: 24.02.2023

Trade name HK-Lasur 3in1 Grey-Protect

(Contd. of page 2)

After swallowing Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

To avoid dermatitis (skin inflammation), use skin cream.

symptomatic treatment

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Foam

Water spray jet

Water mist

5.2 Special hazards arising from the substance or mixture

May be released in case of fire

Carbon monoxide (CO)

Carbon dioxide

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Prevent from spreading (e.g. by confining or oil barrier).

This product may not be allowed to reach surface water because it is toxic to aquatic environments.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable containers.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Use only in well ventilated areas.

Information about protection against explosions and fires:

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and containers: No special requirements.

Information on storage in a common storage facility: Store away from food.

Further information about storage conditions:

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 14 (replaces version 13) Printing date 24.02.2023 Revision: 24.02.2023

Trade name HK-Lasur 3in1 Grey-Protect

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Com	Components with limit values that require monitoring at the workplace:				
CAS:	13463-67-7 titanium dioxide				
WEL	Long-term value: 10* 4** mg/m³ *total inhalable **respirable				
CAS:	CAS: 34590-94-8 (2-methoxymethylethoxy)propanol				
WEL	Long-term value: 308 mg/m³, 50 ppm Sk				

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Appropriate engineering controls No further data: see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.

Apply solvent-resistant skin protection preparation before beginning work.

Keep away from food, beverages and animal feed.

Wash hands before pauses and after work.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euigment is not required or the amount of the PPE can be adpated accordingly.

Respiratory equipment: Filter A/P2.

Hand protection

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Safety glasses recommended during refilling.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid

Colour: Different, according to dye

Odour: Solvent-like **Odour threshold:** Not determined. Melting point/freezing point: Not determined

Boiling point or initial boiling point and boiling

range Not determined **Flammability** Not applicable.

Lower and upper explosion limit

Lower: 0.6 Vol %

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 14 (replaces version 13) Printing date 24.02.2023 Revision: 24.02.2023

Trade name HK-Lasur 3in1 Grey-Protect

(Contd. of page 4)

Upper: 7.0 Vol % Flash point: > 60 °C Ignition temperature: not applicable **Decomposition temperature:** Not determined. Hq Not determined.

Viscosity:

Kinematic viscosity at 20 °C 16 +/-2 s (DIN 53211/4)

dvnamic: Not determined.

Solubility

Water: Not miscible or difficult to mix

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C: 0.85±0.03 g/cm³ Relative density Not determined. Vapour density Not determined.

9.2 Other information

Appearance:

Form: Liquid

Important information on protection of health

and environment, and on safety.

Explosive properties: Product is not explosive.

Solvent separation test < 3 % **VOC EU** < 400 g/l

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard

classes **Explosives** Void Flammable gases Void Void **Aerosols** Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void Oxidising solids Void Organic peroxides Void Corrosive to metals Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

Desensitised explosives

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions

Used empty containers may contain product gases which form explosive mixtures with air

Void

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

(Contd. on page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2023 Version number 14 (replaces version 13) Revision: 24.02.2023

Trade name HK-Lasur 3in1 Grey-Protect

(Contd. of page 5)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:			
Alkanes, C10-13			
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rat)	
Inhalative	LC50/4 h	>20 mg/l (rat)	

Skin corrosion/irritation: Based on available data, the classification criteria are not met. **Serious eye damage/irritation:** Based on available data, the classification criteria are not met.

Sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met. **STOT-single exposure:** Based on available data, the classification criteria are not met. **STOT-repeated exposure:** Based on available data, the classification criteria are not met.

Aspiration hazard: May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects Remark: Harmful to fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system, even in small

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if extremely small quantities leak into soil.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

Recommendation

Liquid material remains are to be disposed of at collection facilities for old varnishes.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2023 Version number 14 (replaces version 13) Revision: 24.02.2023

Trade name HK-Lasur 3in1 Grey-Protect

(Contd. of page 6)

SECTION 14: Transport information		
14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according to IMO instruments Not applicable.		
Transport/Additional information:	Not a hazardous good according to the above regulations.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed. REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Date of previous version: 25.05.2021 **Version number of previous version:** 13

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

Page 8/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.02.2023 Version number 14 (replaces version 13) Revision: 24.02.2023

Trade name HK-Lasur 3in1 Grey-Protect

(Contd. of page 7)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity - Category 3 Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3