

Remmers (UK) Limited

fon +44 (0) 1293 594 010

fax +44 (0) 1293 594 037

Unit 4, Lloyds Court

Page 1/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 7 (replaces version 6) Revision: 08.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name CEM rapid (Fast Cement)

Article number: 2834

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category PC9b Fillers, putties, plasters, modelling clay Application of the substance / the mixture Regulated set cement

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH Bernhard-Remmers-Str. 13 D-49624 Löningen / Germany Manor Royal, Crawley - West Sussex RH10 9QU Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985 Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage. STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

Flue dust, portland cement calcium hydroxide calcium oxide

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

Printing date 08.12.2022 Version number 7 (replaces version 6) Revision: 08.12.2022

Trade name CEM rapid (Fast Cement)

(Contd. of page 1)

H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

2.3 Other hazards low chromate content according to directive 2003/53 EG

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:				
CAS: 65997-15-1 EINECS: 266-043-4	cement Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥40-<50%		
CAS: 584-08-7 EINECS: 209-529-3 Reg.nr.: 01-2119532646-36- XXXX	potassium carbonate Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥2.5-<5%		
CAS: 68475-76-3 EINECS: 270-659-9 Reg.nr.: 01-2119486767-17- XXXX	Flue dust, portland cement Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥1-<2.5%		
CAS: 1305-62-0 EINECS: 215-137-3 Reg.nr.: 01-2119475151-45- XXXX	calcium hydroxide Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥1-<2.5%		
CAS: 1305-78-8 EINECS: 215-138-9 Reg.nr.: 01-2119475325-36- XXX	Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥1-<2.5%		

Additional information For the wording of the listed hazard phrases refer to section 16.

* SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation In case of unconsciousness bring patient into stable side position for transport.

After skin contact Wash immediately with water and soap and rinse thoroughly.

After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing Call a doctor immediately.

Information for doctor see item 3

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 7 (replaces version 6)

Trade name CEM rapid (Fast Cement)

(Contd. of page 2)

Revision: 08.12.2022

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents No special measures required.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid causing dust.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow to enter sewage system, surface or ground water.

6.3 Methods and material for containment and cleaning up:

Keep away from water.

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Thorough removal of dust.

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of dust.

Information about protection against explosions and fires: No special requirements.

7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and containers: No special requirements.

Information on storage in a common storage facility: none

Further information about storage conditions:

Store drv.

Protect from humidity and keep away from water.

Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Com	Components with limit values that require monitoring at the workplace:				
CAS:	CAS: 65997-15-1 cement				
WEL	Long-term value: 10* 4** mg/m³ *inhalable dust **respirable dust				
CAS: 1305-78-8 calcium oxide					
WEL	Short-term value: 4* mg/m³ Long-term value: 2 1* mg/m³ *respirable fraction				

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Observe Professional Association regulations.

Keep away from food, beverages and animal feed.

(Contd. on page 4)

Printing date 08.12.2022 Version number 7 (replaces version 6) Revision: 08.12.2022

Trade name CEM rapid (Fast Cement)

(Contd. of page 3)

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.

Respiratory equipment:

Particle-Filter P2

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Avoid contact with eyes. In case of eye contact, rinse immediately and thoroughly with water. Seek medical advice.

Tightly sealed safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Solid.

Colour: Grey
Odour: cement-like
Odour threshold: Not determined.

Melting point/freezing point: > 1000 °C

Boiling point or initial boiling point and boiling

range Not determined Flammability Not determined.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:Not applicableIgnition temperature:not applicableDecomposition temperature:Not determined.

pH (10 g/l) at 20 °C ca. 12

Viscosity:

Kinematic viscosity dynamic:Not applicable.
Not applicable.

Solubility

Water: Partly miscible
Partition coefficient n-octanol/water (log value) Not determined.
Vapour pressure: Not applicable.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022 Version number 7 (replaces version 6) Revision: 08.12.2022

Trade name CEM rapid (Fast Cement)

(Contd. of page 4)

	(Contd. of page 4)
Density and/or relative density	
Density:	Not determined
Relative density	Not determined.
Bulk apparent density at 20 °C	ca. 1.4 kg/dm3
Vapour density	Not applicable.
Particle characteristics	See item 3.
9.2 Other information	
Appearance:	
Form:	Powder
Important information on protection of health	
and environment, and on safety.	
Explosive properties:	Product is not explosive.
Solvent separation test	·
Organic solvents:	0.0 %
VOC EU	
Solid content:	100.0 %
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard	
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:				
CAS: 584-08-7 potassium carbonate				
Oral	LD50	>2,000 mg/kg (rat)		
Dermal	LD50	>2,000 mg/kg (rabbit)		

Printing date 08.12.2022 Version

Version number 7 (replaces version 6)

Trade name CEM rapid (Fast Cement)

(Contd. of page 5)

Revision: 08.12.2022

Inhalative LC50/4 h >5 mg/l (rat)

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye damage.

Sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met. **Reproductive toxicity:** Based on available data, the classification criteria are not met.

STOT-single exposure: May cause respiratory irritation.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

* SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes: Do not allow product to reach ground water, bodies of water or sewage system.

SECTION 13: Disposal considerations

Recommendation

Do not dispose of together with household garbage. Do not allow product to reach sewage system. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

17 01 01 concrete

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information

14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void
14.3 Transport hazard class(es)	
ADR, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR, IMDG, IATA	Void

(Contd. on page 7)

Printing date 08.12.2022

Version number 7 (replaces version 6)

Trade name CEM rapid (Fast Cement)

(Contd. of page 6)

Revision: 08.12.2022

	· · · · · · · · · · · · · · · · · · ·	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according to IMO instruments Not applicable.		
Transport/Additional information:	Not a hazardous good according to the above regulations.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations

Other regulations, limitations and prohibition ordinances

Corrosive properties are set free when worked with water; therefore experience is expected of the user and our notes on working are to be observed.

Professional Association Principles/Industrial Medicine regulations, e.g. principles of industrial medicine Occupational Safety Regulations.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Date of previous version: 29.01.2021 **Version number of previous version:** 6

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 8)

Page 8/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 7 (replaces version 6)

Trade name CEM rapid (Fast Cement)

(Contd. of page 7)

Revision: 08.12.2022

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3