

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2023

Version number 4 (replaces version 3)

Revision: 14.12.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **PUR IF-235-Isolierfüller**

Article number: 3218, 3219

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category PC9a Coatings and paints, thinners, paint removers

Application of the substance / the mixture Paint

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Remmers GmbH  
Bernhard-Remmers-Str. 13  
D-49624 Lönigen / Germany  
Tel.: +49(0)5432/83-0  
Fax: +49(0)5432/3985

Remmers (UK) Limited  
Unit 4 , Lloyds Court  
Manor Royal, Crawley – West Sussex RH10 9QU  
fon +44 (0) 1293 594 010  
fax +44 (0) 1293 594 037

##### Information department:

Product Safety department: Phone: +44 (0) 1293 594 010  
Email: sales@remmers.co.ukk

#### 1.4 Emergency telephone number:

National Poisons Information Service (NPIS):  
In England and Wales: NHS 111 - dial 111  
In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:  
within USA and Canada: 1-800-424-9300  
outside USA and Canada: 001-703-527-3887

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H336 May cause drowsiness or dizziness.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS02 GHS07

Signal word Warning

##### Hazard-determining components of labelling:

n-butyl acetate  
2-methoxy-1-methylethyl acetate

##### Hazard statements

H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.

(Contd. on page 2)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2023

Version number 4 (replaces version 3)

Revision: 14.12.2023

## Trade name **PUR IF-235-Isolierfüller**

(Contd. of page 1)

### Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P240 Ground and bond container and receiving equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### Additional information:

- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH208 Contains maleic anhydride, methyl methacrylate. May produce an allergic reaction.
- EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

**Determination of endocrine-disrupting properties** Not applicable.

## \* SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

**Description:** Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:		
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-XXXX	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	≥30-<40%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide substance with a Community workplace exposure limit	≥5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	≥5-<10%
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-XXXX	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-≤0.25%
CAS: 108-31-6 EINECS: 203-571-6 Index number: 607-096-00-9 Reg.nr.: 01-2119472428-31-XXXX	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥0.001 %	0.0002%

**Additional information** For the wording of the listed hazard phrases refer to section 16.

## \* SECTION 4: First aid measures

### 4.1 Description of first aid measures

**General information** Immediately remove any clothing soiled by the product.

**After inhalation** Seek medical treatment in case of complaints.

**After skin contact** Wash off immediately with water.

**After eye contact** Rinse opened eye for several minutes under running water.

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2023

Version number 4 (replaces version 3)

Revision: 14.12.2023

Trade name **PUR IF-235-Isolierfüller**

(Contd. of page 2)

**After swallowing** Seek immediate medical advice.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**  
symptomatic treatment**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents**CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.**For safety reasons unsuitable extinguishing agents** Water with a full water jet.**5.2 Special hazards arising from the substance or mixture**

Vapours are heavier than air and spread out over the ground. Ignition over greater distances is possible.

**5.3 Advice for firefighters****Protective equipment:** No special measures required.**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:** Do not allow to enter sewage system, surface or ground water.**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

**Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities****Storage****Requirements to be met by storerooms and containers:** No special requirements.**Further information about storage conditions:** Keep container tightly closed.**\* SECTION 8: Exposure controls/personal protection****8.1 Control parameters**

<b>Components with limit values that require monitoring at the workplace:</b>	
<b>CAS: 123-86-4 n-butyl acetate</b>	
WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
<b>CAS: 13463-67-7 titanium dioxide</b>	
WEL	Long-term value: 10* 4** mg/m <sup>3</sup> *total inhalable **respirable
<b>CAS: 108-65-6 2-methoxy-1-methylethyl acetate</b>	
WEL	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm Long-term value: 274 mg/m <sup>3</sup> , 50 ppm Sk

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2023

Version number 4 (replaces version 3)

Revision: 14.12.2023

Trade name **PUR IF-235-Isolierfüller**

(Contd. of page 3)

<b>CAS: 80-62-6 methyl methacrylate</b>	
WEL	Short-term value: 416 mg/m <sup>3</sup> , 100 ppm Long-term value: 208 mg/m <sup>3</sup> , 50 ppm
<b>CAS: 108-31-6 maleic anhydride</b>	
WEL	Short-term value: 3 mg/m <sup>3</sup> Long-term value: 1 mg/m <sup>3</sup> Sen

**Additional information:** The lists that were valid during compilation were used as a basis.

## 8.2 Exposure controls

**Appropriate engineering controls** No further data; see section 7.

**Individual protection measures, such as personal protective equipment**

### General protective and hygienic measures

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-site shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

### Respiratory equipment:

Respiratory protection if there is a risk of splashes/mist.

Filter A/P2.

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

### Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

Break through time: max. 240 min (DIN EN 374).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection** Tightly sealed safety glasses.

## \* SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

#### Physical state

Fluid

#### Colour:

According to product specification

#### Odour:

Solvent-like

#### Odour threshold:

Not determined.

#### Melting point/freezing point:

Not determined

#### Boiling point or initial boiling point and boiling range

120 °C

#### Flammability

Flammable.

#### Lower and upper explosion limit

#### Lower:

1.2 Vol % (CAS: 123-86-4 n-butyl acetate)

#### Upper:

7.5 Vol %

#### Flash point:

26 °C (CAS: 123-86-4 n-butyl acetate)

#### Auto-ignition temperature:

not applicable

#### Decomposition temperature:

Not determined.

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2023

Version number 4 (replaces version 3)

Revision: 14.12.2023

Trade name **PUR IF-235-Isolierfüller**

(Contd. of page 4)

<b>pH</b>	Not determined.
<b>Viscosity:</b>	
<b>Kinematic viscosity at 20 °C</b>	185 s (DIN 53211/4)
<b>dynamic:</b>	Not determined.
<b>Solubility</b>	
<b>Water:</b>	Not miscible or difficult to mix
<b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
<b>Vapour pressure at 20 °C:</b>	11.2 hPa (CAS: 123-86-4 n-butyl acetate)
<b>Density and/or relative density</b>	
<b>Density at 20 °C:</b>	1.3 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>9.2 Other information</b>	
<b>Appearance:</b>	
<b>Form:</b>	Fluid
<b>Important information on protection of health and environment, and on safety.</b>	
<b>Explosive properties:</b>	Product is not explosive. However, formation of dangerous explosive vapour/air mixtures is possible.
<b>Solvent separation test</b>	< 3 %
<b>VOC EU</b>	<600 g/l
<b>Change in condition</b>	
<b>Evaporation rate</b>	Not determined.
<b>Information with regard to physical hazard classes</b>	
<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	Flammable liquid and vapour.
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void
<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

## SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

**10.2 Chemical stability**

**Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions** No dangerous reactions known

**10.4 Conditions to avoid** No further relevant information available.

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:** No dangerous decomposition products known

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2023

Version number 4 (replaces version 3)

Revision: 14.12.2023

Trade name **PUR IF-235-Isolierfüller**

(Contd. of page 5)

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity:** Based on available data, the classification criteria are not met.

#### LD/LC50 values that are relevant for classification:

**CAS: 123-86-4 n-butyl acetate**

Oral	LD50	14,000 mg/kg (rat)
Inhalative	LC50/4 h	>21 mg/l (rat)

**Skin corrosion/irritation:** Based on available data, the classification criteria are not met.

**Serious eye damage/irritation:** Based on available data, the classification criteria are not met.

**Sensitisation:** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

**Carcinogenicity:** Based on available data, the classification criteria are not met.

**Reproductive toxicity:** Based on available data, the classification criteria are not met.

**STOT-single exposure:** May cause drowsiness or dizziness.

**STOT-repeated exposure:** Based on available data, the classification criteria are not met.

**Aspiration hazard:** Based on available data, the classification criteria are not met.

### 11.2 Information on other hazards

#### Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

### 12.1 Toxicity

**Aquatic toxicity:** No further relevant information available.

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

### 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

### 12.7 Other adverse effects

#### Additional ecological information:

**General notes:** Do not allow product to reach ground water, bodies of water or sewage system.

## SECTION 13: Disposal considerations

### Recommendation

Do not dispose of together with household garbage. Do not allow product to reach sewage system.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

#### European waste catalogue

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
-----------	---

### Uncleaned packaging:

#### Recommendation:

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

## SECTION 14: Transport information

### 14.1 UN number or ID number

**ADR, IMDG, IATA** UN1263

### 14.2 UN proper shipping name

**ADR** 1263 PAINT  
**IMDG, IATA** PAINT

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 14.12.2023

Version number 4 (replaces version 3)

Revision: 14.12.2023

Trade name **PUR IF-235-Isolierfüller**

(Contd. of page 6)

<b>14.3 Transport hazard class(es)</b>	
<b>ADR</b>	
	
<b>Class</b>	3 (F1) Flammable liquids.
<b>Label</b>	3
<hr/>	
<b>IMDG, IATA</b>	
	
<b>Class</b>	3 Flammable liquids.
<b>Label</b>	3
<b>14.4 Packing group</b>	
<b>ADR, IMDG, IATA</b>	III
<b>14.5 Environmental hazards:</b>	Not applicable.
<b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
<b>hazard identification number:</b>	30
<b>EMS Number:</b>	F-E,S-E
<b>Stowage Category</b>	A
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	
Not applicable.	
<b>Transport/Additional information:</b>	
<hr/>	
<b>ADR</b>	
<b>Limited quantities (LQ)</b>	5L
<b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>Transport category</b>	3
<b>Tunnel restriction code</b>	D/E
<hr/>	
<b>IMDG</b>	
<b>Limited quantities (LQ)</b>	5L
<b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Directive 2012/18/EU

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category** P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

**DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

(Contd. on page 8)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2023

Version number 4 (replaces version 3)

Revision: 14.12.2023

Trade name **PUR IF-235-Isolierfüller**

(Contd. of page 7)

**REGULATION (EU) 2019/1148****Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

**Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH071 Corrosive to the respiratory tract.

**Classification according to Regulation (EC) No 1272/2008** Calculation method**Department issuing data specification sheet:** Product Safety department / EHS**Date of previous version:** 08.02.2023**Version number of previous version:** 3**Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Resp. Sens. 1: Respiratory sensitisation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1A: Skin sensitisation – Category 1A
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1