

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 08.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **UMA-824-Universal-Metallhaft-Additiv**

Article number: 3249

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category PC9a Coatings and paints, thinners, paint removers

Application of the substance / the mixture Adhering additive

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH

Bernhard-Remmers-Str. 13

D-49624 Lönigen / Germany

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985

Remmers (UK) Limited

Unit 4 , Lloyds Court

Manor Royal, Crawley – West Sussex RH10 9QU

fon +44 (0) 1293 594 010

fax +44 (0) 1293 594 037

Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS):

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300

outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

iso-butanol

1-methoxy-2-propanol

2-aminoethanol

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 08.12.2022

Trade name **UMA-824-Universal-Metallhaft-Additiv**

(Contd. of page 1)

Hazard statements

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P243 Take action to prevent static discharges.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash thoroughly after handling.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.* **SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:		
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3	1-methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	≥70-≤85%
CAS: 78-83-1 EINECS: 201-148-0 Index number: 603-108-00-1 Reg.nr.: 01-2119484609-23-XXXX	iso-butanol Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥5-<10%
CAS: 141-43-5 EINECS: 205-483-3 Index number: 603-030-00-8 Reg.nr.: 01-2119486455-28-XXXX	2-aminoethanol Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limit: STOT SE 3; H335: C ≥ 5%	≥1-<2.5%
CAS: 1589-47-5 EINECS: 216-455-5 Index number: 603-106-00-0 Reg.nr.: 01-2119752454-37-XXXX	2-methoxypropanol Flam. Liq. 3, H226; Repr. 1B, H360D; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335	≥0.1-≤0.25%

Additional information For the wording of the listed hazard phrases refer to section 16.* **SECTION 4: First aid measures****4.1 Description of first aid measures****General information**

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

Immediately remove any clothing soiled by the product.

After inhalation

Take affected persons into the open air and position comfortably

In case of unconsciousness bring patient into stable side position for transport.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 08.12.2022

Trade name **UMA-824-Universal-Metallhaft-Additiv**

(Contd. of page 2)

After skin contact

Wash immediately with water and soap and rinse thoroughly.

Wash off immediately with water.

After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.**After swallowing**

Do not induce vomiting. In case of prolonged discomfort, see a doctor. If the patient is conscious, give water to drink.

4.2 Most important symptoms and effects, both acute and delayed

In case of prolonged/repeated exposure or in high concentrations:

Headache

Dizziness

nausea

Danger Long-term or repeated exposure may cause inflammation of the skin (dermatitis).**4.3 Indication of any immediate medical attention and special treatment needed**

symptomatic treatment

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents**

Foam

Water spray jet

Water mist

Dry extinguishing agents, carbon dioxide, sand or earth should only be used for small fires.

For safety reasons unsuitable extinguishing agents Water with a full water jet.**5.2 Special hazards arising from the substance or mixture**

May be released in case of fire

Carbon monoxide (CO)

Vapours are heavier than air and spread out over the ground. Ignition over greater distances is possible.

5.3 Advice for firefighters**Protective equipment:**

Wear self-contained breathing apparatus.

Wear full protective suit.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources

Use breathing protection against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow to enter the ground/soil.**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Use only in well ventilated areas.

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 08.12.2022

Trade name **UMA-824-Universal-Metallhaft-Additiv**

(Contd. of page 3)

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Storage****Requirements to be met by storerooms and containers:** Prevent any penetration into the ground.**Information on storage in a common storage facility:**

Do not store together with fire promoting and self-igniting materials as well as easily flammable solids.

Further information about storage conditions:

Store container in a well ventilated position.

Keep container tightly closed.

* **SECTION 8: Exposure controls/personal protection****8.1 Control parameters**

Components with limit values that require monitoring at the workplace:	
CAS: 107-98-2 1-methoxy-2-propanol	
WEL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
	Sk
CAS: 78-83-1 iso-butanol	
WEL	Short-term value: 231 mg/m ³ , 75 ppm Long-term value: 154 mg/m ³ , 50 ppm
CAS: 141-43-5 2-aminoethanol	
WEL	Short-term value: 7.6 mg/m ³ , 3 ppm Long-term value: 2.5 mg/m ³ , 1 ppm
	Sk

Additional information: The lists that were valid during compilation were used as a basis.**8.2 Exposure controls****Appropriate engineering controls** Use only in well-ventilated areas.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures**

Do not eat, drink or smoke while working.

Apply solvent-resistant skin protection preparation before beginning work.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-site shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

Respiratory equipment:

Filter A/P2.

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Hand protection

Solvent resistant gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 08.12.2022

Trade name **UMA-824-Universal-Metallhaft-Additiv**

(Contd. of page 4)

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.

Body protection: Protective work clothing.

* SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Fluid
Colour:	clear
Odour:	Solvent-like
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling range	Not determined
Flammability	Flammable.
Lower and upper explosion limit	
Lower:	1.5 Vol %
Upper:	13.7 Vol %
Flash point:	32 °C
Ignition temperature:	270 °C
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity at 20 °C	14 s (DIN 53211/4)
dynamic:	Not determined.
Solubility	
Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	13.3 hPa
Density and/or relative density	
Density at 20 °C:	0.95 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Explosive properties:	Product is not explosive. However, formation of dangerous explosive vapour/air mixtures is possible.
Solvent separation test	< 3 %
Organic solvents:	87.0 %
Change in condition	
Evaporation rate	Not determined.

Information with regard to physical hazard

classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 08.12.2022

Trade name **UMA-824-Universal-Metallhaft-Additiv**

(Contd. of page 5)

Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

Avoid: heat, flames, sparks

10.3 Possibility of hazardous reactions Reacts with strong oxidising agents

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

CAS: 107-98-2 1-methoxy-2-propanol

Oral	LD50	4,016 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	25.8 mg/l (rat)

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye damage.

Sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: May cause drowsiness or dizziness.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Experience with humans:

High concentrations may cause tiredness and dizziness.

Frequent or longer lasting skin contact may degrease and dry out skin which may lead to skin irritation and inflammation (dermatitis).

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 08.12.2022

Trade name **UMA-824-Universal-Metallhaft-Additiv**

(Contd. of page 6)

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects**Additional ecological information:****General notes:**

Do not allow undiluted or non-neutralised product to reach the sewage system or receiving waters.

Do not allow product to reach ground water, bodies of water or sewage system.

* **SECTION 13: Disposal considerations****Recommendation**

Do not dispose of together with household garbage. Do not allow product to reach sewage system.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances

Uncleaned packaging:**Recommendation:**

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

SECTION 14: Transport information**14.1 UN number or ID number**

ADR, IMDG, IATA

UN1263

14.2 UN proper shipping name

ADR

1263 PAINT

IMDG, IATA

PAINT

14.3 Transport hazard class(es)

ADR



Class

3 (F1) Flammable liquids.

Label

3

IMDG, IATA



Class

3 Flammable liquids.

Label

3

14.4 Packing group

ADR, IMDG, IATA

III

14.5 Environmental hazards:**Marine pollutant:**

No

14.6 Special precautions for user**hazard identification number:**

Warning: Flammable liquids.

30

EMS Number:

F-E,S-E

Stowage Category

A

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 08.12.2022

Trade name **UMA-824-Universal-Metallhaft-Additiv**

(Contd. of page 7)

14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

* SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

* SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H360D May damage the unborn child.
- H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008 Calculation method

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.12.2022

Version number 5 (replaces version 4)

Revision: 08.12.2022

Trade name UMA-824-Universal-Metallhaft-Additiv

(Contd. of page 8)

Department issuing data specification sheet: Product Safety department / EHS**Date of previous version:** 18.06.2019**Version number of previous version:** 4**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3