

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 4 (replaces version 3)

Revision: 09.12.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **NC HB-005 Wood Stain (mahogany, special colours)**

Article number: 3828; 3838

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category PC9a Coatings and paints, thinners, paint removers

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Remmers GmbH

Bernhard-Remmers-Str. 13

D-49624 Lönigen / Germany

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985

Remmers (UK) Limited

Unit 4 , Lloyds Court

Manor Royal, Crawley – West Sussex RH10 9QU

fon +44 (0) 1293 594 010

fax +44 (0) 1293 594 037

##### Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

#### 1.4 Emergency telephone number:

National Poisons Information Service (NPIS):

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300

outside USA and Canada: 001-703-527-3887

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS02 GHS07

Signal word Danger

##### Hazard-determining components of labelling:

1-methoxy-2-propanol

metal complex dye (contains chromium III)

n-butyl acetate

acetone

(Contd. on page 2)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 4 (replaces version 3)

Revision: 09.12.2022

## Trade name **NC HB-005 Wood Stain (mahogany, special colours)**

(Contd. of page 1)

Acid Brown 355

**Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**2.3 Other hazards****Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures****Description:** Mixture of the substances listed below with harmless additions.

| <b>Dangerous components [% w/w]:</b>   |  |          |
|--|--|----------|
| CAS: 107-98-2<br>EINECS: 203-539-1<br>Index number: 603-064-00-3                                   | 1-methoxy-2-propanol<br>Flam. Liq. 3, H226; STOT SE 3, H336                              | ≥40-<50% |
| CAS: 123-86-4<br>EINECS: 204-658-1<br>Index number: 607-025-00-1<br>Reg.nr.: 01-2119485493-29-XXXX | n-butyl acetate<br>Flam. Liq. 3, H226; STOT SE 3, H336, EUH066                           | ≥20-<30% |
| CAS: 67-64-1<br>EINECS: 200-662-2<br>Index number: 606-001-00-8<br>Reg.nr.: 01-2119471330-49-XXXX  | acetone<br>Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066               | ≥5-<10%  |
| CAS: 70236-62-3<br>EINECS: 274-492-2   | metal complex dye (contains chromium III)<br>Aquatic Chronic 2, H411; Skin Sens. 1, H317 | ≥5-<10%  |
| CAS: 9004-70-0<br>EC number: 682-719-5<br>Index number: 603-037-01-3                               | cellulose nitrate<br>Expl. 1.1, H201   | ≥2.5-<5% |

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 4 (replaces version 3)

Revision: 09.12.2022

## Trade name **NC HB-005 Wood Stain (mahogany, special colours)**

(Contd. of page 2)

|  |   |             |
|--|---|-------------|
| CAS: 64-17-5<br>EINECS: 200-578-6<br>Index number: 603-002-00-5<br>Reg.nr.: 01-2119457610-43-XXXX    | ethanol<br>Flam. Liq. 2, H225; Eye Irrit. 2, H319   | ≥2.5-<5%    |
| CAS: 13463-67-7<br>EINECS: 236-675-5<br>Index number: 022-006-00-2<br>Reg.nr.: 01-2119489379-17-XXXX | titanium dioxide<br>Carc. 2, H351   | ≥1-<2.5%    |
| CAS: 84989-26-4<br>EINECS: 284-915-2<br>Reg.nr.: 01-2120077343-57-XXXX                               | Acid Brown 355<br>Skin Sens. 1, H317; Aquatic Chronic 3, H412   | ≥0.5-<1%    |
| CAS: 67-63-0<br>EINECS: 200-661-7<br>Index number: 603-117-00-0<br>Reg.nr.: 01-2119457558-25-XXXX    | propan-2-ol<br>Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336  | ≥0.25-≤0.5% |
| CAS: 112-34-5<br>EINECS: 203-961-6<br>Index number: 603-096-00-8<br>Reg.nr.: 01-2119475104-44-XXXX   | 2-(2-butoxyethoxy)ethanol<br>Eye Irrit. 2, H319   | ≥0.25-≤0.5% |
| CAS: 28553-12-0<br>EINECS: 249-079-5<br>Reg.nr.: 01-2119430798-28-XXXX                               | diisononyl phthalate<br>substance with a Community workplace exposure limit   | ≥0.1-≤0.25% |
| CAS: 123-42-2<br>EINECS: 204-626-7<br>Index number: 603-016-00-1<br>Reg.nr.: 01-2119473975-21-XXXX   | 4-hydroxy-4-methylpentan-2-one<br>Eye Irrit. 2, H319; STOT SE 3, H335<br>Specific concentration limit:<br>Eye Irrit. 2; H319: C ≥ 10% | ≥0.1-≤0.25% |
| CAS: 1589-47-5<br>EINECS: 216-455-5<br>Index number: 603-106-00-0<br>Reg.nr.: 01-2119752454-37-XXXX  | 2-methoxypropanol<br>Flam. Liq. 3, H226; Repr. 1B, H360D; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335                      | ≥0.1-≤0.25% |

**Additional information** For the wording of the listed hazard phrases refer to section 16.

### \* SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General information

Immediately remove any clothing soiled by the product.

Immediately remove any clothing soiled by the product.

##### After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

##### After skin contact

Wash immediately with water and soap and rinse thoroughly.

Wash off immediately with water.

##### After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

**After swallowing** Seek immediate medical advice.

#### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 4 (replaces version 3)

Revision: 09.12.2022

Trade name **NC HB-005 Wood Stain (mahogany, special colours)**

(Contd. of page 3)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing agents

CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.**For safety reasons unsuitable extinguishing agents** Water with a full water jet.

### 5.2 Special hazards arising from the substance or mixture

Vapours are heavier than air and spread out over the ground. Ignition over greater distances is possible.

### 5.3 Advice for firefighters

**Protective equipment:** No special measures required.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

### 6.2 Environmental precautions:

Inform responsible authorities in case product reaches bodies of water or sewage system.

### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

#### Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

**Requirements to be met by storerooms and containers:** Store in cool location.

#### Further information about storage conditions:

Keep container tightly closed.

Store cool and dry in tightly closed containers.

## \* SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

| Components with limit values that require monitoring at the workplace: |   |
|--|---|
| <b>CAS: 107-98-2 1-methoxy-2-propanol</b>                              |   |
| WEL  | Short-term value: 560 mg/m <sup>3</sup> , 150 ppm   |
|  | Long-term value: 375 mg/m <sup>3</sup> , 100 ppm    |
|  | Sk  |
| <b>CAS: 123-86-4 n-butyl acetate</b>                                   |   |
| WEL  | Short-term value: 966 mg/m <sup>3</sup> , 200 ppm   |
|  | Long-term value: 724 mg/m <sup>3</sup> , 150 ppm    |
| <b>CAS: 67-64-1 acetone</b>  |   |
| WEL  | Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm |
|  | Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm   |
| <b>CAS: 64-17-5 ethanol</b>  |   |
| WEL  | Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm  |

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 4 (replaces version 3)

Revision: 09.12.2022

## Trade name **NC HB-005 Wood Stain (mahogany, special colours)**

(Contd. of page 4)

|   |  |
|---|--|
| <b>CAS: 13463-67-7 titanium dioxide</b>             |  |
| WEL   | Long-term value: 10* 4** mg/m <sup>3</sup><br>*total inhalable **respirable                            |
| <b>CAS: 67-63-0 propan-2-ol</b>                     |  |
| WEL   | Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm<br>Long-term value: 999 mg/m <sup>3</sup> , 400 ppm |
| <b>CAS: 112-34-5 2-(2-butoxyethoxy)ethanol</b>      |  |
| WEL   | Short-term value: 101.2 mg/m <sup>3</sup> , 15 ppm<br>Long-term value: 67.5 mg/m <sup>3</sup> , 10 ppm |
| <b>CAS: 28553-12-0 diisononyl phthalate</b>         |  |
| WEL   | Long-term value: 5 mg/m <sup>3</sup>   |
| <b>CAS: 123-42-2 4-hydroxy-4-methylpentan-2-one</b> |  |
| WEL   | Short-term value: 362 mg/m <sup>3</sup> , 75 ppm<br>Long-term value: 241 mg/m <sup>3</sup> , 50 ppm    |

**Additional information:** The lists that were valid during compilation were used as a basis.

### 8.2 Exposure controls

**Appropriate engineering controls** No further data; see item 7.

**Individual protection measures, such as personal protective equipment**

#### General protective and hygienic measures

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-site shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

#### Respiratory equipment:

In case vapours/aerosols develop:

Filter A/P2.

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

#### Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

Break through time: max. 240 min (DIN EN 374).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection** Tightly sealed safety glasses.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

**Physical state**

Fluid

**Colour:**

According to product specification

**Odour:**

Characteristic

**Odour threshold:**

Not determined.

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 4 (replaces version 3)

Revision: 09.12.2022

Trade name **NC HB-005 Wood Stain (mahogany, special colours)**

(Contd. of page 5)

|  |  |
|--|--|
| <b>Melting point/freezing point:</b>   | Not determined   |
| <b>Boiling point or initial boiling point and boiling range</b>                      | 55 °C  |
| <b>Flammability</b>  | Highly flammable.  |
| <b>Lower and upper explosion limit</b>   |  |
| <b>Lower:</b>  | 1.2 Vol % (CAS: 123-86-4 n-butyl acetate)  |
| <b>Upper:</b>  | 13.7 Vol % (CAS: 107-98-2 1-methoxy-2-propanol)  |
| <b>Flash point:</b>  | <21 °C   |
| <b>Ignition temperature:</b>   | 287 °C   |
| <b>Decomposition temperature:</b>  | Not determined.  |
| <b>pH</b>  | Not determined.  |
| <b>Viscosity:</b>  |  |
| <b>Kinematic viscosity at 20 °C</b>  | 40-60 s (ISO 3 mm)   |
| <b>dynamic:</b>  | Not determined.  |
| <b>Solubility</b>  |  |
| <b>Water:</b>  | Not miscible or difficult to mix   |
| <b>Partition coefficient n-octanol/water (log value)</b>                             | Not determined.  |
| <b>Vapour pressure at 20 °C:</b>   | 13.3 hPa (CAS: 107-98-2 1-methoxy-2-propanol)<br>12 hPa  |
| <b>Density and/or relative density</b>   |  |
| <b>Density at 20 °C:</b>   | 0.9-0.95 g/cm <sup>3</sup>   |
| <b>Relative density</b>  | Not determined.  |
| <b>Vapour density</b>  | Not determined.  |
| <b>9.2 Other information</b>   |  |
| <b>Appearance:</b>   |  |
| <b>Form:</b>   | Fluid  |
| <b>Important information on protection of health and environment, and on safety.</b> |  |
| <b>Explosive properties:</b>   | Product is not explosive. However, formation of dangerous explosive vapour/air mixtures is possible. |
| <b>Solvent separation test</b>   | < 3 %  |
| <b>Change in condition</b>   |  |
| <b>Evaporation rate</b>  | Not determined.  |
| <b>Information with regard to physical hazard classes</b>                            |  |
| <b>Explosives</b>  | Void   |
| <b>Flammable gases</b>   | Void   |
| <b>Aerosols</b>  | Void   |
| <b>Oxidising gases</b>   | Void   |
| <b>Gases under pressure</b>  | Void   |
| <b>Flammable liquids</b>   | Highly flammable liquid and vapour.  |
| <b>Flammable solids</b>  | Void   |
| <b>Self-reactive substances and mixtures</b>   | Void   |
| <b>Pyrophoric liquids</b>  | Void   |
| <b>Pyrophoric solids</b>   | Void   |
| <b>Self-heating substances and mixtures</b>  | Void   |
| <b>Substances and mixtures, which emit flammable gases in contact with water</b>     | Void   |
| <b>Oxidising liquids</b>   | Void   |
| <b>Oxidising solids</b>  | Void   |
| <b>Organic peroxides</b>   | Void   |
| <b>Corrosive to metals</b>   | Void   |
| <b>Desensitised explosives</b>   | Void   |

## SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 4 (replaces version 3)

Revision: 09.12.2022

## Trade name **NC HB-005 Wood Stain (mahogany, special colours)**

(Contd. of page 6)

### 10.2 Chemical stability

#### Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions** No dangerous reactions known

**10.4 Conditions to avoid** No further relevant information available.

**10.5 Incompatible materials:** No further relevant information available.

**10.6 Hazardous decomposition products:** No dangerous decomposition products known

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity:** Based on available data, the classification criteria are not met.

#### LD/LC50 values that are relevant for classification:

##### CAS: 107-98-2 1-methoxy-2-propanol

|            |          |                      |
|------------|----------|----------------------|
| Oral       | LD50     | 4,016 mg/kg (rat)    |
| Dermal     | LD50     | 2,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 25.8 mg/l (rat)      |

##### CAS: 123-86-4 n-butyl acetate

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | 14,000 mg/kg (rat) |
| Inhalative | LC50/4 h | >21 mg/l (rat)     |

**Skin corrosion/irritation:** Based on available data, the classification criteria are not met.

**Serious eye damage/irritation:** Causes serious eye irritation.

**Sensitisation:** May cause an allergic skin reaction.

**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

**Carcinogenicity:** Based on available data, the classification criteria are not met.

**Reproductive toxicity:** Based on available data, the classification criteria are not met.

**STOT-single exposure:** May cause drowsiness or dizziness.

**STOT-repeated exposure:** Based on available data, the classification criteria are not met.

**Aspiration hazard:** Based on available data, the classification criteria are not met.

### 11.2 Information on other hazards

#### Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

### 12.1 Toxicity

**Aquatic toxicity:** No further relevant information available.

**12.2 Persistence and degradability** No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

### 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

### 12.7 Other adverse effects

**Remark:** Harmful to fish

### Additional ecological information:

#### General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Harmful to aquatic organisms

## SECTION 13: Disposal considerations

### Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations.

Hardened product remains may be disposed of as building rubble or put into household garbage.

(Contd. on page 8)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 4 (replaces version 3)

Revision: 09.12.2022

## Trade name **NC HB-005 Wood Stain (mahogany, special colours)**

(Contd. of page 7)

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.



| European waste catalogue |   |
|--------------------------|---|
| 08 01 11*                | waste paint and varnish containing organic solvents or other hazardous substances |

**Uncleaned packaging:****Recommendation:**

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

### SECTION 14: Transport information

|   |   |
|---|---|
| <b>14.1 UN number or ID number</b><br>ADR, IMDG, IATA   | UN1263  |
| <b>14.2 UN proper shipping name</b><br>ADR<br>IMDG, IATA  | 1263 PAINT<br>PAINT   |
| <b>14.3 Transport hazard class(es)</b><br>ADR   |   |
|    |   |
| <b>Class</b>  | 3 (F1) Flammable liquids.   |
| <b>Label</b>  | 3   |
| <b>IMDG, IATA</b>   |   |
|    |   |
| <b>Class</b>  | 3 Flammable liquids.  |
| <b>Label</b>  | 3   |
| <b>14.4 Packing group</b><br>ADR, IMDG, IATA  | II  |
| <b>14.5 Environmental hazards:</b>  | Not applicable.   |
| <b>14.6 Special precautions for user</b><br><b>hazard identification number:</b><br><b>EMS Number:</b><br><b>Stowage Category</b> | Warning: Flammable liquids.<br>33<br>F-E,S-E<br>B   |
| <b>14.7 Maritime transport in bulk according to IMO instruments</b>   | Not applicable.   |
| <b>Transport/Additional information:</b>  |   |
| <b>ADR</b>  |   |
| <b>Limited quantities (LQ)</b>  | 5L  |
| <b>Excepted quantities (EQ)</b>   | Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml |
| <b>Transport category</b>   | 2   |
| <b>Tunnel restriction code</b>  | D/E   |
| <b>IMDG</b>   |   |
| <b>Limited quantities (LQ)</b>  | 5L  |

(Contd. on page 9)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 4 (replaces version 3)

Revision: 09.12.2022

Trade name **NC HB-005 Wood Stain (mahogany, special colours)**

(Contd. of page 8)

|                                 |   |
|---------------------------------|---|
| <b>Excepted quantities (EQ)</b> | Code: E2<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 500 ml |
| <b>UN "Model Regulation":</b>   | UN 1263 PAINT, 3, II  |

## \* SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Directive 2012/18/EU

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category** P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

#### **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

#### **REGULATION (EU) 2019/1148**

#### **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

#### **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

CAS: 67-64-1 | acetone

≥5-<10%

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## \* SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

### Relevant phrases

H201 Explosive; mass explosion hazard.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H360D May damage the unborn child.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

**Classification according to Regulation (EC) No 1272/2008** Calculation method

**Department issuing data specification sheet:** Product Safety department / EHS

**Date of previous version:** 17.06.2020

**Version number of previous version:** 3

### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 4 (replaces version 3)

Revision: 09.12.2022

**Trade name NC HB-005 Wood Stain (mahogany, special colours)**

(Contd. of page 9)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives – Division 1.1

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3