

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 6 (replaces version 5)

Revision: 09.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **ACRYL VSL-115-VARIO-SCHICHTLACK**

Article number: 3861-62

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Product category PC9a Coatings and paints, thinners, paint removers**Application of the substance / the mixture** Coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH

Bernhard-Remmers-Str. 13
D-49624 Lönningen / Germany

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985

Remmers (UK) Limited
Unit 4 , Lloyds Court
Manor Royal, Crawley – West Sussex RH10 9QU
fon +44 (0) 1293 594 010
fax +44 (0) 1293 594 037**Information department:**

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS):

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300

outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS02 GHS07 GHS08

Signal word Danger**Hazard-determining components of labelling:**

n-butyl acetate

hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

ethyl acetate

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 6 (replaces version 5)

Revision: 09.12.2022

Trade name **ACRYL VSL-115-VARIO-SCHICHTLACK**

(Contd. of page 1)

2-methoxy-1-methylethyl acetate

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statementsP210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.* **SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:		
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-XXXX	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	≥30-<40%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46-XXXX	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	≥20-<30%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-XXXX	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319	≥10-<20%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-XXXX	xylene Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	≥5-<10%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33-XXXX	hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	≥1-<2.5%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	≥1-<2.5%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 6 (replaces version 5)

Revision: 09.12.2022

Trade name **ACRYL VSL-115-VARIO-SCHICHTLACK**

(Contd. of page 2)

CAS: 28553-12-0 EINECS: 249-079-5 Reg.nr.: 01-2119430798-28-XXXX	diisononyl phthalate substance with a Community workplace exposure limit	≥0.5-≤1%
--	---	----------

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

Immediately remove any clothing soiled by the product.

After inhalation Seek medical treatment in case of complaints.

After skin contact

Remove contaminated clothing.

Do not use solvents or thinners!

Wash off immediately with water.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing Keep the person affected quiet.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

For safety reasons unsuitable extinguishing agents Water with a full water jet.

5.2 Special hazards arising from the substance or mixture

Thick black smoke forms in fires. Inhalation of dangerous decomposition products may cause serious damage to your health.

Formation of poisonous gases during heating or in fires.

Vapours are heavier than air and spread out over the ground. Ignition over greater distances is possible.

5.3 Advice for firefighters

Protective equipment: Put on breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Ensure adequate ventilation

Put on breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Clean preferably with a cleaning agent, do not use solvents if possible.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 6 (replaces version 5)

Revision: 09.12.2022

Trade name **ACRYL VSL-115-VARIO-SCHICHTLACK**

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes.

Avoid exposure by inhalation.

Ensure good ventilation, if necessary extract air in work places.

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

Information about protection against explosions and fires:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep breathing equipment ready.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers:

Electrical facilities must be explosion protected according to standards. Floors must be electrically conductive.

Store in cool location.

Information on storage in a common storage facility:

Keep away from highly acidic and alkaline materials as well as oxidizing agents.

Further information about storage conditions:

Store between 15 and 30°C.

Store container in a well ventilated position.

Store dry.

Keep container tightly closed.

Store cool and dry in tightly closed containers.

* SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:	
CAS: 123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
CAS: 141-78-6 ethyl acetate	
WEL	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
CAS: 64-17-5 ethanol	
WEL	Long-term value: 1920 mg/m ³ , 1000 ppm
CAS: 1330-20-7 xylene	
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
CAS: 108-65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
CAS: 28553-12-0 diisononyl phthalate	
WEL	Long-term value: 5 mg/m ³
Ingredients with biological limit values:	
CAS: 1330-20-7 xylene	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

Additional information: The lists that were valid during compilation were used as a basis.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 6 (replaces version 5)

Revision: 09.12.2022

Trade name **ACRYL VSL-115-VARIO-SCHICHTLACK**

(Contd. of page 4)

8.2 Exposure controls**Appropriate engineering controls** No further data; see item 7.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures**

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Store protective clothing separately.

Do not inhale gases / vapours / aerosols.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-site shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

Respiratory equipment:

If the solvent / dust concentration is above TLV-values, respiratory equipment admitted for this purpose must be worn.

Filter A/P2.

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Hand protection

Solvent resistant gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

if there is a risk of splashes

Tightly sealed safety glasses.

Body protection:

Wear anti-static clothing made of natural fibres (cotton) or heat resistant synthetic fibres. After contact with skin, wash thoroughly.

* SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Physical state**

Fluid

Colour:

Cloudy

Odour:

Pungent

Odour threshold:

Not determined.

Melting point/freezing point:

Not determined

Boiling point or initial boiling point and boiling range

76 °C

Flammability

Highly flammable.

Lower and upper explosion limit**Lower:**

1.1 Vol %

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 6 (replaces version 5)

Revision: 09.12.2022

Trade name **ACRYL VSL-115-VARIO-SCHICHTLACK**

(Contd. of page 5)

Upper:	15 Vol %
Flash point:	-4 °C
Ignition temperature:	370 °C
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity at 20 °C	20 s (DIN 53211/4)
dynamic:	Not determined.
Solubility	
Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	100 hPa <1100 hPa
Density and/or relative density	
Density at 20 °C:	0.91 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Explosive properties:	Product is not explosive. However, formation of dangerous explosive vapour/air mixtures is possible.
Solvent separation test	< 3 % (ADR)
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 6 (replaces version 5)

Revision: 09.12.2022

Trade name **ACRYL VSL-115-VARIO-SCHICHTLACK**

(Contd. of page 6)

10.6 Hazardous decomposition products:

At high temperatures, the following may occur:
Carbon monoxide and carbon dioxide
smoke
Nitrogen oxides (NO_x)

* **SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:		
CAS: 123-86-4 n-butyl acetate		
Oral	LD50	14,000 mg/kg (rat)
Inhalative	LC50/4 h	>21 mg/l (rat)
CAS: 141-78-6 ethyl acetate		
Oral	LD50	4,935 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (rat)
CAS: 64-17-5 ethanol		
Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)

Skin corrosion/irritation:

Dries skin out.

May cause irritation.

Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Causes serious eye irritation.

Sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: May cause drowsiness or dizziness.

STOT-repeated exposure: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard: Based on available data, the classification criteria are not met.

Additional toxicological information:

Prolonged or repeated contact with the product impairs natural oiling of the skin and leads to dry skin.

The product can be absorbed by the body through the skin.

11.2 Information on other hazards

Endocrine disrupting properties
None of the ingredients is listed.

SECTION 12: Ecological information**12.1 Toxicity**

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects**Additional ecological information:****General notes:**

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 6 (replaces version 5)

Revision: 09.12.2022

Trade name **ACRYL VSL-115-VARIO-SCHICHTLACK**

(Contd. of page 7)

* SECTION 13: Disposal considerations

Recommendation

Liquid material remains are to be disposed of at collection facilities for old varnishes.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue



08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances

Uncleaned packaging:**Recommendation:**

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

SECTION 14: Transport information

14.1 UN number or ID number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
14.3 Transport hazard class(es) ADR	
	
Class Label	3 (F1) Flammable liquids. 3
IMDG, IATA	
	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	- No
14.6 Special precautions for user hazard identification number: EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E,S-E B
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 6 (replaces version 5)

Revision: 09.12.2022

Trade name **ACRYL VSL-115-VARIO-SCHICHTLACK**

(Contd. of page 8)

Tunnel restriction code	D/E
Remarks:	TREM-Card No. 32
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT, 3, II

* SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 52a

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Date of previous version: 15.04.2021

Version number of previous version: 5

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 6 (replaces version 5)

Revision: 09.12.2022

Trade name ACRYL VSL-115-VARIO-SCHICHTLACK

(Contd. of page 9)

CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2