

Page 1/8

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.10.2023

Version number 3 (replaces version 2)

Revision: 18.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name HK Stain 3 in 1 [plus]

Article number: 5430-5437, 5443

1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. **Application of the substance / the mixture** Coating

Email: sales@remmers.co.ukk

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Remmers GmbH Bernhard-Remmers-Str. 13 D-49624 Löningen / Germany Mar Tel.: +49(0)5432/83-0 Fax: +49(0)5432/3985 Information department: Product Safety department: Phone: +44 (0) 1293 594 010

Remmers (UK) Limited Unit 4 , Lloyds Court Manor Royal, Crawley – West Sussex RH10 9QU fon +44 (0) 1293 594 010 fax +44 (0) 1293 594 037

1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111 In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number: within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms Void

Signal word Void

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations. **Additional information:**

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2- methyl-2H-isothiazol-3one and 2-methyl-2H-isothiazol-3- one (3:1), 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Page 2/8

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 3 (replaces version 2)

Printing date 18.10.2023

Revision: 18.10.2023

Trade name HK Stain 3 in 1 [plus]

(Contd. of page 1)

| 2.3 Other hazards Results of PBT and vPvB assessment |
|--|
| PBT: Not applicable. |
| vPvB: Not applicable. |
| Determination of endocrine-disrupting properties Not applicable. |

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

| v]: titanium dioxide | ≥1-<2.5% |
|--|---|
| litanium dioxide | |
| Carc. 2, H351 | 21-<2.3% |
| (2-methoxymethylethoxy)propanol substance with a Community workplace exposure limit | ≥0.5-≤1% |
| 3-iodo-2-propynyl butylcarbamate Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317 | ≥0.25-≤0.5% |
| 1,2-benzisothiazol-3(2H)-one Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1;H317: C ≥ 0.05 % | ≥0.0015-<0.05% |
| reaction mass of 5-chloro-2- methyl-2H- isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C;H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 % | ≥0.00025-<0.0015% |
| pyrithione zinc Acute Tox. 3, H301; Acute Tox. 2, H330; Repr. 1B, H360D; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=1000); Aquatic Chronic 1, H410 (M=10) ATE: LD50 oral: 221 mg/kg LC50/4 h inhalative: 0.14 mg/l | 0.0001% |
| | (2-methoxymethylethoxy)propanol substance with a Community workplace exposure limit 3-iodo-2-propynyl butylcarbamate Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317 1,2-benzisothiazol-3(2H)-one Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1;H317: C ≥ 0.05 % reaction mass of 5-chloro-2- methyl-2H- isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C;H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318; C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317; C ≥ 0.0015 % pyrithione zinc Acute Tox. 3, H301; Acute Tox. 2, H330; Repr. 1B, H360D; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=1000); Aquatic Chronic 1, H410 (M=10) ATE: LD50 oral: 221 mg/kg |

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation Seek medical treatment in case of complaints.

After skin contact If skin irritation continues, consult a doctor.

After eye contact Rinse opened eye for several minutes under running water.

After swallowing Seek immediate medical advice.

Page 3/8

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 3 (replaces version 2)

Printing date 18.10.2023

Revision: 18.10.2023

Trade name HK Stain 3 in 1 [plus]

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed symptomatic treatment

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture No further relevant information available. **5.3 Advice for firefighters**

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep people at a distance and stay on the windward side.

6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

Dilute with plenty of water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures required.

No special precautions necessary if used correctly.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: No special requirements. **Further information about storage conditions:** None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| 0.1 0 | on to parameters |
|-------|---|
| Comp | ponents with limit values that require monitoring at the workplace: |
| CAS: | 13463-67-7 titanium dioxide |
| | Long-term value: 10* 4** mg/m ³ |
| | *total inhalable **respirable |
| CAS: | 34590-94-8 (2-methoxymethylethoxy)propanol |
| WEL | Long-term value: 308 mg/m ³ , 50 ppm |
| | Sk |

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment General protective and hygienic measures

Wash hands before pauses and after work.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.

(Contd. of page 2)

according to 1907/2006/EC, Article 31

Printing date 18.10.2023

Version number 3 (replaces version 2)

Revision: 18.10.2023

(Contd. of page 3)

Trade name HK Stain 3 in 1 [plus]

Respiratory equipment:

In case of insufficient ventilation/or spraying procedures: Respiratory equipment with particle filter P 2 In case of insufficient ventilation, use respiratory protection:

Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

Break through time: max. 240 min (DIN EN 374).

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Safety glasses recommended during refilling.

SECTION 9: Physical and chemical properties

| 9.1 Information on basic physical and chemica | I properties |
|--|------------------------------------|
| General Information | |
| Physical state | Fluid |
| Colour: | According to product specification |
| Odour: | Characteristic |
| Odour threshold: | Not determined. |
| Melting point/freezing point: | Not determined |
| Boiling point or initial boiling point and boiling | |
| range | >60 °C |
| Flammability | Not applicable. |
| Lower and upper explosion limit | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| Flash point: | Not applicable |
| Auto-ignition temperature: | not applicable |
| Decomposition temperature: | Not determined. |
| pH at 20 °C | 8.3 |
| Viscosity: | |
| Kinematic viscosity at 20 °C | 25 s (DIN 53211/4) |
| dynamic: | Not determined. |
| Solubility | |
| Water: | Fully miscible |
| Partition coefficient n-octanol/water (log value |) Not determined. |
| Vapour pressure at 20 °C: | 23 hPa (CAS: 7732-18-5 Water) |
| Density and/or relative density | |
| Density at 20 °C: | 1.03 g/cm ³ |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| 9.2 Other information | |
| Appearance: | |
| Form: | Fluid |
| Important information on protection of health | |
| and environment, and on safety. | |
| Explosive properties: | Product is not explosive. |
| Solvent separation test | < 3 % |
| VOC EU | <130 g/l |
| | 100 g/i |

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 18.10.2023

Version number 3 (replaces version 2)

Revision: 18.10.2023

Trade name HK Stain 3 in 1 [plus]

(Contd. of page 4)

| Change in condition Evaporation rate | Not determined. |
|--|-----------------|
| Information with regard to physical hazard | |
| classes | |
| Explosives | Void |
| Flammable gases | Void |
| Aerosols | Void |
| Oxidising gases | Void |
| Gases under pressure | Void |
| Flammable liquids | Void |
| Flammable solids | Void |
| Self-reactive substances and mixtures | Void |
| Pyrophoric liquids | Void |
| Pyrophoric solids | Void |
| Self-heating substances and mixtures | Void |
| Substances and mixtures, which emit | |
| flammable gases in contact with water | Void |
| Oxidising liquids | Void |
| Oxidising solids | Void |
| Organic peroxides | Void |
| Corrosive to metals | Void |
| Desensitised explosives | Void |

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

| Oral | | 1 170 man//(cm (mat) |
|------------|-----------|----------------------|
| Oral | LD50 | 1,470 mg/kg (rat) |
| Dermal | | >2,000 mg/kg (rat) |
| Inhalativa | 1 CE0/4 h | 6.90 ma/l (rat) |

Inhalative LC50/4 h 6.89 mg/l (rat)

Skin corrosion/irritation: Based on available data, the classification criteria are not met.
Serious eye damage/irritation: Based on available data, the classification criteria are not met.
Sensitisation: Based on available data, the classification criteria are not met.
Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.
STOT-single exposure: Based on available data, the classification criteria are not met.
STOT-repeated exposure: Based on available data, the classification criteria are not met.
Aspiration hazard: Based on available data, the classification criteria are not met.

Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 18.10.2023

Version number 3 (replaces version 2)

Revision: 18.10.2023

Trade name HK Stain 3 in 1 [plus]

(Contd. of page 5)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Harmful to fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system. Hazardous to drinking water even if small quantities leak into soil. Harmful to aquatic organisms

SECTION 13: Disposal considerations

Recommendation

Do not dispose of together with household garbage. Do not allow product to reach sewage system. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

08 01 19* aqueous suspensions containing paint or varnish containing organic solvents or other hazardous substances

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations. Packaging can be reused or recycled after cleaning. **Recommended cleaning agent:** Water, if necessary with cleaning agent.

SECTION 14: Transport information

| 14.1 UN number or ID number ADR, IMDG, IATA | Void |
|---|--------------------------|
| 14.2 UN proper shipping name ADR, IMDG, IATA | Void |
| 14.3 Transport hazard class(es) | |
| ADR, ADN, IMDG, IATA Class | Void |
| 14.4 Packing group ADR, IMDG, IATA | Void |
| 14.5 Environmental hazards: | Not applicable. |
| 14.6 Special precautions for user | Not applicable. |
| 14.7 Maritime transport in bulk accordir IMO instruments | ng to Not applicable. |
| UN "Model Regulation": | Void |

(Contd. on page 7)

according to 1907/2006/EC, Article 31

Printing date 18.10.2023

Version number 3 (replaces version 2)

Revision: 18.10.2023

Trade name HK Stain 3 in 1 [plus]

(Contd. of page 6)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed. REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

- Toxic if swallowed. H301
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- May cause an allergic skin reaction. H317
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H351 Suspected of causing cancer.
- H360D May damage the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Version number of previous version: 2

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

- Acute Tox. 4: Acute toxicity Category 4 Acute Tox. 2: Acute toxicity Category 2 Acute Tox. 3: Acute toxicity Category 3

Skin Corr. 1C: Skin corrosion/irritation – Category 1C Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

- Skin Sens. 1: Skin sensitisation Category 1
- Skin Sens. 1A: Skin sensitisation Category 1A

Page 8/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.10.2023

Version number 3 (replaces version 2)

Revision: 18.10.2023

Trade name HK Stain 3 in 1 [plus]

Carc. 2: Carcinogenicity – Category 2 Repr. 1B: Reproductive toxicity – Category 1B STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 (Contd. of page 7)