

Page 1/8

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 6 (replaces version 5)

Revision: 12.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1 Product identifier

# Trade name HSL-30/m-Profi-Holzschutzlasur 3in1

Article number: 7100-7114

1.2 Relevant identified uses of the substance or mixture and uses advised against
 Product category
 PC8 Biocidal products
 PC9a Coatings and paints, thinners, paint removers
 Application of the substance / the mixture Wood protection glazing

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Remmers GmbH Bernhard-Remmers-Str. 13 D-49624 Löningen / Germany Mano Tel.: +49(0)5432/83-0 Fax: +49(0)5432/3985 Information department: Product Safety department: Phone: +44 (0) 1293 594 010 Email: sales@remmers.co.ukk

Remmers (UK) Limited Unit 4 , Lloyds Court Manor Royal, Crawley – West Sussex RH10 9QU fon +44 (0) 1293 594 010 fax +44 (0) 1293 594 037

### 1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111 In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number: within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

**SECTION 2: Hazards identification** 

# 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Eye Irrit. 2H319 Causes serious eye irritation.Skin Sens. 1H317 May cause an allergic skin reaction.STOT RE 2H373 May cause damage to the larynx through prolonged or repeated exposure.Asp. Tox. 1H304 May be fatal if swallowed and enters airways.Aquatic Chronic 3H412 Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation. **Hazard pictograms** 



Signal word Danger

Hazard-determining components of labelling: Alkanes, C10-13

Page 2/8

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 6 (replaces version 5)

Revision: 12.12.2022

# Trade name HSL-30/m-Profi-Holzschutzlasur 3in1

(Contd. of page 1)

	(Cond. of pa	age
3-iodo-2-propynyl l	butylcarbamate	-
hydrocarbons, C14	-C18, n-alkanes, isoalkanes, cyclics	
Hazard statement	S	
H319 Causes serie	bus eye irritation.	
H317 May cause a	n allergic skin reaction.	
	amage to the larynx through prolonged or repeated exposure.	
H304 May be fatal	if swallowed and enters airways.	
H412 Harmful to a	quatic life with long lasting effects.	
Precautionary sta	tements	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
P273	Avoid release to the environment.	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing	g
	protection.	-
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.	
P331	Do NOT induce vomiting.	
P302+P352	IF ON SKIN: Wash with plenty of soap and water.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact	
	lenses, if present and easy to do. Continue rinsing.	
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional/national/	
	international regulations.	
Additional inform	ation:	

### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

Attention please! This product may cause a self ignition of the material, such as brushes or textiles, if contaminated with the product. Those materials and textiles should be dipped into water after use and before waste treatment. Do not use this product in application cabins, if there are NC - or PUR-coatings are used too, because retarded self-ignitions are possible!

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients** 

# 3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

# Dangerous components [% w/w]:

EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39- XXXX	Alkanes, C10-13 Asp. Tox. 1, H304, EUH066	≥40-<50%	
EC number: 920-360-0 Reg.nr.: 01-2119448343-41- XXXX	hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics Asp. Tox. 1, H304	≥20-<30%	
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17- XXXX	titanium dioxide Carc. 2, H351	≥5-<10%	
CAS: 55406-53-6 EINECS: 259-627-5 Index number: 616-212-00-7	3-iodo-2-propynyl butylcarbamate Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317	≥1-<2.5%	
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60- XXXX	(2-methoxymethylethoxy)propanol substance with a Community workplace exposure limit	≥0.1-≤0.25%	

# Safety data sheet

according to 1907/2006/EC, Article 31 Version number 6 (replaces version 5)

Printing date 12.12.2022

Revision: 12.12.2022

(Contd. of page 2)

# Trade name HSL-30/m-Profi-Holzschutzlasur 3in1

# Additional information

Benzene content: < 0,1% Note P is applicable. It is not necessary to classify nor to mark the product as carcinogenic.

For the wording of the listed hazard phrases refer to section 16.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

# After inhalation

Take affected persons into the open air and position comfortably
Supply fresh air and call for doctor for safety reasons.
In case of unconsciousness bring patient into stable side position for transport.
After skin contact Wash immediately with water and soap and rinse thoroughly.
After eye contact
Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
After swallowing Seek immediate medical advice.
4.2 Most important symptoms and effects, both acute and delayed
Headache
Dizziness
Irritating effect on skin and eyes.
4.3 Indication of any immediate medical attention and special treatment needed
symptomatic treatment

**SECTION 5: Firefighting measures** 

# 5.1 Extinguishing media

Suitable extinguishing agents Foam Water spray jet Water mist 5.2 Special hazards arising from the substance or mixture May be released in case of fire Carbon monoxide (CO) Carbon dioxide Formation of toxic gases is possible during heating or in case of fire. 5.3 Advice for firefighters **Protective equipment:** Wear self-contained breathing apparatus. Wear full protective suit. Additional information Cool endangered containers with water spray jet. Collect contaminated fire fighting water separately. It must not enter drains. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

# SECTION 6: Accidental release measures

# 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

# Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Prevent from spreading (e.g. by confining or oil barrier).

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

# 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable containers.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

# 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

(Contd. on page 4)

Page 4/8

# Safety data sheet

according to 1907/2006/EC, Article 31 Version number 6 (replaces version 5)

Printing date 12.12.2022

Revision: 12.12.2022

# Trade name HSL-30/m-Profi-Holzschutzlasur 3in1

(Contd. of page 3)

**SECTION 7: Handling and storage** 

# 7.1 Precautions for safe handling

Use only in well ventilated areas. Ensure good ventilation/exhaust in workplaces. Avoid the formation of aerosols. Information about protection against explosions and fires: Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage

**Requirements to be met by storerooms and containers:** No special requirements. **Information on storage in a common storage facility:** Store away from food.

Further information about storage conditions:

Store container in a well ventilated position. Protect from frost.

Keep container tightly closed.

### **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

8.1 C	8.1 Control parameters		
Comp	Components with limit values that require monitoring at the workplace:		
CAS:	CAS: 13463-67-7 titanium dioxide		
	Long-term value: 10* 4** mg/m³ *total inhalable **respirable		
CAS:	34590-94-8 (2-methoxymethylethoxy)propanol		
WEL	Long-term value: 308 mg/m³, 50 ppm Sk		

Additional information: The lists that were valid during compilation were used as a basis.

### 8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

### Individual protection measures, such as personal protective equipment General protective and hygienic measures

Do not eat, drink or smoke while working.

Apply solvent-resistant skin protection preparation before beginning work.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Store protective clothing separately.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.

# Respiratory equipment:

Filter A (brown)

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

### Hand protection

Solvent resistant gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

# Material of gloves

# Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Page 5/8

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 6 (replaces version 5)

Revision: 12.12.2022

# Trade name HSL-30/m-Profi-Holzschutzlasur 3in1

(Contd. of page 4)

**Penetration time of glove material** The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye/face protection** Tightly sealed safety glasses.

Body protection: Protective work clothing.

**SECTION 9: Physical and chemical properties** 

9.1 Information on basic physical and chemical	properties
General Information	
Physical state	Fluid
Colour:	According to product specification
Odour:	Solvent-like
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling	
	Not determined
range Elemente kiliter	
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	0.6 Vol %
Upper:	7 Vol %
Flash point:	>60 °C
Ignition temperature:	not applicable
Decomposition temperature:	Not determined.
рН	Not determined.
Viscosity:	
Kinematic viscosity at 20 °C	80 s (ISO 3 mm)
dynamic:	Not determined.
Solubility	
Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.87 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health	
and environment, and on safety.	
Explosive properties:	Product is not explosive.
Solvent separation test	< 3 %
VOC EU	<400 g/l
Solid content:	36.0 %
Change in condition	
Evaporation rate	Not determined.
•	
Information with regard to physical hazard	
classes	Vaid
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void

Page 6/8

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 6 (replaces version 5)

Revision: 12.12.2022

# Trade name HSL-30/m-Profi-Holzschutzlasur 3in1

(Contd. of page 5)

Self-reactive substances and mixturesVoidPyrophoric liquidsVoidPyrophoric solidsVoidSelf-heating substances and mixturesVoidSubstances and mixtures, which emitVoidflammable gases in contact with waterVoidOxidising liquidsVoidOxidising solidsVoidOrganic peroxidesVoidCorrosive to metalsVoidDesensitised explosivesVoid			10
Pyrophoric solidsVoidSelf-heating substances and mixturesVoidSubstances and mixtures, which emitflammable gases in contact with waterflammable gases in contact with waterVoidOxidising liquidsVoidOxidising solidsVoidOrganic peroxidesVoidCorrosive to metalsVoid	Self-reactive substances and mixtures	Void	
Self-heating substances and mixturesVoidSubstances and mixtures, which emitVoidflammable gases in contact with waterVoidOxidising liquidsVoidOxidising solidsVoidOrganic peroxidesVoidCorrosive to metalsVoid	Pyrophoric liquids	Void	
Substances and mixtures, which emitflammable gases in contact with waterVoidOxidising liquidsVoidOxidising solidsVoidOrganic peroxidesVoidCorrosive to metalsVoid	Pyrophoric solids	Void	
flammable gases in contact with waterVoidOxidising liquidsVoidOxidising solidsVoidOrganic peroxidesVoidCorrosive to metalsVoid	Self-heating substances and mixtures	Void	
Oxidising liquidsVoidOxidising solidsVoidOrganic peroxidesVoidCorrosive to metalsVoid	Substances and mixtures, which emit		
Oxidising solidsVoidOrganic peroxidesVoidCorrosive to metalsVoid	flammable gases in contact with water	Void	
Organic peroxidesVoidCorrosive to metalsVoid	Oxidising liquids	Void	
Corrosive to metals Void	Oxidising solids	Void	
	Organic peroxides	Void	
Desensitised explosives Void	Corrosive to metals	Void	
	Desensitised explosives	Void	

# **SECTION 10: Stability and reactivity**

**10.1 Reactivity** No further relevant information available.

# 10.2 Chemical stability

# Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

Avoid: heat, flames, sparks

# 10.3 Possibility of hazardous reactions

Used empty containers may contain product gases which form explosive mixtures with air

**10.4 Conditions to avoid** No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

# 10.6 Hazardous decomposition products:

None if used properly.

None if stored properly.

# **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50	LD/LC50 values that are relevant for classification:		
Alkanes,	Alkanes, C10-13		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rat)	
Inhalative	LC50/4 h	>20 mg/l (rat)	
Skin corrosion/irritation: Based on available data, the classification criteria are not met.			

Skin corrosion/irritation: Based on available data, the classification criteria are not

Serious eye damage/irritation: Causes serious eye irritation.

Sensitisation: May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

**Reproductive toxicity:** Based on available data, the classification criteria are not met.

**STOT-single exposure:** Based on available data, the classification criteria are not met.

**STOT-repeated exposure:** May cause damage to the larynx through prolonged or repeated exposure. **Aspiration hazard:** May be fatal if swallowed and enters airways.

# 11.2 Information on other hazards

# Endocrine disrupting properties

None of the ingredients is listed.

**SECTION 12: Ecological information** 

# 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.

**vPvB:** Not applicable.

Page 7/8

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 6 (replaces version 5) Revision: 12.12.2022

# Trade name HSL-30/m-Profi-Holzschutzlasur 3in1

(Contd. of page 6)

# **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties. **12.7 Other adverse effects Remark:** Harmful to fish **Additional ecological information: General notes:** Do not allow product to reach ground water, bodies of water or sewage system, even in small quantities. Do not allow product to reach ground water, bodies of water or sewage system. Hazardous to drinking water even if extremely small quantities leak into soil. Harmful to aquatic organisms **SECTION 13: Disposal considerations**

# Recommendation

Liquid material remains are to be disposed of at collection facilities for old varnishes. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

# European waste catalogue

03 02 02\* organochlorinated wood preservatives

# **Uncleaned packaging:**

### Recommendation:

Disposal must be made according to official regulations. Packaging can be reused or recycled after cleaning.

### **SECTION 14: Transport information** 14.1 UN number or ID number ADR, ADN, IMDG, IATA Void 14.2 UN proper shipping name ADR, ADN, IMDG, IATA Void 14.3 Transport hazard class(es) ADR, ADN, IMDG, IATA Class Void 14.4 Packing group ADR, IMDG, IATA Void 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user Not applicable. 14.7 Maritime transport in bulk according to **IMO** instruments Not applicable. Transport/Additional information: Not a hazardous good according to the above regulations. **UN "Model Regulation":** Void SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU Named dangerous substances - ANNEX I None of the ingredients is listed. REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 6 (replaces version 5)

Revision: 12.12.2022

# Trade name HSL-30/m-Profi-Holzschutzlasur 3in1

(Contd. of page 7)

# **REGULATION (EU) 2019/1148**

# Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

# Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

# National regulations

### Other regulations, limitations and prohibition ordinances

Do not use this wood preservative on wood that could come in direct contact with food or animal feed. Wood preservatives contain biocidal ingredients to protect wood from pests. They should only be used according to directions and only in the approved areas where protective measures are required. Misuse may harm your health and the environment.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **SECTION 16: Other information**

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

### **Relevant phrases**

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H331 Toxic if inhaled.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

# Classification according to Regulation (EC) No 1272/2008 Calculation method

### Department issuing data specification sheet: Product Safety department / EHS

Date of previous version: 01.09.2022

### Version number of previous version: 5

### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Acute Tox. 4: Acute toxicity Category 4
- Acute Tox. 3: Acute toxicity Category 3
- Eye Dam. 1: Serious eye damage/eye irritation Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- Skin Sens. 1: Skin sensitisation Category 1
- Carc. 2: Carcinogenicity Category 2
- STOT RE 1: Specific target organ toxicity (repeated exposure) Category 1
- STOT RE 2: Specific target organ toxicity (repeated exposure) Category 2
- Asp. Tox. 1: Aspiration hazard Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment acute aquatic hazard Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment long-term aquatic hazard Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment long-term aquatic hazard Category 3