

Page 1/10

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024 Version number 4 (replaces version 3) Revision: 08.06.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name IG-10 Impregnation Primer IT

Article number: 7142, 7143, 7144

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Wood preservatives

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH Remmers (UK) Limited Bernhard-Remmers-Str. 13 Unit 4 , Lloyds Court

D-49624 Löningen / Germany Manor Royal, Crawley – West Sussex RH10 9QU Tel.: +49(0)5432/83-0 fon +44 (0) 1293 594 010 Fax: +49(0)5432/3985 fax +44 (0) 1293 594 037

Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aguatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms







GHS02 GHS08 GHS09

Signal word Danger

Hazard-determining components of labelling:

Alkanes, C10-13

Hazard statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

Printing date 30.01.2024 Version number 4 (replaces version 3) Revision: 08.06.2023

Trade name IG-10 Impregnation Primer IT

(Contd. of page 1)

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower].

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

Determination of endocrine-disrupting properties Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: solvent-based wood preservative with biocide actival ingredient

Dangerous components [% w/	w]:	
EC number: 918-481-9 Reg.nr.: 01-2119457273-39- XXXX	Alkanes, C10-13 Asp. Tox. 1, H304, EUH066	≥85-100%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60- XXXX	(2-methoxymethylethoxy)propanol substance with a Community workplace exposure limit	≥5-<10%
CAS: 107534-96-3 ELINCS: 403-640-2 Index number: 603-197-00-7	tebuconazole (ISO) Repr. 2, H361d; Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=10); Acute Tox. 4, H302	≥0.5-≤1%
CAS: 55406-53-6 EINECS: 259-627-5 Index number: 616-212-00-7	3-iodo-2-propynyl butylcarbamate Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317	≥0.5-<1%
CAS: 78-83-1 EINECS: 201-148-0 Index number: 603-108-00-1 Reg.nr.: 01-2119484609-23- XXXX	iso-butanol Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥0.25-≤0.5%
CAS: 52315-07-8 EINECS: 257-842-9 Index number: 607-421-00-4	cypermethrin STOT RE 2, H373; Aquatic Acute 1, H400 (M=100000); Aquatic Chronic 1, H410 (M=100000); Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335 ATE: LD50 oral: 500 mg/kg	≥0.1-≤0.25%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3	1-methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	≥0.1-≤0.25%

(Contd. on page 3)

Printing date 30.01.2024 Version number 4 (replaces version 3) Revision: 08.06.2023

Trade name IG-10 Impregnation Primer IT

(Contd. of page 2)

Additional information

Benzene content: < 0,1% Note P is applicable. It is not necessary to classify nor to mark the product as carcinogenic.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When symptoms occur or in case of doubt, seek medical advice

Immediately remove any clothing soiled by the product.

After inhalation Take affected persons into the open air and position comfortably

After skin contact Wash off immediately with water.

After eye contact Rinse opened eye for several minutes under running water.

After swallowing Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

In case of prolonged/repeated exposure or in high concentrations:

Headache

Dizziness

Irritating effect on skin and eyes.

Danger Long-term or repeated exposure may cause inflammation of the skin (dermatitis).

4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

To avoid dermatitis (skin inflammation), use skin cream.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

For safety reasons unsuitable extinguishing agents Water with a full water jet.

5.2 Special hazards arising from the substance or mixture

May be released in case of fire

Carbon monoxide (CO)

Carbon dioxide

Not rated as flammable, however, it is combustible.

Vapours are heavier than air and spread out over the ground. Ignition over greater distances is possible.

5.3 Advice for firefighters

Protective equipment:

Wear full protective suit.

Wear self-contained breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Prevent from spreading (e.g. by confining or oil barrier).

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable containers.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 30.01.2024

Version number 4 (replaces version 3)

Trade name IG-10 Impregnation Primer IT

(Contd. of page 3)

Revision: 08.06.2023

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Use only in well ventilated areas.

Information about protection against explosions and fires:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: Prevent any penetration into the ground.

Information on storage in a common storage facility: Store away from food.

Further information about storage conditions:

Store container in a well ventilated position.

Do not smoke in storage areas. Storage temperature: room temperature.

Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Com	Components with limit values that require monitoring at the workplace:		
CAS:	CAS: 34590-94-8 (2-methoxymethylethoxy)propanol		
WEL	Long-term value: 308 mg/m³, 50 ppm Sk		
CAS:	78-83-1 iso-butanol		
WEL	Short-term value: 231 mg/m³, 75 ppm Long-term value: 154 mg/m³, 50 ppm		
CAS:	CAS: 107-98-2 1-methoxy-2-propanol		
WEL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk		

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Appropriate engineering controls Use only in well-ventilated areas.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.

Apply solvent-resistant skin protection preparation before beginning work.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.

Respiratory equipment:

Respiratory protection if there is a risk of splashes/mist.

Filter A/P2.

Hand protection

Solvent resistant gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3) Printing date 30.01.2024 Revision: 08.06.2023

Trade name IG-10 Impregnation Primer IT

(Contd. of page 4)

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Colour: According to product specification

Odour: Solvent-like Odour threshold: Not determined. Melting point/freezing point: Not determined

Boiling point or initial boiling point and boiling

range Not determined **Flammability** Flammable.

Lower and upper explosion limit

Lower: Not determined. Upper: Not determined.

Flash point: <60 °C **Auto-ignition temperature:** not applicable **Decomposition temperature:** Not determined. Not determined. pН

Viscosity:

Kinematic viscosity at 20 °C 11 s (DIN 53211/4) dynamic: Not determined.

Solubility

Water: Not miscible or difficult to mix

Partition coefficient n-octanol/water (log value) Not determined. Not determined. Vapour pressure:

Density and/or relative density

Density at 20 °C: 0.81 g/cm³ Relative density Not determined. Vapour density Not determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health

and environment, and on safety.

Explosive properties: Product is not explosive. However, formation of

dangerous explosive vapour/air mixtures is

possible.

< 3 % Solvent separation test

VOC EU

Solid content: 5.0 %

Change in condition

Evaporation rate Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024 Version number 4 (replaces version 3) Revision: 08.06.2023

Trade name IG-10 Impregnation Primer IT

(Contd. of page 5)

Information with regard to physical hazard classes	
Explosives Void	
Flammable gases Void	
Aerosols Void	
Oxidising gases Void	
Gases under pressure Void	
Flammable liquids Flammable liquid and vapor	ur.
Flammable solids Void	
Self-reactive substances and mixtures Void	
Pyrophoric liquids Void	
Pyrophoric solids Void	
Self-heating substances and mixtures Void	
Substances and mixtures, which emit	
flammable gases in contact with water Void	
Oxidising liquids Void	
Oxidising solids Void	
Organic peroxides Void	
Corrosive to metals Void	
Desensitised explosives Void	

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

Avoid: heat, flames, sparks

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

None if used properly. None if stored properly.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50	values tha	t are relevant for classification:
Alkanes,	C10-13	
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/4 h	>20 mg/l (rat)

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties	
None of the ingredients is listed.	

(Contd. on page 7)

Printing date 30.01.2024 Version number

Version number 4 (replaces version 3) Revision: 08.06.2023

Trade name IG-10 Impregnation Primer IT

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects Remark: Very toxic for fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system, even in small quantities.

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if extremely small quantities leak into soil.

Also toxic for fish and plankton in bodies of water.

Very toxic for aquatic organisms

SECTION 13: Disposal considerations

Recommendation

Must be specially treated in compliance with official regulations.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

03 02 99 wood preservatives not otherwise specified

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

SECTION 14: Transport information

PROPANOL, 3-iodo-2-propynyl butylcarbamate) IMDG FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2- PROPANOL, 3-iodo-2-propynyl butylcarbamate), MARINE POLLUTANT	14.1 UN number or ID number ADR, IMDG, IATA	UN1993
PROPANOL, 3-iodo-2-propynyl butylcarbamate) IMDG FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2- PROPANOL, 3-iodo-2-propynyl butylcarbamate), MARINE POLLUTANT	14.2 UN proper shipping name	
FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2-PROPANOL, 3-iodo-2-propynyl butylcarbamate), MARINE POLLUTANT	ADR	1993 FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2-
PROPANOL, 3-iodo-2-propynyl butylcarbamate), MARINE POLLUTANT		
MARINE POLLUTANT	IMDG	FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2-
LATA FLAMMADIE LIQUID NIGO (4 METUOVI) O		MARINE POLLUTANT
IATA FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2-	IATA	FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2-
PROPANOL, 3-iodo-2-propynyl butylcarbamate)		PROPANOL, 3-iodo-2-propynyl butylcarbamate)

14.3 Transport hazard class(es)

ADR



Class 3 (F1) Flammable liquids.

(Contd. on page 8)

Printing date 30.01.2024 Version number 4 (replaces version 3) Revision: 08.06.2023

Trade name IG-10 Impregnation Primer IT

(Contd. of page 7)

Label 3 **IMDG** Class 3 Flammable liquids. Label IATA 3 Flammable liquids. Class Label 3 14.4 Packing group ADR, IMDG, IATA Ш 14.5 Environmental hazards: Marine pollutant: Yes Symbol (fish and tree) Special marking (ADR): Symbol (fish and tree) 14.6 Special precautions for user Warning: Flammable liquids. hazard identification number: F-E,S-E **EMS Number: Stowage Category** 14.7 Maritime transport in bulk according to **IMO** instruments Not applicable. **Transport/Additional information:** Limited quantities (LQ) 5L **Excepted quantities (EQ)** Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml **Transport category** 3 **Tunnel restriction code** D/E Limited quantities (LQ) 5L **Excepted quantities (EQ)** Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml **UN "Model Regulation":** UN 1993 FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2-PROPANOL, 3-IODO-2-PROPYNYL BUTYLCARBAMATE), 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category

E1 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024 Version number 4 (replaces version 3) Revision: 08.06.2023

Trade name IG-10 Impregnation Primer IT

(Contd. of page 8)

Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations

Other regulations, limitations and prohibition ordinances

According to the Federal Institute for Sanitary Consumer Protection and Veterinary Medicine (BgVV): Requirements/restructions:

Wood preservatives contains biocidal ingredients to protect wood from pests. They should be used only according to directions and only in the approved application areas where protection measures are required. Misuse may harm your health and the enironment. Do not use this wood preservative on wood that could come in direct contact with food or animal feed.

Only for use in professional facilities.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H226 Flammable liquid a	nd vapour.
-------------------------	------------

H302 Harmful if swallowed.

May be fatal if swallowed and enters airways. H304

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

Toxic if inhaled. H331

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Version number of previous version: 3

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity - Category 3

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 4 (replaces version 3)

Trade name IG-10 Impregnation Primer IT

(Contd. of page 9)

Revision: 08.06.2023

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1