

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 6 (replaces version 5)

Revision: 22.08.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **AG-20 Universal Primer / SG-20 Barrier Primer**

Article number: 7150; 7153; 7154

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Product category PC9a Coatings and paints, thinners, paint removers

Application of the substance / the mixture Wood treatment

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH

Bernhard-Remmers-Str. 13
D-49624 Lönigen / Germany

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985

Remmers (UK) Limited

Unit 4 , Lloyds Court

Manor Royal, Crawley – West Sussex RH10 9QU

fon +44 (0) 1293 594 010

fax +44 (0) 1293 594 037

Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS):

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300

outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Warning

Hazard-determining components of labelling:

hydrocarbons, C9, aromatics

1-methoxy-2-propanol

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 6 (replaces version 5)

Revision: 22.08.2023

Trade name **AG-20 Universal Primer / SG-20 Barrier Primer**

(Contd. of page 1)

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing mist/vapours/spray.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

2.3 Other hazards

Attention please! This product may cause a self ignition of the material, such as brushes or textiles, if contaminated with the product. Those materials and textiles should be dipped into water after use and before waste treatment. Do not use this product in application cabins, if there are NC - or PUR-coatings are used too, because retarded self-ignitions are possible!

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.

* SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:		
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-XXXX	hydrocarbons, C9, aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	≥10-<20%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide substance with a Community workplace exposure limit	≥10-<20%
EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39-XXXX	Alkanes, C10-13 Asp. Tox. 1, H304, EUH066	≥10-<20%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3	1-methoxy-2-propanol Flam. Liq. 3, H226; STOT SE 3, H336	≥2.5-<5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥1-<2.5%
CAS: 55406-53-6 EINECS: 259-627-5 Index number: 616-212-00-7	3-iodo-2-propynyl butylcarbamate Acute Tox. 3, H331; STOT RE 1, H372; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Acute Tox. 4, H302; Skin Sens. 1, H317	≥0.25-≤0.5%
CAS: 22464-99-9 EINECS: 245-018-1 Reg.nr.: 01-2119979088-21-XXXX	2-ethylhexanoic acid, zirconium salt Repr. 2, H361d	≥0.1-≤0.25%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 6 (replaces version 5)

Revision: 22.08.2023

Trade name **AG-20 Universal Primer / SG-20 Barrier Primer**

(Contd. of page 2)

Additional information

Benzene content: < 0,1% Note P is applicable. It is not necessary to classify nor to mark the product as carcinogenic.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

Immediately remove any clothing soiled by the product.

After inhalation Seek medical treatment in case of complaints.

After skin contact Wash off immediately with water.

After eye contact Rinse opened eye for several minutes under running water.

After swallowing Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents**

Foam

Water spray jet

Water mist

Dry extinguishing agents, carbon dioxide, sand or earth should only be used for small fires.

For safety reasons unsuitable extinguishing agents Water with a full water jet.

5.2 Special hazards arising from the substance or mixture

May be released in case of fire

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic substances cannot be excluded.

Vapours are heavier than air and spread out over the ground. Ignition over greater distances is possible.

5.3 Advice for firefighters**Protective equipment:**

Wear self-contained breathing apparatus.

Wear full protective suit.

Additional information Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable containers.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 6 (replaces version 5)

Revision: 22.08.2023

Trade name **AG-20 Universal Primer / SG-20 Barrier Primer**

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas.
Ensure good ventilation/exhaust in workplaces.
Avoid the formation of aerosols.

Information about protection against explosions and fires:

Fumes can combine with air to form an explosive mixture.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: Install solvent resistant, sealed floor.

Information on storage in a common storage facility:

Store away from oxidising agents.
Do not store together with fire promoting and self-igniting materials as well as easily flammable solids.

Further information about storage conditions:

Store container in a well ventilated position.
Do not smoke in storage areas. Storage temperature: room temperature.
Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:	
CAS: 13463-67-7 titanium dioxide	
WEL	Long-term value: 10* 4** mg/m ³ *total inhalable **respirable
CAS: 107-98-2 1-methoxy-2-propanol	
WEL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Sk
CAS: 1330-20-7 xylene	
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
Ingredients with biological limit values:	
CAS: 1330-20-7 xylene	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Appropriate engineering controls Use only in well-ventilated areas.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.
Apply solvent-resistant skin protection preparation before beginning work.
Immediately remove soiled, saturated clothing.
Wash hands before pauses and after work.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-site shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

Respiratory equipment:

In case of a risk of inhaling, wear half-mask with combination filter for organic vapours and particles.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 6 (replaces version 5)

Revision: 22.08.2023

Trade name **AG-20 Universal Primer / SG-20 Barrier Primer**

(Contd. of page 4)

Short term filter device:

Filter A/P2.

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Hand protection

Solvent resistant gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Fluid

Colour:

According to product specification

Odour:

Type specific

Odour threshold:

Not determined.

Melting point/freezing point:

Not determined

Boiling point or initial boiling point and boiling range

Not determined

Flammability

Flammable.

Lower and upper explosion limit

Lower:

Not determined.

Upper:

Not determined.

Flash point:

ca.42 °C

Ignition temperature:

not applicable

Decomposition temperature:

Not determined.

pH

Not determined.

Viscosity:

Kinematic viscosity

Not determined.

dynamic at 20 °C:

1400+/-150 mPas

Solubility

Water:

Not miscible or difficult to mix

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure:

Not determined.

Density and/or relative density

Density at 20 °C:

1.30+/-0.05 g/cm³

Relative density

Not determined.

Vapour density

Not determined.

9.2 Other information

Appearance:

Form:

Fluid

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 6 (replaces version 5)

Revision: 22.08.2023

Trade name **AG-20 Universal Primer / SG-20 Barrier Primer**

(Contd. of page 5)

Important information on protection of health and environment, and on safety.	
Explosive properties:	Product is not explosive. However, formation of dangerous explosive vapour/air mixtures is possible.
Solvent separation test	< 3 %
VOC EU	<750 g/l
Solid content:	67+/-3 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided: Avoid: heat, flames, sparks

10.3 Possibility of hazardous reactions Reacts with strong oxidising agents

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: No dangerous decomposition products known

* SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:		
hydrocarbons, C9, aromatics		
Oral	LD50	3,592 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit)
Alkanes, C10-13		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/4 h	>20 mg/l (rat)

Bemerkung: geschätzt

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 6 (replaces version 5)

Revision: 22.08.2023

Trade name **AG-20 Universal Primer / SG-20 Barrier Primer**

(Contd. of page 6)

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: May cause drowsiness or dizziness.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Experience with humans:

Frequent or longer lasting skin contact may decrease and dry out skin which may lead to skin irritation and inflammation (dermatitis).

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Harmful to fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

Attention please! This product may cause a self ignition of the material, such as brushes or textiles, if contaminated with the product. Those materials and textiles should be dipped into water after use and before waste treatment. Do not use this product in application cabins, if there are NC - or PUR-coatings are used too, because retarded self-ignitions are possible!

Recommendation

Must be specially treated in compliance with official regulations.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, ADN, IMDG

Void

IATA

UN1263

14.2 UN proper shipping name

ADR, ADN, IMDG

Void

IATA

PAINT

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 22.08.2023

Version number 6 (replaces version 5)

Revision: 22.08.2023

Trade name **AG-20 Universal Primer / SG-20 Barrier Primer**

(Contd. of page 7)

14.3 Transport hazard class(es)	
ADR, ADN, IMDG Class	Void
IATA	
	
Class Label	3 Flammable liquids. 3
14.4 Packing group	
ADR, IMDG IATA	Void III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	
	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments	
	Not applicable.
Transport/Additional information:	
	Not a hazardous good according to the above regulations.
UN "Model Regulation":	
	Void

* SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2023

Version number 6 (replaces version 5)

Revision: 22.08.2023

Trade name AG-20 Universal Primer / SG-20 Barrier Primer

(Contd. of page 8)

- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Date of previous version: 07.04.2020

Version number of previous version: 5

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3