

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 8 (replaces version 7)

Revision: 12.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **PRIMER PUR**

Article number: 7530

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category PC9a Coatings and paints, thinners, paint removers

Application of the substance / the mixture Priming

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH
Bernhard-Remmers-Str. 13
D-49624 Lönningen / Germany
Tel.: +49(0)5432/83-0
Fax: +49(0)5432/3985

Remmers (UK) Limited
Unit 4 , Lloyds Court
Manor Royal, Crawley – West Sussex RH10 9QU
fon +44 (0) 1293 594 010
fax +44 (0) 1293 594 037

Information department:

Product Safety department: Phone: +44 (0) 1293 594 010
Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS):
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:
within USA and Canada: 1-800-424-9300
outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3	H226	Flammable liquid and vapour.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Warning

Hazard-determining components of labelling:

isophorondiisocyanate Homopolymer
1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate
Solvent naphtha (mineral oil), slight aromatic
2-methoxy-1-methylethyl acetate

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 8 (replaces version 7)

Revision: 12.12.2022

Trade name **PRIMER PUR**

(Contd. of page 1)

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Hazard statements

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.* **SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:		
EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39-XXXX	Alkanes, C10-13 Asp. Tox. 1, H304, EUH066	≥30-<40%
CAS: 53880-05-0 NLP: 500-125-5 Reg.nr.: 01-2119488734-24-XXXX	isophorondiisocyanate Homopolymer Skin Sens. 1, H317; STOT SE 3, H335	≥30-<40%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-XXXX	hydrocarbons, C9, aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	≥10-<20%
CAS: 140921-24-0 ELINCS: 411-700-4 Index number: 616-079-00-5 Reg.nr.: 01-0000015906-63-XXXX	1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate Skin Sens. 1, H317	≥5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	≥5-<10%
CAS: 4098-71-9 EINECS: 223-861-6 Index number: 615-008-00-5 Reg.nr.: 01-2119490408-31-XXXX	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.1-<0.25%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 8 (replaces version 7)

Revision: 12.12.2022

Trade name **PRIMER PUR**

CAS: 3648-18-8 EINECS: 222-883-3 Index number: 050-031-00-9	dioctyltin dilaurate Repr. 1B, H360D; STOT RE 1, H372	(Contd. of page 2) ≥0.1-≤0.25%
---	--	-----------------------------------

Additional information For the wording of the listed hazard phrases refer to section 16.

* SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

After inhalation

Take affected persons into the open air and position comfortably

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact Wash immediately with water and soap and rinse thoroughly.

After eye contact Rinse opened eye for several minutes under running water.

After swallowing Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

In case of prolonged/repeated exposure or in high concentrations:

Headache

Dizziness

nausea

Unconsciousness

Inhalation may have an irritating effect on mucous membranes.

Danger Long-term or repeated exposure may cause inflammation of the skin (dermatitis).

4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

To avoid dermatitis (skin inflammation), use skin cream.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Foam

Water spray jet

Water mist

Dry extinguishing agents, carbon dioxide, sand or earth should only be used for small fires.

For safety reasons unsuitable extinguishing agents Water with a full water jet.

5.2 Special hazards arising from the substance or mixture

May be released in case of fire

Carbon monoxide (CO)

Nitrogen oxides (NO_x)

Hydrogen cyanide (HCN)

(Traces)

Formation of poisonous gases during heating or in fires.

Vapours are heavier than air and spread out over the ground. Ignition over greater distances is possible.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

Put on breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 8 (replaces version 7)

Revision: 12.12.2022

Trade name **PRIMER PUR**

(Contd. of page 3)

Put on breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable containers.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

Information about protection against explosions and fires:

Fumes can combine with air to form an explosive mixture.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep breathing equipment ready.

7.2 Conditions for safe storage, including any incompatibilities**Storage****Requirements to be met by storerooms and containers:** No special requirements.**Information on storage in a common storage facility:**

Suitable material for containers and pipes: Light metals and their alloys.

Further information about storage conditions:

Store container in a well ventilated position.

Protect from humidity and keep away from water.

Keep container tightly closed.

*** SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Components with limit values that require monitoring at the workplace:****CAS: 108-65-6 2-methoxy-1-methylethyl acetate**WEL Short-term value: 548 mg/m³, 100 ppmLong-term value: 274 mg/m³, 50 ppm

Sk

CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanateWEL Short-term value: 0.07 mg/m³Long-term value: 0.02 mg/m³

Sen; as -NCO

Ingredients with biological limit values:**CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate**

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period of exposure

Parameter: isocyanate-derived diamine

Additional information: The lists that were valid during compilation were used as a basis.**8.2 Exposure controls****Appropriate engineering controls** Use only in well-ventilated areas.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 8 (replaces version 7)

Revision: 12.12.2022

Trade name **PRIMER PUR**

(Contd. of page 4)

Individual protection measures, such as personal protective equipment**General protective and hygienic measures**

Do not eat, drink or smoke while working.

Apply solvent-resistant skin protection preparation before beginning work.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-site shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

Respiratory equipment:

Filter A (brown)

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Hand protection

Solvent resistant gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

if there is a risk of splashes

Tightly sealed safety glasses.

Body protection: Protective work clothing.

*

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information**

Physical state	Fluid
Colour:	Clear
Odour:	Solvent-like
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling range	145 °C
Flammability	Flammable.
Lower and upper explosion limit	
Lower:	0.6 Vol %
Upper:	10.8 Vol %
Flash point:	50.5 °C (Setaflash)
Ignition temperature:	>200 °C
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity at 20 °C	24 s (DIN 53211/4)
dynamic:	Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 8 (replaces version 7)

Revision: 12.12.2022

Trade name **PRIMER PUR**

(Contd. of page 5)

Solubility	
Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	1 hPa
Density and/or relative density	
Density at 20 °C:	0.93 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Explosive properties:	Product is not explosive. However, formation of dangerous explosive vapour/air mixtures is possible.
Solvent separation test	< 3 %
Organic solvents:	59.1 %
VOC EU	
Solid content:	32.1 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if handled and stored according to specifications.

Avoid: heat, flames, sparks

10.3 Possibility of hazardous reactions Danger of bursting**10.4 Conditions to avoid** No further relevant information available.**10.5 Incompatible materials:**

Amines

Alcohols

10.6 Hazardous decomposition products: Isobutyraldehyde

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 8 (replaces version 7)

Revision: 12.12.2022

Trade name **PRIMER PUR**

(Contd. of page 6)

* SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

Alkanes, C10-13

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50/4 h	>20 mg/l (rat)

hydrocarbons, C9, aromatics

Oral	LD50	3,592 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit)

Skin corrosion/irritation:

Dries skin out.

Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation: May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Experience with humans:

Frequent or longer lasting skin contact may degrease and dry out skin which may lead to skin irritation and inflammation (dermatitis).

Additional toxicological information:

Special characteristics/effects of isocyanates:

In case of over-exposure - especially when spraying isocyanate based varnishes without protective measures - there is a danger of a concentration-dependent, irritating effect on eyes, nose, throat, and respiratory tract. The delayed appearance of symptoms and the development of hypersensitivity (trouble breathing, cough, asthma) are possible. For hypersensitive persons, reactions may be triggered by very low isocyanate concentrations, also below the TLV value. In case of prolonged contact with skin, tanning and irritating effects are possible.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Harmful to fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Harmful to aquatic organisms

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 8 (replaces version 7)

Revision: 12.12.2022

Trade name **PRIMER PUR**

(Contd. of page 7)

SECTION 13: Disposal considerations

Recommendation

Liquid material remains are to be disposed of at collection facilities for old varnishes.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue



08 05 01* waste isocyanates

Uncleaned packaging:**Recommendation:**

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

SECTION 14: Transport information

14.1 UN number or ID number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT PAINT
14.3 Transport hazard class(es) ADR	
	
Class Label	3 (F1) Flammable liquids. 3
IMDG, IATA	
	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user hazard identification number: EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E,S-E A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 8 (replaces version 7)

Revision: 12.12.2022

Trade name **PRIMER PUR**

(Contd. of page 8)

Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

* SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 74

Regulation (EU) No 649/2012

CAS: 3648-18-8 dioctyltin dilaurate

Annex I Part 1

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations

Other regulations, limitations and prohibition ordinances

From the European Committee of the Associations for varnish, printing ink and artistry paint producers - CEPE - the following information is given for isocyanate based coating materials:

Ready-to-use coating materials that contain isocyanates may have an irritating effect on mucous membranes - especially on respiratory organs - and cause hypersensitivity reactions. There is a risk of sensitization if vapours or sprayed mist are inhaled. When handling isocyanate based coating materials, all measures for solvent based coating materials must be strictly observed. Sprayed mist and vapours especially should not be inhaled.

Persons with allergies or asthma who have a tendency for respiratory tract ailments should not be allowed to work with isocyanate based coating materials.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H360D May damage the unborn child.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 8 (replaces version 7)

Revision: 12.12.2022

Trade name **PRIMER PUR**

(Contd. of page 9)

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008 Calculation method**Department issuing data specification sheet:** Product Safety department / EHS**Date of previous version:** 10.05.2021**Version number of previous version:** 7**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 1: Acute toxicity – Category 1

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3