

Page 1/9

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 2 (replaces version 1)

Revision: 12.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1 Product identifier Trade name EPOXY PRIMER OS KOMP A

Article number: 0020605717

1.2 Relevant identified uses of the substance or mixture and uses advised against Product category PC9a Coatings and paints, thinners, paint removers Technical function Plating agent

# 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Remmers GmbH Bernhard-Remmers-Str. 13 D-49624 Löningen / Germany Mano Tel.: +49(0)5432/83-0 Fax: +49(0)5432/3985 Information department: Product Safety department: Phone: +44 (0) 1293 594 010 Email: sales@remmers.co.ukk

Remmers (UK) Limited Unit 4 , Lloyds Court Manor Royal, Crawley – West Sussex RH10 9QU fon +44 (0) 1293 594 010 fax +44 (0) 1293 594 037

# 1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111 In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number: within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

**SECTION 2: Hazards identification** 

### 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2H315 Causes skin irritation.Eye Irrit. 2H319 Causes serious eye irritation.Skin Sens. 1H317 May cause an allergic skin reaction.Aquatic Chronic 2H411 Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation. **Hazard pictograms** 



#### Signal word Warning

#### Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Page 2/9

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 2 (replaces version 1)

Revision: 12.12.2022

# Trade name EPOXY PRIMER OS KOMP A

(Contd. of page 1) Hazard statements H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects. **Precautionary statements** P261 Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid release to the environment. P273 Wear protective gloves/protective clothing/eye protection/face protection. P280 P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/container in accordance with local/regional/national/ international regulations. Additional information: EUH205 Contains epoxy constituents. May produce an allergic reaction. 2.3 Other hazards Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

**Description:** Modified epoxide resin

Dangerous components [% w/w]:		
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26- XXXX	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	≥50-≤70%
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40- XXXX	bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥10-<20%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22- XXXX	oxirane, mono[(C12-14-alkyloxy)methyl] derivs. Skin Irrit. 2, H315; Skin Sens. 1, H317	≥10-<20%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38- XXXX	benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332	≥5-<10%

Additional information For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures** 

# 4.1 Description of first aid measures General information

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

#### After inhalation

In case of cessation of respiration, give mouth-to-mouth / mouth-to-nose respiration.

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

#### After skin contact

Remove contaminated clothing.

Do not use solvents or thinners!

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 2 (replaces version 1)

Revision: 12.12.2022

# Trade name EPOXY PRIMER OS KOMP A

(Contd. of page 2) Wash immediately with water and soap and rinse thoroughly. Wash off immediately with water. After eye contact Seek immediate medical advice. Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor. After swallowing Seek immediate medical advice. 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available. 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

# 5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

# 5.2 Special hazards arising from the substance or mixture

Thick black smoke forms in fires. Inhalation of dangerous decomposition products may cause serious damage to your health.

5.3 Advice for firefighters

Protective equipment: Wear self-contained breathing apparatus.

### Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

### 6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

## 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

# Ensure adequate ventilation.

# 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

**SECTION 7: Handling and storage** 

# 7.1 Precautions for safe handling

Use only in well ventilated areas. Avoid contact with skin and eyes. Ensure good ventilation/exhaust in workplaces. Avoid the formation of aerosols. Information about protection against explosions and fires: No special requirements.

# 7.2 Conditions for safe storage, including any incompatibilities

Storage

# Requirements to be met by storerooms and containers:

Prevent any penetration into the ground. Store only in the original container. Information on storage in a common storage facility:

Keep away from highly acidic and alkaline materials as well as oxidizing agents. Store away from food.

# Further information about storage conditions:

Store container in a well ventilated position.

Keep container tightly closed.

according to 1907/2006/EC, Article 31 Version number 2 (replaces version 1)

Printing date 12.12.2022

Revision: 12.12.2022

# Trade name EPOXY PRIMER OS KOMP A

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.

Additional information: The lists that were valid during compilation were used as a basis.

#### 8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

### Individual protection measures, such as personal protective equipment General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.

#### Respiratory equipment:

#### Filter A (brown)

Only use ambient air independent respiratory equipment in pits, shafts and silos!

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

# Hand protection

### Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.

Body protection: Protective work clothing.

**SECTION 9: Physical and chemical properties** 

9.1 Information on basic physical and chemic	al properties	
General Information		
Physical state	Fluid	
Colour:	clear	
Odour:	Characteristic	
Odour threshold:	Not determined.	
Melting point/freezing point:	Not determined	
Boiling point or initial boiling point and boiling		
range	Not determined	
Flammability	Not applicable.	

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 2 (replaces version 1)

Revision: 12.12.2022

# Trade name EPOXY PRIMER OS KOMP A

(Contd. of page 4)

	(eonita: of page 4
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	>100 °C
Ignition temperature:	not applicable
Decomposition temperature:	Not determined.
• •	
pH Viacositur	Not determined.
Viscosity:	Mat data selected
Kinematic viscosity	Not determined.
dynamic at 20 °C:	800 mPas
Solubility	
Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	0.4 hPa
Density and/or relative density	
Density at 20 °C:	1.15 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health	
and environment, and on safety.	
Explosive properties:	Product is not explosive.
Solvent separation test	< 3 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard	
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

**SECTION 10: Stability and reactivity** 

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions Exothermic polymerisation

10.4 Conditions to avoid No further relevant information available.

**10.5 Incompatible materials:** No further relevant information available.

10.6 Hazardous decomposition products:

None if used properly.

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 2 (replaces version 1) Revision: 12.12.2022

# Trade name EPOXY PRIMER OS KOMP A

(Contd. of page 5)

None if stored properly. May be released in fire: Carbon monoxide and carbon dioxide smoke Nitrogen oxides (NOx)

**SECTION 11: Toxicological information** 

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity:** Based on available data, the classification criteria are not met.

# LD/LC50 values that are relevant for classification:

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral LD50 >10,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

# CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >4,500 mg/kg (rabbit)

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation.

Sensitisation: May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure:** Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

# 11.2 Information on other hazards

### **Endocrine disrupting properties**

None of the ingredients is listed.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

# 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

vPvB: Not applicable.

#### **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Toxic for fish

# Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system. Hazardous to drinking water even if small quantities leak into soil. Also toxic for fish and plankton in bodies of water. Toxic for aquatic organisms

# **SECTION 13: Disposal considerations**

# Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions. Page 7/9

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 2 (replaces version 1)

Revision: 12.12.2022

# Trade name EPOXY PRIMER OS KOMP A

(Contd. of page 6)

### European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

### Uncleaned packaging:

# Recommendation:

Disposal must be made according to official regulations. Packaging can be reused or recycled after cleaning.

# **SECTION 14: Transport information**

14.1 UN number or ID number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR IMDG	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin), MARINE POLLUTANT
ΙΑΤΑ	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
14.3 Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous hazardous substances and articles.
Label	9
IMDG	
Class Label	<ul><li>9 Miscellaneous hazardous substances and articles.</li><li>9</li></ul>
ΙΑΤΑ	
Class Label	9 Miscellaneous hazardous substances and articles. 9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous hazardous substances and articles.
hazard identification number:	90
EMS Number:	F-A,S-F
Stowage Category	Α

(Contd. on page 8)

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 2 (replaces version 1)

Revision: 12.12.2022

# Trade name EPOXY PRIMER OS KOMP A

(Contd. of page 7)

14.7 Maritime transport in bulk accord IMO instruments	ing to Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	(-)
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS
-	SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN), 9, III

**SECTION 15: Regulatory information** 

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

Newsofiles and electronic equipment – Anne

None of the ingredients is listed.

**REGULATION (EU) 2019/1148** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

# Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information** 

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

# **Relevant phrases**

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS Date of previous version: 25.11.2020

Version number of previous version: 1

Page 9/9

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 2 (replaces version 1)

Revision: 12.12.2022

# Trade name EPOXY PRIMER OS KOMP A

(Contd. of page 8)

Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2