

Page 1/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.10.2023 Version number 4 Revision: 05.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name PUR Top TX, Komp. A

Article number: 6330

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category PC9a Coatings and paints, thinners, paint removers

Application of the substance / the mixture Sealing

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH Remmers (UK) Limited Bernhard-Remmers-Str. 13 Unit 4 Lloyds Court D-49624 Löningen / Germany Manor Royal, Crawley - West Sussex RH10 9QU

Tel.: +49(0)5432/83-0 fon +44 (0) 1293 594 010 Fax: +49(0)5432/3985 fax +44 (0) 1293 594 037

Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 3 H331 Toxic if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS06

Signal word Danger

Hazard-determining components of labelling:

aliphatic polvisocvanate hexamethylene-di-isocyanate 4-isocyanatosulphonyltoluene

Printing date 05.10.2023 Version number 4 Revision: 05.10.2023

Trade name PUR Top TX, Komp. A

(Contd. of page 1)

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Hazard statements

H331 Toxic if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P284 Wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

Determination of endocrine-disrupting properties Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

EC number: 931-288-4 aliphatic polyisocyanate Reg.nr.: 01-2119488177-26- Acute Tox. 3, H331; Skin S	≥70-≤85%
XXXX H335, EUH204	letis. 1, 11317, 3101 3L 3,
CAS: 127519-17-9 ELINCS: 407-000-3 Index number: 607-281-00-4 Reg.nr.: 01-0000015648-61- XXXX A mixture of branched and (2H-benzotriazol-2-yl)-5-(1, hydroxyphenyl]propionates Aquatic Chronic 2, H411	1-dimethyl-ethyl)-4-
CAS: 4083-64-1	Irrit. 2, H315; Eye Irrit. 2, EUH014, EUH204 s: 6 5 %
EC number: 915-687-0 Reg.nr.: 01-2119491304-40- XXXX reaction mass of bis(1,2,2,6 piperidyl) sebacate and me 4-piperidyl sebacate Repr. 2, H361f; Aquatic Act Chronic 1, H410; Skin Sens	thyl 1,2,2,6,6-pentamethyl- ute 1, H400; Aquatic
CAS: 822-06-0 EINECS: 212-485-8 Index number: 615-011-00-1 Reg.nr.: 01-2119457571-37- XXXX hexamethylene-di-isocyana Acute Tox. 2, H330; Resp. 2, H315; Eye Irrit. 2, H319; SE 3, H335, EUH204 Specific concentration limits Resp. Sens. 1; H334: C≥ Skin Sens. 1; H317: C≥	Sens. 1, H334; Skin Irrit. Skin Sens. 1, H317; STOT s: ≥ 0.5 %
CAS: 108-65-6 2-methoxy-1-methylethyl action EINECS: 203-603-9 Flam. Liq. 3, H226; STOT S Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29- XXXX	

(Contd. on page 3)

Printing date 05.10.2023 Version number 4 Revision: 05.10.2023

Trade name PUR Top TX, Komp. A

(Contd. of page 2)

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after soiled clothing has been completely removed.

In case of irregular breathing or respiratory arrest, provide artificial respiration.

After inhalation

Take affected persons into the open air and position comfortably

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact Wash immediately with water and soap and rinse thoroughly.

After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Carbon dioxide

Foam

Fire-extinguishing powder

Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

May be released in case of fire

Carbon monoxide (CO)

Carbon dioxide

Nitrogen oxides (NOx)

Hydrogen cyanide (HCN)

(Traces)

further harmful conflagration gases and fumes

Formation of poisonous gases during heating or in fires.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

Put on breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Ensure adequate means of retaining the water used for extinguishing

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Put on breathing apparatus.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

Printing date 05.10.2023 Version number 4 Revision: 05.10.2023

Trade name PUR Top TX, Komp. A

(Contd. of page 3)

See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good ventilation/exhaust in workplaces.

Open and handle container with care.

Avoid the formation of aerosols.

Information about protection against explosions and fires: Keep breathing equipment ready.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: No special requirements.

Information on storage in a common storage facility: none

Further information about storage conditions:

Store container in a well ventilated position.

Protect from humidity and keep away from water.

Protect from frost.

Keep container tightly closed.

* SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Comp	Components with limit values that require monitoring at the workplace:					
CAS:	4083-64-1 4-isocyanatosulphonyltoluene					
WEL	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO					
CAS:	822-06-0 hexamethylene-di-isocyanate					
WEL	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO					
CAS:	108-65-6 2-methoxy-1-methylethyl acetate					
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk					
Ingredients with biological limit values:						
CAS: 822-06-0 hexamethylene-di-isocyanate						
BMG	V 1 μmol creatinine/mol Medium: urine					

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Sampling time: At the end of the period od exposure

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Parameter: isocyanate-derived diamine

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Store protective clothing separately.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.

(Contd. on page 5)

Printing date 05.10.2023 Version number 4 Revision: 05.10.2023

Trade name PUR Top TX, Komp. A

(Contd. of page 4)

Respiratory equipment:

Respiratory protection recommended.

Short term filter device:

Filter A/P2.

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Face protection

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical stateFluidColour:WhitishOdour:OdourlessOdour threshold:Not determined.Melting point/freezing point:Not determined

Boiling point or initial boiling point and boiling

range Not determined Flammability Not applicable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:>100 °C (Setaflash)Auto-ignition temperature:not applicableDecomposition temperature:Not determined.pHNot determined.

Viscosity:

Kinematic viscosity dynamic at 20 °C:Not determined.
2,000 mPas

Solubility

Water: Not miscible or difficult to mix

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure:

Not determined.

Density and/or relative density

Density at 20 °C:1.1 g/cm³Relative densityNot determined.Vapour densityNot determined.

9.2 Other information

Appearance:

Form: thixotropic

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 4 Revision: 05.10.2023 Printing date 05.10.2023

Trade name PUR Top TX, Komp. A

(Contd. of page 5)

Important information on protection of health and environment, and on safety. **Explosive properties:** Product is not explosive. Solvent separation test < 3 % **VOC EU** 5.4 a/l Change in condition **Evaporation rate** Not determined. Information with regard to physical hazard classes **Explosives** Void Flammable gases Void Void **Aerosols Oxidising gases** Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Oxidising solids Void Organic peroxides Void Corrosive to metals Void **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Toxic if inhaled.

LD/LC50 values that are relevant for classification: No further relevant information available.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation: May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: May cause respiratory irritation.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 7)

Printing date 05.10.2023 Version number 4 Revision: 05.10.2023

Trade name PUR Top TX, Komp. A

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects Remark: Harmful to fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

SECTION 14: Transport information

SECTION 14: Transport information						
14.1 UN number or ID number ADR, IMDG, IATA	UN2206					
14.2 UN proper shipping name ADR IMDG, IATA	2206 ISOCYANATES, TOXIC, N.O.S. (aliphatic polyisocyanate) ISOCYANATES, TOXIC, N.O.S. (aliphatic polyisocyanate)					
14.3 Transport hazard class(es)	polylosofanato/					
ADR						
Class Label	6.1 (T1) Toxic substances.6.1					
IMDG, IATA						
Class	6.1 Toxic substances.					

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.10.2023 Version number 4 Revision: 05.10.2023

Trade name PUR Top TX, Komp. A

(Contd. of page 7)

	(Conta. or page 1)
Label	6.1
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user hazard identification number: EMS Number: Stowage Category Stowage Code	Warning: Toxic substances. 60 F-A,S-A E SW1 Protected from sources of heat. SW2 Clear of living quarters.
14.7 Maritime transport in bulk according t IMO instruments	o Not applicable.
Transport/Additional information:	Not a hazardous good according to the above regulations.
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 2
Tunnel restriction code IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 2206 ISOCYANATES, TOXIC, N.O.S. (ALIPHATIC POLYISOCYANATE), 6.1, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category H2 ACUTE TOXIC

Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 74

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

(Contd. on page 9)

Version number 4 Printing date 05.10.2023 Revision: 05.10.2023

Trade name PUR Top TX, Komp. A

(Contd. of page 8)

Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H226	Flamma	ahla	liquid	and v	vanour
11220	I Iallilli	агис	11(1(1)(1	and	יוות אות או

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH014 Reacts violently with water.

EUH204 Contains isocyanates. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 2: Acute toxicity – Category 2
Acute Tox. 3: Acute toxicity – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3