

Page 1/9

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2023 Version number 5 (replaces version 4) Revision: 26.06.2023

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

## Trade name Epoxy UV 100 Komp. A

Article number: 6344

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product category PC9a Coatings and paints, thinners, paint removers

Application of the substance / the mixture Coating

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH

Bernhard-Remmers-Str. 13

Unit 4, Lloyds Court

D-49624 Löningen / Germany Manor Royal, Crawley – West Sussex RH10 9QU Tel.: +49(0)5432/83-0 fon +44 (0) 1293 594 010 Fax: +49(0)5432/3985 fax +44 (0) 1293 594 037

Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

#### 1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

### \* SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

#### **Hazard pictograms**





GHS07 GHS09

### Signal word Warning

#### Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) oxirane, mono[(C12-14-alkyloxy)methyl] derivs. bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

(Contd. on page 2)

Printing date 26.06.2023 Version number 5 (replaces version 4) Revision: 26.06.2023

## Trade name Epoxy UV 100 Komp. A

(Contd. of page 1)

#### **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling. P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection. P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P391 Collect spillage. **Additional information:** 

EUH205 Contains epoxy constituents. May produce an allergic reaction.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

**Description:** Mixture of the substances listed below with harmless additions.

Dangerous components [% w	/w]:	
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26- XXXX	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)  Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205  Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5% Eye Irrit. 2; H319: C ≥ 5 %	≥50-≤70%
CAS: 28064-14-4 NLP: 500-006-8 Reg.nr.: 01-2119454392-40- XXXX	bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥10-<20%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22- XXXX	oxirane, mono[(C12-14-alkyloxy)methyl] derivs. Skin Irrit. 2, H315; Skin Sens. 1, H317	≥10-<20%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38- XXXX	benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332	≥2.5-<5%
CAS: 108-83-8 EINECS: 203-620-1 Index number: 606-005-00-X Reg.nr.: 01-2119474441-41- XXXX	2,6-dimethylheptan-4-one Flam. Liq. 3, H226; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥10 %	≥0.25-≤0.5%
CAS: 41556-26-7 EINECS: 255-437-1	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	≥0.1-<0.25%

Additional information For the wording of the listed hazard phrases refer to section 16.

#### \* SECTION 4: First aid measures

## 4.1 Description of first aid measures General information

When symptoms occur or in case of doubt, seek medical advice Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Printing date 26.06.2023 Version number 5 (replaces version 4) Revision: 26.06.2023

## Trade name Epoxy UV 100 Komp. A

(Contd. of page 2)

#### After inhalation

Take affected persons into the open air and position comfortably

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact Wash immediately with water and soap and rinse thoroughly.

#### After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing Seek immediate medical advice.

#### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

#### Suitable extinguishing agents

Water spray jet

Carbon dioxide

Foam

Use fire fighting measures that suit the environment.

#### 5.2 Special hazards arising from the substance or mixture

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen chloride (HCI)

further harmful conflagration gases and fumes

#### 5.3 Advice for firefighters

#### **Protective equipment:**

Wear self-contained breathing apparatus.

Body protection

#### **Additional information**

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### \* SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

#### 6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

#### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

## 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

Requirements to be met by storerooms and containers: Prevent any penetration into the ground.

#### Information on storage in a common storage facility:

Store away from oxidising agents.

Store away from food.

(Contd. on page 4)

Printing date 26.06.2023

Version number 5 (replaces version 4) Revision: 26.06.2023

## Trade name Epoxy UV 100 Komp. A

(Contd. of page 3)

#### Further information about storage conditions:

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Components with limit values that require monitoring at the workplace:

CAS: 108-83-8 2,6-dimethylheptan-4-one

WEL Long-term value: 148 mg/m³, 25 ppm

Additional information: The lists that were valid during compilation were used as a basis.

#### 8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

#### Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.

#### Respiratory equipment:

Filter A (brown)

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

#### Hand protection

Long cuffed gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.

Body protection: Protective work clothing.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

**General Information** 

**Physical state** Fluid Colour: clear Odour: Odourless **Odour threshold:** Not determined.

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 26.06.2023 Version number 5 (replaces version 4) Revision: 26.06.2023

## Trade name Epoxy UV 100 Komp. A

(Contd. of page 4)

Melting point/freezing point:	Not determined
Boiling point or initial boiling point an	d boiling
range	Not determined
Flammability	Not applicable.

Lower and upper explosion limit

Lower: Not determined. Upper: Not determined. >100 °C Flash point: Ignition temperature: not applicable **Decomposition temperature:** Not determined. pН Not determined.

Viscosity:

Kinematic viscosity Not determined. dynamic at 20 °C: 750 mPas

Solubility

Water: Not miscible or difficult to mix

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C: 1.12 g/cm<sup>3</sup> Relative density Not determined. Not determined. Vapour density

#### 9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health

and environment, and on safety.

**Explosive properties:** Product is not explosive.

Solvent separation test < 3 % Organic solvents: 4.4 %

**VOC EU** 

**Solid content:** 70.5 %

Change in condition

Corrosive to metals

**Desensitised explosives** 

**Evaporation rate** Not determined.

#### Information with regard to physical hazard

classes **Explosives** Void Flammable gases Void **Aerosols** Void **Oxidising gases** Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void **Pyrophoric solids** Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void **Oxidising solids** Void Organic peroxides Void

#### SECTION 10: Stability and reactivity

Void

Void

## Safety data sheet

according to 1907/2006/EC, Article 31

Version number 5 (replaces version 4) Printing date 26.06.2023 Revision: 26.06.2023

## Trade name Epoxy UV 100 Komp. A

(Contd. of page 5)

#### 10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions Exothermic polymerisation

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

None if used properly.

None if stored properly.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC5	LD/LC50 values that are relevant for classification:				
CAS: 25	CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)				
Oral	LD50	>10,000 mg/kg (rat)			
Dermal	LD50	>2,000 mg/kg (rat)			
CAS: 68	CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs.				
Oral	LD50	>5,000 mg/kg (rat)			
Dermal	LD50	>4,500 mg/kg (rabbit)			

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation.

Sensitisation: May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met. STOT-single exposure: Based on available data, the classification criteria are not met. STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

#### **Endocrine disrupting properties**

None of the ingredients is listed.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

12.4 Mobility in soil No further relevant information available.

#### 12.5 Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

#### 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

#### 12.7 Other adverse effects

Remark: Toxic for fish

#### Additional ecological information:

#### **General notes:**

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

(Contd. on page 7)

Printing date 26.06.2023 Version number 5 (replaces version 4)

Trade name Epoxy UV 100 Komp. A

(Contd. of page 6)

Revision: 26.06.2023

#### **SECTION 13: Disposal considerations**

#### Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

#### European waste catalogue

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

#### **Uncleaned packaging:**

#### **Recommendation:**

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

### SECTION 14: Transport information

SECTION 14: Transport information	
14.1 UN number or ID number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR	3082 ENVIRONMENTALLY HAZARDOUS
IMDG	SUBSTANCE, LIQUID, N.O.S. (epoxy resin) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin), MARINE POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
14.3 Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous hazardous substances and articles.
Label	9
IMDG	
Class Label	Miscellaneous hazardous substances and articles.     9
IATA	
Class Label	9 Miscellaneous hazardous substances and articles. 9
14.4 Packing group ADR, IMDG, IATA	III
	(Contd. on page 9)

(Contd. on page 8)

Printing date 26.06.2023 Version number 5 (replaces version 4) Revision: 26.06.2023

## Trade name Epoxy UV 100 Komp. A

(Contd. of page 7)

Product contains environmentally hazardous substances: bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700)) Yes		
Symbol (fish and tree)		
Symbol (fish and tree)		
Warning: Miscellaneous hazardous substances and articles.		
90		
F-A,S-F		
A		
0		
Not applicable.		
5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml		
3		
(-)		
5L Code: 54		
Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml		
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN), 9, III		

### **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

#### **REGULATION (EU) 2019/1148**

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

(Contd. on page 9)

Printing date 26.06.2023 Version number 5 (replaces version 4)

## Trade name Epoxy UV 100 Komp. A

(Contd. of page 8)

Revision: 26.06.2023

Delivery specifications are found in the respective Technical Information Sheets.

#### Relevant phrases

H226	Flammab	le liqui	d and	vapour

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Date of previous version: 13.12.2022 Version number of previous version: 4

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2