

Page 1/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.10.2023 Version number 4 (replaces version 3) Revision: 17.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name EPOXY SIC COLOR KOMP A

Article number: 6844-6847

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating material

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH Remmers (UK) Limited
Bernhard-Remmers-Str. 13 Unit 4 , Lloyds Court

D-49624 Löningen / Germany Manor Royal, Crawley – West Sussex RH10 9QU Tel.: +49(0)5432/83-0 fon +44 (0) 1293 594 010 Fax: +49(0)5432/3985 fax +44 (0) 1293 594 037

Information department:

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

* SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Aguatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS07 GHS09

Signal word Warning

Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

1,6-Bis(2,3-epoxypropoxy)hexan

(Contd. on page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.10.2023 Version number 4 (replaces version 3) Revision: 17.10.2023

Trade name EPOXY SIC COLOR KOMP A

(Contd. of page 1)

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash contaminated body parts thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P321 Specific treatment (see on this label).

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention. P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

P332+P313

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

Determination of endocrine-disrupting properties Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:		
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26- XXXX	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	≥25-<30%
CAS: 28064-14-4 NLP: 500-006-8 Reg.nr.: 01-2119454392-40- XXXX	bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) Skin Irrit. 2, H315; Skin Sens. 1, H317	≥5-<10%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17- XXXX	titanium dioxide Carc. 2, H351	≥5-<10%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22- XXXX	oxirane, mono[(C12-14-alkyloxy)methyl] derivs. Skin Irrit. 2, H315; Skin Sens. 1, H317	≥2.5-<5%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38- XXXX	benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332	≥1-<2.5%

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 17.10.2023 Version number 4 (replaces version 3) Revision: 17.10.2023

Trade name EPOXY SIC COLOR KOMP A

(Contd. of page 2)

CAS: 16096-31-4	1,6-Bis(2,3-epoxypropoxy)hexan	≥0.5-<1%
EINECS: 240-260-4	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1,	
	H317; Aquatic Chronic 3, H412	
XXXX		

Additional information For the wording of the listed hazard phrases refer to section 16.

* SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact Wash immediately with water and soap and rinse thoroughly.

After eve contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

Formation of poisonous gases during heating or in fires.

5.3 Advice for firefighters

Protective equipment: Put on breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Put on breathing apparatus.

6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

Dilute with plenty of water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

Information about protection against explosions and fires: Keep breathing equipment ready.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: No special requirements.

Further information about storage conditions: Keep container tightly closed.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Version number 4 (replaces version 3) Printing date 17.10.2023 Revision: 17.10.2023

Trade name EPOXY SIC COLOR KOMP A

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

CAS: 13463-67-7 titanium dioxide

WEL Long-term value: 10* 4** mg/m³

*total inhalable **respirable

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euigment is not required or the amount of the PPE can be adpated accordingly.

Respiratory equipment:

Filter A (brown)

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eve/face protection Tightly sealed safety glasses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid

Colour: According to product specification

Odour: Characteristic **Odour threshold:** Not determined. Melting point/freezing point: Not determined

Boiling point or initial boiling point and boiling

Not determined **Flammability** Not applicable.

Lower and upper explosion limit

Lower: Not determined. Upper: Not determined.

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 17.10.2023 Version number 4 (replaces version 3) Revision: 17.10.2023

Trade name EPOXY SIC COLOR KOMP A

(Contd. of page 4)

Flash point: >100 °C **Auto-ignition temperature:** not applicable Not determined. **Decomposition temperature:** Not determined. Viscosity:

Kinematic viscosity Not determined. dynamic: Not determined.

Solubility

Water: Fully miscible Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C: 1.697 g/cm³ Relative density Not determined. Vapour density Not determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health

and environment, and on safety.

Explosive properties: Product is not explosive.

Solvent separation test < 3 % **VOC EU** <130 g/l

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard

classes **Explosives** Void Flammable gases Void Void **Aerosols Oxidising gases** Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void **Pyrophoric solids** Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void Oxidising solids Void Organic peroxides Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability

Corrosive to metals

Desensitised explosives

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

Void

Void

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 17.10.2023

Version number 4 (replaces version 3)

Trade name EPOXY SIC COLOR KOMP A

(Contd. of page 5)

Revision: 17.10.2023

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

LD50 >10,000 mg/kg (rat) Dermal LD50 >2,000 mg/kg (rat)

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation.

Sensitisation: May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met. STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met. Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Toxic for fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

Recommendation

Do not dispose of together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

Recommended cleaning agent: Water, if necessary with cleaning agent.

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.10.2023 Version r

Version number 4 (replaces version 3)

Trade name EPOXY SIC COLOR KOMP A

(Contd. of page 6)

Revision: 17.10.2023

	(Contd. of page 6)		
SECTION 14: Transport information			
14.1 UN number or ID number ADR, IMDG, IATA	UN3082		
14.2 UN proper shipping name ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)		
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE.		
1010	LIQUID, N.O.S. (epoxy resin)		
14.3 Transport hazard class(es)			
ADR			
Class Label	9 (M6) Miscellaneous hazardous substances and articles.		
IMDG			
Class Label	Miscellaneous hazardous substances and articles. 9		
IATA			
Class Label	9 Miscellaneous hazardous substances and articles.9		
14.4 Packing group ADR, IMDG, IATA	III		
14.5 Environmental hazards: Marine pollutant: Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)		
14.6 Special precautions for user	Warning: Miscellaneous hazardous substances and articles.		
hazard identification number: EMS Number: Stowage Category	90 F-A,S-F A		
14.7 Maritime transport in bulk according IMO instruments	14.7 Maritime transport in bulk according to		
Transport/Additional information:			
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml		
Transport category	3		

according to 1907/2006/EC, Article 31

Printing date 17.10.2023 Version number 4 (replaces version 3) Revision: 17.10.2023

Trade name EPOXY SIC COLOR KOMP A

(Contd. of page 7)

Tunnel restriction code	(-)
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

May cause an allergic skin reaction. H317

Causes serious eye irritation. H319

H332 Harmful if inhaled.

H351 Suspected of causing cancer.

Toxic to aquatic life with long lasting effects. H411

Harmful to aquatic life with long lasting effects. H412

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Version number of previous version: 3

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 9)

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.10.2023

Version number 4 (replaces version 3)

Trade name EPOXY SIC COLOR KOMP A

(Contd. of page 8)

Revision: 17.10.2023

vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3