

Page 1/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 5 (replaces version 4)

Revision: 13.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name UNTERWASSERPRIMER, KOMP. A

Article number: 7450

 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 Product category PC9a Coatings and paints, thinners, paint removers
 Application of the substance / the mixture Priming

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: Remmers GmbH Bernhard-Remmers-Str. 13 D-49624 Löningen / Germany Tel.: +49(0)5432/83-0 Fax: +49(0)5432/3985 Information department: Product Safety department: Phone: +44 (0) 1293 594 010 Email: sales@remmers.co.ukk

Remmers (UK) Limited Unit 4 , Lloyds Court Manor Royal, Crawley – West Sussex RH10 9QU fon +44 (0) 1293 594 010 fax +44 (0) 1293 594 037

1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111 In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number: within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2H315 Causes skin irritation.Eye Irrit. 2H319 Causes serious eye irritation.Skin Sens. 1H317 May cause an allergic skin reaction.Ann tic Olumit 0H4111 Texis to provide the series of the series

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation. **Hazard pictograms**



Signal word Warning

Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) [[(2-ethylhexyl)oxy]methyl]oxirane

Page 2/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 5 (replaces version 4)

Revision: 13.12.2022

Trade name UNTERWASSERPRIMER, KOMP. A

		(Contd. of page 1)
Hazard statement	ls	
H315 Causes skin	irritation.	
H319 Causes serie	bus eye irritation.	
H317 May cause a	n allergic skin reaction.	
H411 Toxic to aqu	atic life with long lasting effects.	
Precautionary sta	Itements	
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read carefully and follow all instructions.	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
P273	Avoid release to the environment.	
P280	Wear protective gloves / eye protection / face protection.	
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.	
P321	Specific treatment (see on this label).	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for bro	eathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove	contact
	lenses, if present and easy to do. Continue rinsing.	
P312	Call a POISON CENTER/doctor if you feel unwell.	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P501	Dispose of contents/container in accordance with local/regional/nation	al/
	international regulations.	
Additional inform	ation:	
EUH205 Contains	epoxy constituents. May produce an allergic reaction.	
2.3 Other hazards	6	
Results of PBT a	nd vPvB assessment	

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

Dangerous components [% w/	w]:	
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317, EUH205	≥70-≤85%
XXXX	Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	
CAS: 28064-14-4 NLP: 500-006-8 Reg.nr.: 01-2119454392-40- XXXX	bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥10-<20%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38- XXXX	benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332	≥5-<10%
CAS: 2461-15-6 EINECS: 219-553-6 Reg.nr.: 01-2119962196-31- XXXX	[[(2-ethylhexyl)oxy]methyl]oxirane Skin Irrit. 2, H315; Skin Sens. 1, H317	≥1-<2.5%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When symptoms occur or in case of doubt, seek medical advice Immediately remove any clothing soiled by the product. Page 3/9

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 5 (replaces version 4)

Printing date 13.12.2022

Revision: 13.12.2022

Trade name UNTERWASSERPRIMER, KOMP. A

(Contd. of page 2)

 After inhalation

 Take affected persons into the open air and position comfortably

 Supply fresh air and call for doctor for safety reasons.

 In case of unconsciousness bring patient into stable side position for transport.

 After skin contact Wash immediately with water and soap and rinse thoroughly.

 After eye contact

 Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

 After swallowing Seek immediate medical advice.

 4.2 Most important symptoms and effects, both acute and delayed

 No further relevant information available.

 4.3 Indication of any immediate medical attention and special treatment needed

 No further relevant information available.

 SECTION 5: Firefighting measures

 5.1 Extinguishing media

 Switchle optimewishing media

Suitable extinguishing agents Water spray jet Carbon dioxide Foam Fire-extinguishing powder Use fire fighting measures that suit the environment. 5.2 Special hazards arising from the substance or mixture May be released in case of fire Carbon monoxide (CO) Carbon dioxide carbon monoxides Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.: Hydrogen chloride (HCI) further harmful conflagration gases and fumes 5.3 Advice for firefighters **Protective equipment:** Wear self-contained breathing apparatus. Wear full protective suit. Additional information Cool endangered containers with water spray jet. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas. Avoid contact with skin. Ensure good ventilation/exhaust in workplaces. Page 4/9

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 5 (replaces version 4)

Printing date 13.12.2022

Revision: 13.12.2022

Trade name UNTERWASSERPRIMER, KOMP. A

(Contd. of page 3)

Avoid the formation of aerosols.

7.2 Conditions for safe storage, including any incompatibilities Storage Requirements to be met by storerooms and containers: Prevent any penetration into the ground. Information on storage in a common storage facility: Store away from food. Further information about storage conditions: Store container in a well ventilated position. Protect from frost. Keep container tightly closed. SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.

Respiratory equipment:

Filter A (brown)

Only use ambient air independent respiratory equipment in pits, shafts and silos!

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Hand protection

Long cuffed gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.

Body protection:

Use protective suit.

Boots

Page 5/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 5 (replaces version 4)

Revision: 13.12.2022

Trade name UNTERWASSERPRIMER, KOMP. A

(Contd. of page 4)

If body contact is possible, wear suitable arm protection.

SECTION 9: Physical and chemical propert	
9.1 Information on basic physical and chemical	properties
General Information	F I-14
Physical state	Fluid
Colour:	Clear
Odour:	Weak, characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling	
range	>100 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	>100 °C (Setaflash)
Ignition temperature:	not applicable
Decomposition temperature:	Not determined.
pH .	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic at 20 °C:	950 mPas
Solubility	
Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	
	pure epoxide resin
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	1.16 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health	
and environment, and on safety.	
Explosive properties:	Product is not explosive.
Solvent separation test	< 3 %
Organic solvents:	9.9 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard	
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
	Void
Self-heating substances and mixtures	Void
Self-heating substances and mixtures Substances and mixtures, which emit	
Self-heating substances and mixtures	Void Void Void

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 5 (replaces version 4)

Printing date 13.12.2022

Revision: 13.12.2022

Trade name UNTERWASSERPRIMER, KOMP. A

(Contd. of page 5)

		· · · · ·
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions

May produce violent reactions with bases and numerous organic substances including alcohols and amines

Exothermic polymerisation

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

None if used properly.

None if stored properly.

May be released in fire:

Carbon monoxide and carbon dioxide

Hydrogen chloride (HCI)

Irritating gases/vapours

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral LD50 >10,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation.

Sensitisation: May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

Page 7/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 5 (replaces version 4)

Revision: 13.12.2022

Trade name UNTERWASSERPRIMER, KOMP. A

(Contd. of page 6)

12.7 Other adverse effects Remark: Toxic for fish Additional ecological information:
General notes: Do not allow product to reach ground water, bodies of water or sewage system. Hazardous to drinking water even if small quantities leak into soil. Also toxic for fish and plankton in bodies of water. Toxic for aquatic organisms

SECTION 13: Disposal considerations

Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

20 01 28 paint, inks, adhesives and resins other than those mentioned in 20 01 27

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations. Packaging can be reused or recycled after cleaning.

SECTION 14: Transport information

14.1 UN number or ID number	
ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR IMDG	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700)), bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700)), bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700)),
ΙΑΤΑ	MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol A-(epichlorhydrin) (number average molecular weight ≤ 700)), bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700))
14.3 Transport hazard class(es)	
ADR	
Class	9 (M6) Miscellaneous hazardous substances and articles.
Label	9

(Contd. on page 8)

Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 5 (replaces version 4)

Revision: 13.12.2022

Trade name UNTERWASSERPRIMER, KOMP. A

(Contd. of page 7)

9 Miscellaneous hazardous substances and articles. 9 9 Miscellaneous hazardous substances and articles. 9 III Product contains environmentally hazardous substances: Epoxy Resin (reaction product: bispheno A-(epichlorhydrin) (number average molecular weight ≤ 700)) Yes Symbol (fish and tree)
9 9 Miscellaneous hazardous substances and articles. 9 III Product contains environmentally hazardous substances: Epoxy Resin (reaction product: bispheno A-(epichlorhydrin) (number average molecular weight ≤ 700)) Yes Symbol (fish and tree)
9 9 Miscellaneous hazardous substances and articles. 9 III Product contains environmentally hazardous substances: Epoxy Resin (reaction product: bispheno A-(epichlorhydrin) (number average molecular weight ≤ 700)) Yes Symbol (fish and tree)
9 Miscellaneous hazardous substances and articles. 9 III Product contains environmentally hazardous substances: Epoxy Resin (reaction product: bispheno A-(epichlorhydrin) (number average molecular weight ≤ 700)) Yes Symbol (fish and tree)
9 III Product contains environmentally hazardous substances: Epoxy Resin (reaction product: bispheno A-(epichlorhydrin) (number average molecular weight ≤ 700)) Yes Symbol (fish and tree)
9 III Product contains environmentally hazardous substances: Epoxy Resin (reaction product: bispheno A-(epichlorhydrin) (number average molecular weight ≤ 700)) Yes Symbol (fish and tree)
Product contains environmentally hazardous substances: Epoxy Resin (reaction product: bispheno A-(epichlorhydrin) (number average molecular weight ≤ 700)) Yes Symbol (fish and tree)
substances: Epoxy Resin (reaction product: bispheno A-(epichlorhydrin) (number average molecular weight ≤ 700)) Yes Symbol (fish and tree)
Symbol (fish and tree)
Symbol (fish and tree)
Warning: Miscellaneous hazardous substances and articles.
90
F-A,S-F A
)
Not applicable.
5L Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml 3
5L
Code: E1 Maximum pet quantity per inper packaging: 30 ml
Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN (REACTION PRODUCT: BISPHENOL A- (EPICHLORHYDRIN) (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), BISPHENOL F- (EPICHLORHYDRIN); EPOXY RESIN(NUMBER AVERAGE MOLECULAR WEIGHT<700)), 9, III

(Contd. on page 9)

Page 9/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.12.2022

Version number 5 (replaces version 4)

Revision: 13.12.2022

Trade name UNTERWASSERPRIMER, KOMP. A

(Contd. of page 8)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations

Other regulations, limitations and prohibition ordinances

APME document: "Epoxy resins and curing agents: Toxicology, working safety, environment." **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS **Date of previous version:** 23.02.2018

Version number of previous version: 4

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2