

Page 1/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name PUR BASE WPM KOMP.B

Article number: 6065

1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. **Application of the substance / the mixture** Coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Remmers GmbH Bernhard-Remmers-Str. 13 D-49624 Löningen / Germany Mano Tel.: +49(0)5432/83-0 Fax: +49(0)5432/3985 Information department: Product Safety department: Phone: +44 (0) 1293 594 010 Email: sales@remmers.co.ukk

Remmers (UK) Limited Unit 4 , Lloyds Court Manor Royal, Crawley – West Sussex RH10 9QU fon +44 (0) 1293 594 010 fax +44 (0) 1293 594 037

1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111 In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number: within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled.

- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2 H319 Causes serious eye irritation.
- Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Carc. 2 H351 Suspected of causing cancer.
- STOT SE 3 H335 May cause respiratory irritation.
- STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation. **Hazard pictograms**



Signal word Danger

Page 2/9

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 4 (replaces version 3)

Printing date 14.12.2022

Hazard statements H332 Harmful if inhaled. Revision: 14.12.2022

(Contd. of page 1)

Trade name PUR BASE WPM KOMP.B

Hazard-determining components of labelling:

diphenylmethanediisocyanate, isomeres and homologues

H315 Causes skin irritation. H319 Causes serious eye irritation.

diphenylmethane-2,4'-diisocyanate 4,4'-methylenediphenyl diisocyanate

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

	P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
	P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing	
		protection.	
	P302+P352	IF ON SKIN: Wash with plenty of soap and water.	
	P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact	
		lenses, if present and easy to do. Continue rinsing.	
	P308+P313	IF exposed or concerned: Get medical advice/attention.	
	P501	Dispose of contents/container in accordance with local/regional/national/	
		international regulations.	
Additional information:			
	EUH204 Contains isocvanates. May produce an allergic reaction.		

nales. Ma

As from 24 August 2023 adequate training is required before industrial or professional use.

2.3 Other hazards

Results of PBT and vPvB assessment PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:		
CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: $C \ge 5 \%$ Skin Irrit. 2; H315: $C \ge 5 \%$ Resp. Sens. 1; H334: $C \ge 0.1 \%$ STOT SE 3; $C \ge 5 \%$	≥50-≤70%

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

Trade name PUR BASE WPM KOMP.B

	(Ce	ontd. of page 2)
CAS: 5873-54-1	diphenylmethane-2,4'-diisocyanate	≥10-<20%
EINECS: 227-534-9 Index number: 615-005-00-9 Reg.nr.: 01-2119480143-45- XXXX	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: $C \ge 5$ % Skin Irrit. 2; H315: $C \ge 5$ % Resp. Sens. 1; H334: $C \ge 0.1$ % STOT SE 3; $C \ge 5$ %	
CAS: 101-68-8 EINECS: 202-966-0 Index number: 615-005-00-9 Reg.nr.: 01-2119457014-47- XXXX	4,4'-methylenediphenyl diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: $C \ge 5$ % Skin Irrit. 2; H315: $C \ge 5$ % Resp. Sens. 1; H334: $C \ge 0.1$ % STOT SE 3; $C \ge 5$ %	≥10-<20%

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Call a doctor immediately.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact Wash immediately with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor. **After swallowing** Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

 CO_{\Box} , extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. **5.2 Special hazards arising from the substance or mixture**

May be released in case of fire

Carbon dioxide

Carbon monoxide (CO)

Nitrogen oxides (NOx) Isocyanate fumes

(Traces)

(Haces) Hydrogen cyanide (HCN)

Formation of poisonous gases during heating or in fires.

5.3 Advice for firefighters

Protective equipment:

Wear self-contained breathing apparatus.

Wear full protective suit.

Put on breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Page 4/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

Trade name PUR BASE WPM KOMP.B

(Contd. of page 3)

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Put on breathing apparatus.

6.2 Environmental precautions: Do not allow to enter the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas. Ensure good ventilation/exhaust in workplaces. Avoid the formation of aerosols.

Information about protection against explosions and fires: Keep breathing equipment ready.

7.2 Conditions for safe storage, including any incompatibilities Storage

Requirements to be met by storerooms and containers: Store only in the original container. Prevent any penetration into the ground. Information on storage in a common storage facility: none Further information about storage conditions: Store container in a well ventilated position. Protect from humidity and keep away from water. Protect from frost. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:	
CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues	
WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO	
CAS: 5873-54-1 diphenylmethane-2,4'-diisocyanate	
WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO	
CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate	
WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO	
Ingredients with biological limit values:	
CAS: 5873-54-1 diphenylmethane-2,4'-diisocyanate	
BMGV 1 μmol creatinine/mol Medium: urine Sampling time: At the end of the period od exposure Parameter: isocyanate-derived diamine	
	(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

Trade name PUR BASE WPM KOMP.B

(Contd. of page 4)

CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate

BMGV 1 µmol creatinine/mol Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Store protective clothing separately.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.

Respiratory equipment:

Short term filter device:

Filter A (brown)

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Hand protection

Impervious gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Face protection

Tightly sealed safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties General Information		
Physical state	Fluid	
Colour:	Brown	
Odour:	Characteristic	
Odour threshold:	Not determined.	
Melting point/freezing point:	Not determined	
Boiling point or initial boiling point and	boiling	
range	> 300 °C	

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

Trade name PUR BASE WPM KOMP.B

	(Contd. of page
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	220 °C
Ignition temperature:	>500 °C
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
dynamic at 20 °C:	70 mPas
Solubility	
Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	
Vapour pressure:	ca. 19 hPa
Density and/or relative density	Ca. 1911Fa
Density at 20 °C:	$1.02 \mathrm{a/om^3}$
	1.22 g/cm ³ Not determined.
Relative density	
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health	
and environment, and on safety.	
Explosive properties:	Product is not explosive.
Solvent separation test	< 3 %
Organic solvents:	0.0 %
Change in condition	
Evaporation rate	Not determined.
•	
Information with regard to physical hazard	
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions Danger of bursting

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

Page 7/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

Trade name PUR BASE WPM KOMP.B

(Contd. of page 6)

10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity: Harmful if inhaled.

LD/LC50 values that are relevant for classification:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues		
Oral	LD50	>10,000 mg/kg (rat)
Dermal	LD50	>9,400 mg/kg (rabbit)
Inhalative	LC50/4 h	1.5 mg/l (rat)
CAS: 101-	CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate	
Oral	LD50	>15,000 mg/kg (rat)
Inhalative	LC50/4 h	~0.49 mg/l (rat)

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation.

Sensitisation:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Suspected of causing cancer.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: May cause respiratory irritation.

STOT-repeated exposure: May cause damage to organs through prolonged or repeated exposure. **Aspiration hazard:** Based on available data, the classification criteria are not met.

Additional toxicological information:

Special characteristics/effects of isocyanates:

In case of over-exposure - especially when spraying isocyanate based varnishes without protective measures - there is a danger of a concentration-dependent, irritating effect on eyes, nose, throat, and respiratory tract. The delayed appearance of symptoms and the development of hypersensitivity (trouble breathing, cough, asthma) are possible. For hypersensitive persons, reactions may be triggered by very low isocyanate concentrations, also below the TLV value. In case of prolonged contact with skin, tanning and irritating effects are possible.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Do not allow undiluted or larger quantities of the product to reach ground water, bodies fo water or sewage system.

(Contd. on page 8)

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 4 (replaces version 3)

Revision: 14.12.2022

Trade name PUR BASE WPM KOMP.B

(Contd. of page 7)

SECTION 13: Disposal considerations

Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions. Do not dispose of together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 05 01* waste isocyanates

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations. Packaging can be reused or recycled after cleaning.

SECTION 14: Transport information

Void
Void
Void
Void
No
Not applicable.
to Not applicable.
Not a hazardous good according to the above regulations.
Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU Named dangerous substances - ANNEX I None of the ingredients is listed. REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 56a, 56b, 74 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II None of the ingredients is listed. REGULATION (EU) 2019/1148 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of

licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 9)

according to 1907/2006/EC, Article 31 Version number 4 (replaces version 3)

Printing date 14.12.2022

Revision: 14.12.2022

(Contd. of page 8)

Trade name PUR BASE WPM KOMP.B

National regulations

Other regulations, limitations and prohibition ordinances

From the European Committee of the Associations for varnish, printing ink and artistry paint producers - CEPE - the following information is given for isocyanate based coating materials:

Ready-to-use coating materials that contain isocyanates may have an irritating effect on mucous membranes - especially on respiratory organs - and cause hypersensitivity reactions. There is a risk of sensitization if vapours or sprayed mist are inhaled. When handling isocyanate based coating materials, all measures for solvent based coating materials must be strictly observed. Sprayed mist and vapours especially should not be inhaled.

Persons with allergies or asthma who have a tendency for respiratory tract ailments should not be allowed to work with isocyanate based coating materials.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H315 Causes skin irritation.

- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

EUH204 Contains isocvanates. May produce an allergic reaction.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS Date of previous version: 12.06.2017

Version number of previous version: 3

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2