

Page 1/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 6 (replaces version 5)

Revision: 14.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name EPOXY UV 100 TX, KOMP. B

Article number: 6300

1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. **Application of the substance / the mixture** Coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Remmers GmbH Bernhard-Remmers-Str. 13 D-49624 Löningen / Germany Mano Tel.: +49(0)5432/83-0 Fax: +49(0)5432/3985 Information department: Product Safety department: Phone: +44 (0) 1293 594 010 Email: sales@remmers.co.ukk

Remmers (UK) Limited Unit 4 , Lloyds Court Manor Royal, Crawley – West Sussex RH10 9QU fon +44 (0) 1293 594 010 fax +44 (0) 1293 594 037

1.4 Emergency telephone number:

National Poisons Information Service (NPIS): In England and Wales: NHS 111 - dial 111 In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number: within USA and Canada: 1-800-424-9300 outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4	H302 Harmful if swallowed.
Acute Tox. 4	H312 Harmful in contact with skin.
Skin Corr. 1A	H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.
Skin Sens. 1	H317 May cause an allergic skin reaction.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation. **Hazard pictograms**



Signal word Danger

Hazard-determining components of labelling: benzyl alcohol 3,6,9-triazaundecamethylenediamine Page 2/9

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 6 (replaces version 5) Revision

Revision: 14.12.2022

1)

Trade name EPOXY UV 100 TX, KOMP. B

(Contd. of page				
3-aminomethyl-3,5,5-trimethylcyclohexylamine				
2-methylpentane-1,5-diamine				
2,4,6-tris(dimethylaminomethyl)phenol				
Hazard statements				
H302+H312 Harmful if swallowed or in contact with skin.				
H314 Causes severe skin burns and eye damage.				
H317 May cause an allergic skin reaction.				
H412 Harmful to aquatic life with long lasting effects.				
Precautionary statements				
P260 Do not breathe dust/fume/gas/mist/vapours/spray.				
P273 Avoid release to the environment.				
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing				
protection.				
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.				
P302+P352 IF ON SKIN: Wash with plenty of soap and water.				
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.				
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact				
lenses, if present and easy to do. Continue rinsing.				
P312 Call a POISON CENTER/doctor if you feel unwell.				
P501 Dispose of contents/container in accordance with local/regional/national/				
international regulations.				
2.3 Other hazards				
Results of PBT and vPvB assessment				

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Epoxy resin hardener, formulation based on aliphatic polyamines

Dangerous components [% w	//w]:	
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38- XXXX	benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332	≥30-<40%
CAS: 38294-64-3 NLP: 500-101-4 Reg.nr.: 01-2119965165-33- XXXX	Reaktionprodukte von 3-Aminomethyl-3,5,5- trimethylcyclohexylamin und 4,4'-Isopropylidendiphenol, oligomerisches Reaktionprodukt mit 1-Chlor-2,3- epoxypropan Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥25-<30%
CAS: 112-57-2 EINECS: 203-986-2 Index number: 612-060-00-0	3,6,9-triazaundecamethylenediamine Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	≥20-<25%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32- XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1A, H317 ATE: LD50 oral: 1,030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥10-<20%
CAS: 15520-10-2 EINECS: 239-556-6 Reg.nr.: 01-2119976310-41- XXXX	2-methylpentane-1,5-diamine Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; STOT SE 3, H335	≥3-<5%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27- XXXX	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1B, H314; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<2.5%

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 6 (replaces version 5)

Revision: 14.12.2022

Trade name EPOXY UV 100 TX, KOMP. B

(Contd. of page 2)

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4:	First aid	measures	

4.1 Description of first aid measures

General information

When symptoms occur or in case of doubt, seek medical advice

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation

Take affected persons into the open air and position comfortably

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact Wash immediately with water and soap and rinse thoroughly.

After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing

Call a doctor immediately.

Drink plenty of water and provide fresh air. Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing agents Use fire fighting measures that suit the environment. 5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire. May be released in case of fire Carbon monoxide (CO) Carbon dioxide Nitrogen oxides (NOx) Nitrous gases Formation of poisonous gases during heating or in fires. 5.3 Advice for firefighters **Protective equipment:** Wear self-contained breathing apparatus. Wear full protective suit. Put on breathing apparatus. Additional information Cool endangered containers with water spray jet. Collect contaminated fire fighting water separately. It must not enter drains. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources

Ensure adequate ventilation

Put on breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

Dilute with plenty of water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

according to 1907/2006/EC, Article 31 Version number 6 (replaces version 5)

Printing date 14.12.2022

Revision: 14.12.2022

(Contd. of page 3)

Trade name EPOXY UV 100 TX, KOMP. B

6.4 Reference to other sections

See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas. Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

Information about protection against explosions and fires: Keep breathing equipment ready.

7.2 Conditions for safe storage, including any incompatibilities

 Storage

 Requirements to be met by storerooms and containers: No special requirements.

 Information on storage in a common storage facility:

 Store away from oxidising agents.

 Store away from food.

 Further information about storage conditions:

 Store container in a well ventilated position.

 Protect from frost.

 Keep container tightly closed.

 SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Appropriate engineering controls No further data; see item 7.

Individual protection measures, such as personal protective equipment General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evalutated by the employer depending on the types of operations and the local circumstances. If a risk assessment onsite shows that there is no risk for employees, the personal protective euiqment is not required or the amount of the PPE can be adpated accordingly.

Respiratory equipment:

Filter A (brown)

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Hand protection

Long cuffed gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

according to 1907/2006/EC, Article 31 Version number 6 (replaces version 5)

Printing date 14.12.2022

Revision: 14.12.2022

(Contd. of page 4)

Trade name EPOXY UV 100 TX, KOMP. B

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical	properties
General Information	
Physical state	Fluid
Colour:	Clear
Odour:	Amine-like
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
	Not determined
Boiling point or initial boiling point and boiling	
range	>200 °C
Flammability	Not applicable.
Lower and upper explosion limit	
	1.2.1/0/
Lower:	1.3 Vol %
	1.2 %
Upper:	13 Vol %
	13 %
Flash point:	>100 °C
Ignition temperature:	321 °C
	321 °C
Decomposition temperature:	Not determined.
pH at 20 °C	12
Viscosity:	
Kinematic viscosity	Not determined.
dynamic at 20 °C:	250 mPas
Solubility	
Water:	Fully miscible
Partition coefficient n-octanol/water (log value)	
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.99 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health	
and environment, and on safety.	
Explosive properties:	Product is not explosive.
Solvent separation test	< 3 %
Organic solvents:	47.0 %
	U. U. U
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard	
classes	
	N/-:
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Gases under pressure	volu

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 6 (replaces version 5)

Revision: 14.12.2022

Trade name EPOXY UV 100 TX, KOMP. B

		(Contd. of page 5)
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions Reacts with strong oxidising agents

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: Strong oxidising agents

10.6 Hazardous decomposition products:

None if used properly.

None if stored properly.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity: Harmful if swallowed or in contact with skin.

LD/LC50 values that are relevant for classification:		
CAS: 100-51-6 benzyl alcohol		
Oral	LD50	1,620 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Oral	LD50	1,030 mg/kg (ATE)
		1,030 mg/kg (rat)
Dermal	LD50	1,840 mg/kg (rabbit)
Skin corrosion/irritation: Causes severe skin burns and eye damage.		

Serious eye damage/irritation:

Caustic effect

Causes serious eye damage.

Sensitisation: May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure: Based on available data, the classification criteria are not met. **STOT-repeated exposure:** Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

Page 7/9

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 6 (replaces version 5)

Printing date 14.12.2022

Revision: 14.12.2022

Trade name EPOXY UV 100 TX, KOMP. B

(Contd. of page 6)

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Harmful to fish

Additional ecological information:

General notes:

Do not allow undiluted or non-neutralised product to reach the sewage system or receiving waters. Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Harmful to aquatic organisms

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

Do not allow undiluted or larger quantities of the product to reach ground water, bodies fo water or sewage system.

SECTION 13: Disposal considerations

Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue08 01 11*waste paint and varnish containing organic solvents or other hazardous substances20 01 28paint, inks, adhesives and resins other than those mentioned in 20 01 27

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations. Packaging can be reused or recycled after cleaning.

Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information

14.1 UN number or ID number	
ADR, IMDG, IATA	UN2735
14.2 UN proper shipping name ADR IMDG, IATA	2735 AMINES, LIQUID, CORROSIVE, N.O.S. (2- methylpentane-1,5-diamine, TETRAETHYLENEPENTAMINE) AMINES, LIQUID, CORROSIVE, N.O.S. (2- methylpentane-1,5-diamine, TETRAETHYLENEPENTAMINE)
14.3 Transport hazard class(es)	
ADR	
Class	8 (C7) Corrosive substances.
	(Contd. on page 8)

(Contd. on page 8)

according to 1907/2006/EC, Article 31

Printing date 14.12.2022

Version number 6 (replaces version 5)

Revision: 14.12.2022

Trade name EPOXY UV 100 TX, KOMP. B

	(Contd. of page 7)
Label	8
IMDG, IATA	
Class Label	8 Corrosive substances. 8
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user hazard identification number: EMS Number: Segregation groups Stowage Category Segregation Code	Warning: Corrosive substances. 80 F-A,S-B (SGG18) Alkalis A SG35 Stow "separated from" SGG1-acids
14.7 Maritime transport in bulk according IMO instruments	j to Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (2- METHYLPENTANE-1,5-DIAMINE, TETRAETHYLENEPENTAMINE), 8, III
SECTION 15: Regulatory information	

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

according to 1907/2006/EC, Article 31 Version number 6 (replaces version 5)

Printing date 14.12.2022

Revision: 14.12.2022

(Contd. of page 8)

Trade name EPOXY UV 100 TX, KOMP. B

National regulations

Other regulations, limitations and prohibition ordinances

APME document: "Epoxy resins and curing agents: Toxicology, working safety, environment." **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Date of previous version: 27.06.2018 Version number of previous version: 5

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1A: Skin corrosion/irritation - Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3