

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 5 (replaces version 4)

Revision: 12.12.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Trade name** PUR TOP 2K S KOMP B**Article number:** 6730

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### Application of the substance / the mixture

Coating compound/ Surface coating/ paint  
Coating

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:**

Remmers GmbH

Bernhard-Remmers-Str. 13

D-49624 Lönigen / Germany

Tel.: +49(0)5432/83-0

Fax: +49(0)5432/3985

Remmers (UK) Limited

Unit 4 , Lloyds Court

Manor Royal, Crawley – West Sussex RH10 9QU

fon +44 (0) 1293 594 010

fax +44 (0) 1293 594 037

**Information department:**

Product Safety department: Phone: +44 (0) 1293 594 010

Email: sales@remmers.co.ukk

#### 1.4 Emergency telephone number:

National Poisons Information Service (NPIS):

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:

within USA and Canada: 1-800-424-9300

outside USA and Canada: 001-703-527-3887

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

#### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

**Hazard pictograms**

GHS02 GHS07 GHS08

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 5 (replaces version 4)

Revision: 12.12.2022

Trade name **PUR TOP 2K S KOMP B**

(Contd. of page 1)

**Signal word** Danger**Hazard-determining components of labelling:**hexamethylene diisocyanate, oligomers  
xylene**Hazard statements**

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

**Precautionary statements**

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

As from 24 August 2023 adequate training is required before industrial or professional use.

**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of the substances listed below with harmless additions.

<b>Dangerous components [% w/w]:</b>		
CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119485796-17-XXXX 01-2119970543-34-XXXX	hexamethylene diisocyanate, oligomers Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	≥50-≤70%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	≥10-<20%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥10-<20%

**Additional information** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**After inhalation**

Supply fresh air and call for doctor for safety reasons.

(Contd. on page 3)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 5 (replaces version 4)

Revision: 12.12.2022

Trade name **PUR TOP 2K S KOMP B**

(Contd. of page 2)

In case of unconsciousness bring patient into stable side position for transport.

**After skin contact**

Wash immediately with water and soap and rinse thoroughly.

Wash off immediately with water.

**After eye contact**

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

**After swallowing** Seek immediate medical advice.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents**CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.**For safety reasons unsuitable extinguishing agents** Water with a full water jet.**5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

Vapours are heavier than air and spread out over the ground. Ignition over greater distances is possible.

**5.3 Advice for firefighters****Protective equipment:**

Do not inhale explosion gases or combustion gases.

Put on breathing apparatus.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:** No special measures required.**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling** Ensure good ventilation/exhaust in workplaces.**Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities****Storage****Requirements to be met by storerooms and containers:** No special requirements.**Further information about storage conditions:** Keep container tightly closed.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Components with limit values that require monitoring at the workplace:****CAS: 108-65-6 2-methoxy-1-methylethyl acetate**

WEL	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 274 mg/m <sup>3</sup> , 50 ppm
	Sk

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 5 (replaces version 4)

Revision: 12.12.2022

Trade name **PUR TOP 2K S KOMP B**

(Contd. of page 3)

<b>CAS: 1330-20-7 xylene</b>	
WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
<b>Ingredients with biological limit values:</b>	
<b>CAS: 1330-20-7 xylene</b>	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

**Additional information:** The lists that were valid during compilation were used as a basis.

## 8.2 Exposure controls

**Appropriate engineering controls** No further data; see item 7.

### Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures

Do not eat, drink or smoke while working.  
Keep away from food, beverages and animal feed.  
Immediately remove soiled, saturated clothing.  
Wash hands before pauses and after work.  
Store protective clothing separately.  
Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-site shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

#### Respiratory equipment:

Only during spraying without adequate removal by suction.  
In case of high concentrations, use respiratory protection.  
In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

#### Hand protection

Protective gloves.  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Natural rubber, NR

**Eye/face protection** Tightly sealed safety glasses.

**Body protection:** Protective work clothing.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

<b>Physical state</b>	Fluid
<b>Colour:</b>	According to product specification
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.
<b>Melting point/freezing point:</b>	Not determined
<b>Boiling point or initial boiling point and boiling range</b>	139 °C
<b>Flammability</b>	Flammable.

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 5 (replaces version 4)

Revision: 12.12.2022

Trade name **PUR TOP 2K S KOMP B**

(Contd. of page 4)

<b>Lower and upper explosion limit</b>	
<b>Lower:</b>	1.1 Vol %
<b>Upper:</b>	7.0 Vol %
<b>Flash point:</b>	38 °C
<b>Ignition temperature:</b>	315 °C
<b>Decomposition temperature:</b>	Not determined.
<b>pH</b>	Not determined.
<b>Viscosity:</b>	
<b>Kinematic viscosity</b>	Not determined.
<b>dynamic:</b>	Not determined.
<b>Solubility</b>	
<b>Water:</b>	Not miscible or difficult to mix
<b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
<b>Vapour pressure at 20 °C:</b>	6.7 hPa
<b>Density and/or relative density</b>	
<b>Density at 20 °C:</b>	1.07 g/cm <sup>3</sup>
<b>Relative density</b>	Not determined.
<b>Vapour density</b>	Not determined.
<b>9.2 Other information</b>	
<b>Appearance:</b>	
<b>Form:</b>	Fluid
<b>Important information on protection of health and environment, and on safety.</b>	
<b>Explosive properties:</b>	Product is not explosive. However, formation of dangerous explosive vapour/air mixtures is possible.
<b>Solvent separation test</b>	< 3 %
<b>Organic solvents:</b>	24.7 %
<b>VOC EU</b>	
<b>Solid content:</b>	75.0 %
<b>Change in condition</b>	
<b>Evaporation rate</b>	Not determined.
<b>Information with regard to physical hazard classes</b>	
<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	Flammable liquid and vapour.
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void
<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

## SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

### 10.2 Chemical stability

#### Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

(Contd. on page 6)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 5 (replaces version 4)

Revision: 12.12.2022

Trade name **PUR TOP 2K S KOMP B**

(Contd. of page 5)

**10.3 Possibility of hazardous reactions** No dangerous reactions known**10.4 Conditions to avoid** No further relevant information available.**10.5 Incompatible materials:** No further relevant information available.**10.6 Hazardous decomposition products:** No dangerous decomposition products known

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity:** Harmful if inhaled.

#### LD/LC50 values that are relevant for classification:

**CAS: 28182-81-2 hexamethylene diisocyanate, oligomers**

Oral LD50 &gt;2,500 mg/kg (rat)

Dermal LD50 &gt;2,000 mg/kg (rat)

**CAS: 108-65-6 2-methoxy-1-methylethyl acetate**

Oral LD50 8,500 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

**Skin corrosion/irritation:** Causes skin irritation.**Serious eye damage/irritation:** Causes serious eye irritation.**Sensitisation:** May cause an allergic skin reaction.**Germ cell mutagenicity:** Based on available data, the classification criteria are not met.**Carcinogenicity:** Based on available data, the classification criteria are not met.**Reproductive toxicity:** Based on available data, the classification criteria are not met.**STOT-single exposure:** May cause respiratory irritation.**STOT-repeated exposure:** May cause damage to organs through prolonged or repeated exposure.**Aspiration hazard:** May be fatal if swallowed and enters airways.

### 11.2 Information on other hazards

#### Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

### 12.1 Toxicity

**Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.

### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.**vPvB:** Not applicable.

### 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

### 12.7 Other adverse effects

#### Additional ecological information:

#### General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

## SECTION 13: Disposal considerations

### Recommendation

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

#### European waste catalogue

08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances

### Uncleaned packaging:

#### Recommendation:

Disposal must be made according to official regulations.

(Contd. on page 7)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022



Version number 5 (replaces version 4)

Revision: 12.12.2022

Trade name **PUR TOP 2K S KOMP B**

(Contd. of page 6)

Packaging can be reused or recycled after cleaning.

SECTION 14: Transport information	
<b>14.1 UN number or ID number</b> ADR, IMDG, IATA	UN1866
<b>14.2 UN proper shipping name</b> ADR IMDG, IATA	1866 RESIN SOLUTION RESIN SOLUTION
<b>14.3 Transport hazard class(es)</b> ADR	
	
<b>Class</b> <b>Label</b>	3 (F1) Flammable liquids. 3
<b>IMDG, IATA</b>	
	
<b>Class</b> <b>Label</b>	3 Flammable liquids. 3
<b>14.4 Packing group</b> ADR, IMDG, IATA	III
<b>14.5 Environmental hazards:</b> Marine pollutant:	No
<b>14.6 Special precautions for user</b> hazard identification number: EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S</u> -E A
<b>14.7 Maritime transport in bulk according to</b> IMO instruments	Not applicable.
<b>Transport/Additional information:</b>	
<b>ADR</b> Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>Transport category</b> <b>Tunnel restriction code</b>	3 D/E
<b>IMDG</b> Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<b>UN "Model Regulation":</b>	UN 1866 RESIN SOLUTION, 3, III

(Contd. on page 8)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 5 (replaces version 4)

Revision: 12.12.2022

Trade name **PUR TOP 2K S KOMP B**

(Contd. of page 7)

## \* SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Directive 2012/18/EU

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category** P5c FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

#### DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

#### REGULATION (EU) 2019/1148

#### Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

#### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

### Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

EUH204 Contains isocyanates. May produce an allergic reaction.

**Classification according to Regulation (EC) No 1272/2008** Calculation method

**Department issuing data specification sheet:** Product Safety department / EHS

**Date of previous version:** 16.09.2019

**Version number of previous version:** 4

### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1