

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.05.2024

Version number 5 (replaces version 4)

Revision: 31.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **Epoxy AS Color Komp. B**

Article number: 6975

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Remmers GmbH
Bernhard-Remmers-Str. 13
D-49624 Lönigen / Germany
Tel.: +49(0)5432/83-0
Fax: +49(0)5432/3985

Remmers (UK) Limited
Unit 4 , Lloyds Court
Manor Royal, Crawley – West Sussex RH10 9QU
fon +44 (0) 1293 594 010
fax +44 (0) 1293 594 037

Information department:

Product Safety department: Phone: +44 (0) 1293 594 010
Email: sales@remmers.co.ukk

1.4 Emergency telephone number:

National Poisons Information Service (NPIS):
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111

24h-Transport Emergency Contact Phone Number:
within USA and Canada: 1-800-424-9300
outside USA and Canada: 001-703-527-3887

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4	H302	Harmful if swallowed.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Corr. 1B	H314	Causes severe skin burns and eye damage.
Eye Dam. 1	H318	Causes serious eye damage.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 2	H361d	Suspected of damaging the unborn child.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05 GHS07 GHS08

Signal word Danger

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.05.2024

Version number 5 (replaces version 4)

Revision: 31.05.2024

Trade name **Epoxy AS Color Komp. B**

(Contd. of page 1)

Hazard-determining components of labelling:

benzyl alcohol
 cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer
 3-aminomethyl-3,5,5-trimethylcyclohexylamine
 salicylic acid
 m-phenylenebis(methylamine)
 phenol, styrenated
 2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine
 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)

Hazard statements

H302+H332 Harmful if swallowed or if inhaled.
 H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H361d Suspected of damaging the unborn child.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dusts or mists.
 P273 Avoid release to the environment.
 P280 Wear protective gloves / eye protection / face protection.
 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Determination of endocrine-disrupting properties Not applicable.

* SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:		
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-XXXX	benzyl alcohol ----- Acute Tox. 4, H302; Acute Tox. 4, H332	≥30-<40%
CAS: 68609-08-5 EC number: 614-657-1	cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer ----- Skin Corr. 1B, H314; Eye Dam. 1, H318	≥20-<30%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-XXXX	m-phenylenebis(methylamine) ----- Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412, EUH071	≥10-<20%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine ----- Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 1,030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥0.001 %	≥10-<20%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.05.2024

Version number 5 (replaces version 4)

Revision: 31.05.2024

Trade name **Epoxy AS Color Komp. B**

(Contd. of page 2)

CAS: 69-72-7 EINECS: 200-712-3 Reg.nr.: 01-2119486984-17-XXXX	salicylic acid Repr. 2, H361d; Eye Dam. 1, H318; Acute Tox. 4, H302	≥5-<10%
CAS: 2579-20-6 EINECS: 219-941-5 Reg.nr.: 01-2119543741-41-XXXX	1,3-Cyclohexanedimethanamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Aquatic Chronic 3, H412	≥1-<2.5%
CAS: 61788-44-1 Reg.nr.: 01-2119980970-27-XXXX	phenol, styrenated Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥1-<2.5%
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-XXXX	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319	≥0.5-≤1%
CAS: 25513-64-8 EINECS: 247-063-2 Reg.nr.: 01-2119560598-25-XXXX	2,2,4(or 2,4,4)-trimethylhexane-1,6-diamine Skin Corr. 1A, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	≥0.5-<1%
CAS: 113930-69-1 NLP: 500-302-7 Reg.nr.: 01-2119965162-39-XXXX	4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine) Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Sens. 1B, H317	≥0.25-≤0.5%
CAS: 112-72-1 EINECS: 204-000-3 Reg.nr.: 01-2119485910-33-XXXX	1-Tetradecanol Aquatic Chronic 1, H410; Eye Irrit. 2, H319	≥0.1-<0.25%

Additional information For the wording of the listed hazard phrases refer to section 16.

* SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation

Take affected persons into the open air and position comfortably

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

After skin contact Wash immediately with water and soap and rinse thoroughly.

After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing

Call a doctor immediately.

Drink plenty of water and provide fresh air. Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

symptomatic treatment

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.05.2024

Version number 5 (replaces version 4)

Revision: 31.05.2024

Trade name **Epoxy AS Color Komp. B**

(Contd. of page 3)

5.2 Special hazards arising from the substance or mixture

Thick black smoke forms in fires. Inhalation of dangerous decomposition products may cause serious damage to your health.

May be released in case of fire

Nitrogen oxides (NO_x)

carbon monoxides

Formation of poisonous gases during heating or in fires.

5.3 Advice for firefighters**Protective equipment:**

Wear self-contained breathing apparatus.

Wear full protective suit.

Put on breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated fire fighting water separately. It must not enter drains.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Ensure adequate means of retaining the water used for extinguishing

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Avoid skin contact. Avoid eye contact.

Do not breathe fumes/aerosol

Put on breathing apparatus.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Use only in well ventilated areas.

Ensure good ventilation/exhaust in workplaces.

Avoid the formation of aerosols.

Information about protection against explosions and fires: Keep breathing equipment ready.

7.2 Conditions for safe storage, including any incompatibilities**Storage**

Requirements to be met by storerooms and containers: Prevent any penetration into the ground.

Information on storage in a common storage facility: Store away from food.

Further information about storage conditions:

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

*** SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Components with limit values that require monitoring at the workplace:**

CAS: 64-17-5 ethanol

WEL | Long-term value: 1920 mg/m³, 1000 ppm

Additional information: The lists that were valid during compilation were used as a basis.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.05.2024

Version number 5 (replaces version 4)

Revision: 31.05.2024

Trade name **Epoxy AS Color Komp. B**

(Contd. of page 4)

8.2 Exposure controls**Appropriate engineering controls** No further data; see section 7.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures**

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

The following indication regarding the personal protective equipment are to be considered as suggestions. The selection of the necessary personal protective equipment is to be evaluated by the employer depending on the types of operations and the local circumstances. If a risk assessment on-site shows that there is no risk for employees, the personal protective equipment is not required or the amount of the PPE can be adapted accordingly.

Respiratory equipment:

Filter A (brown)

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Hand protection

Impervious gloves

Long cuffed gloves

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Tightly sealed safety glasses.**Body protection:** Protective work clothing.

* SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Physical state**

Fluid

Colour:

Yellowish

Odour:

Characteristic

Odour threshold:

Not determined.

Melting point/freezing point:

Not determined

Boiling point or initial boiling point and boiling range

>100 °C

Flammability

Not applicable.

Lower and upper explosion limit**Lower:**

Not determined.

Upper:

Not determined.

Flash point:

77 °C

Auto-ignition temperature:

not applicable

Decomposition temperature:

Not determined.

pH

Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.05.2024

Version number 5 (replaces version 4)

Revision: 31.05.2024

Trade name **Epoxy AS Color Komp. B**

(Contd. of page 5)

Viscosity:	
Kinematic viscosity	Not determined.
dynamic at 20 °C:	340 mPas
Solubility	
Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	0.1 hPa
Density and/or relative density	
Density at 20 °C:	1.05 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Explosive properties:	Product is not explosive.
Solvent separation test	< 3 %
Organic solvents:	22.4 %
VOC EU	
Solid content:	98.0 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

None if used properly.

None if stored properly.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.05.2024

Version number 5 (replaces version 4)

Revision: 31.05.2024

Trade name **Epoxy AS Color Komp. B**

(Contd. of page 6)

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Harmful if swallowed or if inhaled.

LD/LC50 values that are relevant for classification:		
CAS: 100-51-6 benzyl alcohol		
Oral	LD50	1,620 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4.178 mg/l (rat)
CAS: 1477-55-0 m-phenylenebis(methylamine)		
Oral	LD50	930 mg/kg (rat)
Dermal	LD50	>3,100 mg/kg (rabbit)
CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Oral	LD50	1,030 mg/kg (ATE) 1,030 mg/kg (rat)

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/irritation: Causes serious eye damage.

Sensitisation: May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Suspected of damaging the unborn child.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties
None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:
CAS: 1477-55-0 m-phenylenebis(methylamine)
EC50/48h 15.2 mg/l (Daphnia magna)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects No further relevant information available.

Remark: Harmful to fish

Additional ecological information:

General notes:

Do not allow undiluted or non-neutralised product to reach the sewage system or receiving waters.

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations.

Hardened product remains may be disposed of as building rubble or put into household garbage.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.05.2024

Version number 5 (replaces version 4)

Revision: 31.05.2024

Trade name **Epoxy AS Color Komp. B**

(Contd. of page 7)

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances



Uncleaned packaging:**Recommendation:**

Disposal must be made according to official regulations.

Packaging can be reused or recycled after cleaning.

*

SECTION 14: Transport information

14.1 UN number or ID number ADR, IMDG, IATA	UN2735
14.2 UN proper shipping name ADR	2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine), 3-aminomethyl-3,5,5-trimethylcyclohexylamine)
IMDG, IATA	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine), 3-aminomethyl-3,5,5-trimethylcyclohexylamine)
14.3 Transport hazard class(es) ADR	
	
Class Label	8 (C7) Corrosive substances. 8
IMDG, IATA	
	
Class Label	8 Corrosive substances. 8
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user hazard identification number: EMS Number: Segregation groups Stowage Category Segregation Code	Warning: Corrosive substances. 80 F-A,S-B (SGG18) Alkalis A SG35 Stow "separated from" SGG1-acids
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.05.2024

Version number 5 (replaces version 4)

Revision: 31.05.2024

Trade name **Epoxy AS Color Komp. B**

(Contd. of page 8)

Transport category	3
Tunnel restriction code	E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS(METHYLAMINE), 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE), 8, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act

Regulated explosives precursors

None of the ingredients is listed.

Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations

Other regulations, limitations and prohibition ordinances

APME document: "Epoxy resins and curing agents: Toxicology, working safety, environment."

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship. Delivery specifications are found in the respective Technical Information Sheets.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 31.05.2024

Version number 5 (replaces version 4)

Revision: 31.05.2024

Trade name Epoxy AS Color Komp. B

(Contd. of page 9)

H332 Harmful if inhaled.
H361d Suspected of damaging the unborn child.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH071 Corrosive to the respiratory tract.

Classification according to Regulation (EC) No 1272/2008 Calculation method**Department issuing data specification sheet:** Product Safety department / EHS**Date of previous version:** 06.04.2020**Version number of previous version:** 4**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
Repr. 2: Reproductive toxicity – Category 2
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3