



FM ECC

- Jointing Mortar ECC -

2-Component mineral jointing mortar with epoxy resin

Colour	Availability		
	Quantity per pallet	90	42
	Size / Quantity	3,9 kg	26,1 kg
	Type of container	Plastic bucket	[sack]
	Container code	03	27
	Art. no.		
	0350	■	
	0351		■

Range of use

- Pointing of natural stone masonry
- Masonry with elevated dynamic stresses

Property profile

- High-grade binder
- High flank adhesion
- High durability
- Reliable setting
- Resistant to cracking
- Water vapour permeable
- Good balance between flexural and compressive strength
- Compressive strength: > 10 N/mm² (M10)


Tools / Cleaning

Remmers tools

- > [Mischgefäß \(4030\)](#)
- > [Collomix® Stirrer KR \(4292\)](#)

Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 9 months.



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.