



CL Prep Historic

- Historic Rough Cast -
Specially formulated rough cast

Availability	
Quantity per pallet	42
Size / Quantity	
Type of container	Paper bag
Container code	20
Art. no.	
0574	■

Application rate

Dependent on building and formulation
Apply to a large enough trial area to determine the precise amount required.



Range of use

- Substrate preparation before applying Remmers Historic renders
- Equalising differences in the absorption properties of the substrate



Property profile

- Reproduction of the original state in accordance with monument preservation targets
- Specially adapted binder
- Specially adapted grain size distribution

Characteristic data of the product

Water requirement	Dependent on formulation
Compressive strength	Dependent on building

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Possible system products


- CL Levell Historic (0575)
- CL Top Historic (0576)

Preparation

- Substrate requirements
Clean, dust-free and capable of supporting a load.
- Substrate preparation
Pre-wet the substrate so that it is slightly moist.


Production of the mixture

- Mixing
Pour water into a clean container and add dry mortar.
Mix thoroughly with a mixer for approx. 3 minutes until homogeneous.





Directions

- Conditions for use
Low temperatures increase, while high temperatures decrease the working and setting time.
 - Working time (+20 °C)
Approx. 60 minutes
- Throw on the mixed mortar in clumps (max. 5 mm).
Do not use the material to level out uneven surfaces.





Tips on use	Once it has hardened, mortar must not be made workable again by adding either water or more wet mortar. Protect wet mortar surfaces against frost, rain and drying out too quickly for at least 4 days. Leave to harden for at least 3 days before applying subsequent layers of render. Since the material is formulated for a specific object, application by machine cannot be guaranteed.
Notes	The mixing water must be of drinking water quality. May contain traces of pyrite (iron sulphide). Do not use on gypsum-based substrates. Low chromate content in accordance with Directive 2003/53/EC. The characteristic data of the product were calculated under laboratory conditions at 20°C and 65% relative humidity.
Tools / Cleaning 	Mixing tool, spray plasterer, aluminium float, Berlin bricklayer's trowel, Bernese style trowel Clean tools with water while the material is still fresh. Remmers tools ➤ Mischgefäß (4030) ➤ Alu-Kardätsche mit Holzgriff (4429) ➤ Spritzputzapparat (4439)
Storage / Shelf life 	If stored in an unopened container and in a dry place, the product will keep for approx. 12 months.
Safety data / Regulations	For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.
Disposal	Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.