



Clean FL

Cleaning concentrate for MB FL 2K

| Availability | |
|---------------------|----------------|
| Quantity per pallet | 288 |
| Size / Quantity | |
| Type of container | Plastic bottle |
| Container code | 01 |
| Art. no. | |
| 0651 | ■ |

Application rate Depending on cleaning requirements:
10% solution in water for normal cleaning requirements
20% solution in water for heavy cleaning requirements
Undiluted for stubborn material deposits

Range of use

- Removing streaks and build-up of MB FL 2K on ceramic coverings
- Secondary cleaning of tiling that has undergone preliminary cleaning
- Cleaning tools



Property profile

- High-yielding concentrate
- Also removes stubborn deposits of MB FL 2K



| | | |
|---|-----------------|--------------------------------|
| Characteristic data of the product | Density (20 °C) | Approx. 0.98 g/cm ³ |
| | Odour | Mild |

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Certificates > [Datenblatt über Inhaltsstoffe](#)

Directions

Apply the material uniformly on the dry substrate and allow to take effect.
After leaving to act for a suitable working time, scrub with a scrubbing brush or Scotch-Brite sponge and wipe off with the foam rubber float.
The working time and application rate depend on the amount of material to be removed.
Repeat the process if necessary on heavily soiled surfaces.
Rinse surfaces with clear water after every cleaning procedure.
Seal opened containers well and use contents as soon as possible.

Tips on use

Always set up a trial area/trial areas first.
Leaving the cleaning agent to act for long periods may cause damage.
Ensure good ventilation.
Use suitable measures to protect nearby components and materials that are not intended to come into contact with the product




- Thinning
Dilute the concentrate with water



Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.



Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Detergents Regulation (EC) No
648/2004

15% < 30% butyl glycol

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.