



## V KSE

Thinner for stone strengtheners

Availability		
Quantity per pallet	84	24
Packaging unit	5 l	30 l
Type of container	Tin canister	Tin canister
Container code	05	30
Art. no.		
0657	■	■

### Application rate

Dependent on application



### Range of use

- Thinning stone strengtheners
- Achieving optimum strength levels via targeted control of the gel deposition rate
- Cleaning tools and surfaces



### Property profile

- Optimum solubility of silicic acid esters
- Low-volatility solvent for preventing unwanted remigration effects during the reaction time of the silicic acid ester
- Clear
- Free of aromatic compounds
- Low odour



### Characteristic data of the product

Density (20 °C)	approx. 0.78 g/cm <sup>3</sup>
Flash point °C	approx. 64 °C

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

### Possible system products

➤ [KSE products](#)

### Directions

#### ■ Conditions for use

Temperature of the material, air and substrate: from min. +8 °C to +25 °C



To remove excess material, soak an absorbent, lint-free cloth with Remmers V KSE and dab the treated surfaces.



---

To adjust the gel deposition rate, add together KSE Stone Strengthener and V KSE and mix thoroughly.

---

#### Notes

Deviations from applicable regulations must be agreed separately.  
The relevant test certificates must be observed when planning and carrying out work.

---

#### Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.



#### Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

---

#### Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.