Technical Data Sheet Product number 0663







## Sulfatex flüssig

## - Sulfatex LQ -

|                           | Availability   |                  |                  |
|---------------------------|--|------------------|------------------|
|                           | Quantity per pallet  | 90               | 24               |
|                           | Packaging unit   | 5 kg             | 30 kg            |
|                           | Type of container  | Plastic canister | Plastic canister |
|                           | Container code   | 05               | 30               |
|                           | Art. no.   |                  |                  |
|                           | 0663   |                  |                  |
|                           |  |                  |                  |
| Range of use              | [AB_SB_1]  |                  |                  |
| •                         |  |                  |                  |
| Property profile          | [EG_SB_1]  |                  |                  |
| H <sub>2</sub> 0          | <b>[</b> EG_SB_2]  |                  |                  |
|                           |  |                  |                  |
| Possible system products  | > Kiesol (1810)  |                  |                  |
|                           | > WP Sulfatex (0430)   |                  |                  |
|                           | <ul> <li>&gt; WP Sulfatex rapid (0429)</li> <li>&gt; Adolit M Liquid* (2100)</li> </ul>  |                  |                  |
|                           | <ul> <li>Adott M Elquid (2100)</li> <li>[sanierputzsysteme_0663]</li> </ul>  |                  |                  |
|                           | *Use biocidal products carefully.<br>Always read the label and product information before use.   |                  |                  |
|                           |  |                  |                  |
| Tools / Cleaning          | Clean tools with water while the material is still fresh.  |                  |                  |
|                           |  |                  |                  |
| Storage / Shelf life      | If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.<br>[H_BI_2] |                  |                  |
|                           |  |                  |                  |
| Safety data / Regulations |  |                  |                  |

Remmers (UK) Ltd 🔳 Unit B1 · The Fleming Centre · Fleming Way Crawley · West Sussex · RH10 9NN 🔳 Tel: 01293 594010 📕 Fax: 01293 594037 🛢 sales@remmers.co.uk 🔳 www.remmers.co.uk 0663 TM-1-163 10/19 EW 1/2







For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.