



# Traffic Film Remover

## - Clean SL -

Surfactant solution for removing grime, dirt incrustation, dust, oil and grease deposits

Availability	
Quantity per pallet	84
<b>Packaging unit</b>	<b>5 kg</b>
Type of container	Plastic canister
Container code	05
<b>Art. no.</b>	
0671	■

### Application rate

Approx. 0.01 – 0.05 ml/m<sup>2</sup> depending on the type of contamination

Apply to a large enough trial area to determine the precise amount required.



### Range of use

- Removing grime, dirt incrustation, dust, oil and grease deposits
- Mineral substrates
- Floors and walls



### Property profile

- Highly washing active
- High-yielding concentrate
- Low-foaming
- Can be used for manual or machine cleaning
- Biodegradable



### Characteristic data of the product

Density (20 °C)	1.00 kg/l
Surfactant content	Approx. 10%
pH value (20 °C)	Approx. 11.5
Appearance	Clear solution

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

### Certificates

➤ [Data sheet for ingredients](#)



Possible system products


- **Funcosil FC (0711)**
- **Funcosil SNL (0602)**
- **Funcosil SN (0604)**

Preparation

■ **Substrate preparation**

Mechanically remove coarse soiling.  
 Moisten the surface to be cleaned with water.  
 Depending on the intensity of the contamination, produce a dilution with a concentration of 1:5 to 1:20.  
 Set up a trial area to determine the cleaning effect.

Directions



■ **Conditions for use**

Temperature of the material, air and substrate: from min. +5 °C to max. +30 °C

Use a suitable tool to apply the solution that has been prepared for the contamination at hand.  
 Work in the material using a scrubbing brush.  
 When using a high-pressure cleaner, pour approx. 0.5% of the product into the bypass tank.  
 Wash off thoroughly.  
 Remove cleaning agent until no residues remain.  
 If needed, repeat the application.

Tips on use

Take appropriate measures to protect adjacent building elements and materials that should not come into contact with the product.  
 Set up the necessary collection receptacles.

Notes

Residue left from cleaning may have a negative influence on subsequent impregnation.  
 The applicable regulations and legal requirements must be observed.  
 Always set up a trial area/trial areas first.

Tools / Cleaning




Scrubbing brush, high-pressure cleaner, steam jet

Clean tools with water immediately after use.

**Remmers tools**

- **Gloria Hochleistungssprühgerät 410 / 405 T Profiline (4667)**
- **Gloria Drucksprüher Pro 100 (4668)**
- **Gloria CleanMaster PERFORMANCE PF 50 (4666)**
- **Gloria CleanMaster EXTREME EX 100 (4665)**
- **Heizkörperpinsel (4541)**

Storage / Shelf life



At least 36 months in unopened, original containers stored cool, dry and protected from frost.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Personal protective equipment




---

Respiratory protection with at least an A/P2 combination filter must be worn during spraying, together with safety goggles. Wear suitable protective gloves and clothing.

---

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

---

Detergents Regulation  
(EC) No 648/2004

5 – 15% nonionic surfactants;  
< 5% EDTA and its salts, aliphatic hydrocarbons, butyl diglycol, butyl glycol

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.