



## Clean AC [basic]

### - Clinker Cleaner AC -

Acidic cleaner

Availability			
Quantity per pallet	240	90	44
Size / Quantity	12 x 1 kg	5 kg	10 kg
Type of container	Plastic bucket	Plastic bucket	Plastic bucket
Container code	01	05	10
Art. no.			
0672	■	■	■

#### Application rate

Approx. 0.05 - 0.1 kg/m<sup>2</sup> depending on the level of soiling when used 1:10 in water

Apply to a large enough trial area to determine the precise amount required.



#### Range of use

- Fair-faced masonry work made of clinker and brick
- Removing mortar residues and lime and cement films
- Removing lime and scale



#### Property profile

- High-yield powder concentrate
- Dissolves easily in warm water
- pH value 0.8 (10% solution)



#### Characteristic data of the product

Solubility	Very good
pH value (20 °C)	0.8 (10% solution)
Appearance	White, crystalline powder

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

#### Certificates

- [Data sheet for ingredients](#)

#### Possible system products

- [Funcosil WS \(0614\)](#)
- [Funcosil SNL \(0602\)](#)
- [Funcosil FC \(0711\)](#)



---

## Preparation

### ■ Substrate preparation


Mechanically remove coarse soiling.  
Pre-wet the substrate being cleaned with water.  
Depending on the intensity of the soiling, prepare a solution with a concentration of from 1:4 to 1:20.  
Set up a trial area to determine the cleaning effect.

---

## Directions

### ■ Conditions for use

Temperature of the material, air and substrate: from min. +5 °C to max. +30 °C.



Use a suitable tool to apply the solution that has been prepared for the contamination at hand.  
Clean surface using a scrubbing brush.  
Wash off thoroughly.  
A high-pressure cleaner may optionally be used for cleaning.  
Remove cleaning agent until no residues remain.  
If needed, repeat the application.

---

## Tips on use

Take appropriate measures to protect adjacent building elements and materials that should not come into contact with the product.  
Set up the necessary collection receptacles.  
Cleaner residue may lead to lime sinter.  
If the material comes into contact with metal, wash away immediately with water.  
Dark joints may be lightened by cleaning.  
Not suitable for sand-lime facing brick.  
On surfaces that are highly porous or prone to efflorescence, pre-impregnate then clean (process patent DE3018116C2).

---

## Notes

Not suitable for sand-lime facing brick.  
The material only dissolves impurities containing lime and not any other dirt deposits.  
The applicable regulations and legal requirements must be observed.  
The relevant test certificates must be observed when planning and carrying out work.  
Always set up a trial area/trial areas first.

---

## Tools / Cleaning

Scrubbing brush, scrubbing broom, high-pressure cleaner




Clean tools with water immediately after use.

---

## Storage / Shelf life

At least 36 months in unopened, original containers stored cool, dry and protected from frost.



---

## Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

---

## Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.



---

Detergents Regulation  
(EC) No 648/2004

> 30 % amphoteric surfactants

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.