



## Green Growth Remover

Special detergent for removing green growth on terraces, stone floors and walls

Availability		
Quantity per pallet	378	200
Size / Quantity	6 x 1 l	4 x 2,5 l
Type of container	Plastic bottle	Plastic canister
Container code	01	03
Art. no.	0676	■
		■

### Application rate

Approx. 10 ml concentrate/m<sup>2</sup> in a mixing ratio of 1:10  
Apply to a large enough trial area to determine the precise amount required.



### Range of use

- Surfaces of construction materials such as concrete, natural stone, sand-lime bricks, ceramics, glass, wood, plastics and WPC



### Property profile

- Self-actively removes organic soiling with a deep cleaning effect
- No further washing of the surface needed, 24 hours of reaction time
- Can be used pure or diluted with water
- Long-term effect if applied undiluted
- Does not contain active chlorine
- Gentle on the substrate



### Characteristic data of the product

State of aggregation	Liquid
pH value (20 °C)	7.6

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

### Certificates


- [Datenblatt über Inhaltsstoffe](#)

### Preparation

- Substrate preparation  
Mechanically remove coarse soiling.

### Directions

- Conditions for use  
Temperature of the material, air and substrate: from min. +5 °C to max. +30 °C.



Apply the material uniformly on the dry substrate and allow to take effect.  
Reaction time of 24 hours, protect against rain, do not rinse with water.  
After a sufficient time for reaction, clean the surface.  
If needed, repeat the application.

### Tips on use

Always set up a trial area/trial areas first.  
If necessary, use tarpaulins or sheeting to protect against the product coming into direct contact with any adjacent crops, plants or building elements.

### Notes

Do not let any rinsing water get into bodies of water.  
Deviations from applicable regulations must be agreed separately.



Tools / Cleaning




Watering can, surface sprayer  
Clean tools immediately after use with water.  
Ensure that any residue from cleaning is disposed of correctly.

Remmers tools

- Gloria Drucksprüher Pro 100 (4668)
- Gloria CleanMaster PERFORMANCE PF 50 (4666)
- Gloria CleanMaster EXTREME EX 100 (4665)
- Heizkörperpinsel (4541)

Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 24 months.

Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

First aid measures

If inhaled:  
Supply fresh air.  
Seek medical treatment in case of complaints.  
If on skin:  
Wash immediately with water and soap and rinse thoroughly.  
If in eyes:  
Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.  
If swallowed:  
Do not induce vomiting; call for medical help immediately.

Personal protective equipment

Protect body parts with suitable clothing when using the product.  
Respiratory protection with a particle filter P2 must be worn during spraying, together with protective goggles. Wear suitable protective gloves and clothing.

Disposal

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.  
European waste code 03 02 02\* organochlorinated wood preservatives

Biocidal Products Regulation

**Active ingredients:**  
100 g of this product contain 2,45 g alkyl (C12-16) dimethylbenzyl ammonium chloride  
Use biocides safely. Always read the label and product information before using!

Detergents Regulation (EC) No 648/2004

< 5% cationic surfactants

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.