



## Power Protect First-Aid Kit

Kit for mould elimination and immediate binding of spores

|   |     |
|---|-----|
| <b>Availability</b>   |     |
| Quantity per pallet   | 108 |
| <b>Size / Quantity</b>  |     |
| Container code  | 01  |
| <b>Art. no.</b>   |     |
| 0679  | ■   |
| <p>The kit contains:</p> <ul style="list-style-type: none"> <li>3 cartridges of Power Protect First-Aid Gel*</li> <li>2 m<sup>2</sup> anti-static film Power Protect First-Aid Sheet</li> <li>1 roll Kip® 328 Fabric Tape Extra</li> </ul> <p>*Use biocides safely. Always read the label and product information before use.</p> |     |

|                  |   |
|------------------|---|
| Application rate | <p>Power Protect First-Aid Gel*: approx. 2,000 ml/m<sup>2</sup></p> <p>Power Protect First-Aid Sheet: approx. 1 m<sup>2</sup>/m<sup>2</sup></p> |
|------------------|---|

|              |   |
|--------------|---|
| Range of use | <ul style="list-style-type: none"> <li>■ Immediate binding of mould spores</li> <li>■ Elimination of mould on mineral substrates and other alcohol-resistant substrates</li> <li>■ Temporary health protection prior to mould remediation measures</li> </ul> |
|--------------|---|




|                  |  |
|------------------|--|
| Property profile | <ul style="list-style-type: none"> <li>■ Prevents spores from being emitted into the ambient air</li> <li>■ Alcohol-based</li> <li>■ Blocking effect until mould remediation can be carried out</li> <li>■ Fast and independent action</li> <li>■ Deep action</li> </ul> |
|------------------|--|

|  |                 |           |
|--|-----------------|-----------|
| Characteristic data of the product   | Density (20 °C) | 0.86 g/ml |
|  | Viscosity       | Gel-like  |
|  | Odour           | Alcohol   |
| The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications. |                 |           |

|                          |   |
|--------------------------|---|
| Possible system products | <ul style="list-style-type: none"> <li>➤ Power Protect First-Aid Gel* (0684)</li> <li>➤ SP Top SL <sup>[basic]</sup> (1050)</li> <li>➤ SL Fill Q2 (2996)</li> <li>➤ SL Fill Q3 (2997)</li> <li>➤ Color SA plus (2984)</li> </ul> <p>*Use biocidal products carefully.<br/>Always read the label and product information before use.</p> |
|--------------------------|---|

|             |  |
|-------------|--|
| Preparation | <ul style="list-style-type: none"> <li>■ Substrate requirements<br/>Alcohol-resistant.</li> <li>■ Substrate preparation<br/>If necessary, use a suitable device to vacuum off larger fruiting bodies.</li> </ul> |
|-------------|--|

|            |   |
|------------|---|
| Directions | <ul style="list-style-type: none"> <li>■ Conditions for use<br/>Temperature of the material, air and substrate: from min. +5 °C to max. +25 °C.</li> </ul> <p>Using sufficient force, apply the material to the surface being treated.<br/>Position a suitable dissipative film on top as tightly as possible and tape the edges with adhesive tape.<br/>Using a suitable tool, spread the material out evenly underneath the film.</p> |
|------------|---|



|             |  |
|-------------|--|
| Tips on use | Keep away from sources of ignition, protect against electrostatic charges. |
|-------------|--|



---

Use to a distance of approx. 20 cm beyond the visibly contaminated area.

---

**Notes**

After application, the Power Protect First-Aid Gel slowly releases isopropanol. Since isopropanol is a potentially flammable substance, explosive alcohol-air mixtures may form in unfavourable environments. For this reason, ignition sources must be avoided and the room containing the treated components must be ventilated thoroughly. Keep away from sources of ignition, protect against electrostatic charges.

Mould remediation measures must be carried out after a maximum of 14 days. Alternatively, re-treat the surface. After a maximum of 14 days, remove the film and dispose of it properly.

Make sure that any material residues that have not dried are disposed of properly.

Do not heat cartridge above +35 °C.

Deviations from applicable regulations must be agreed separately.

The relevant test certificates must be observed when planning and carrying out work.

---

**Tools / Cleaning**

Hand applicator and compressed-air gun, wallpaper brush




Clean tools immediately after use with water.

---

**Storage / Shelf life**

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.



**Safety data / Regulations**

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

---

**First aid measures**

If inhaled:  
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness bring patient into stable side position for transport.  
Seek medical treatment in case of complaints.

If on skin:  
Wash immediately with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.

If in eyes:  
Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

If swallowed:  
Do not induce vomiting; call for medical help immediately.

---

**Disposal**

Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.

---

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.