



# Verdickungsadditiv AFM

Availability	
Quantity per pallet	500
Packaging unit	100 g
Container code	81
Art. no.	
0738	■

## Range of use

- [AW\_AF\_4]
- [AW\_AF\_5]



## Property profile

- [EG\_AF\_6]
- [EG\_AF\_7]

## Possible system products

- [Silicone AFM / Hardener AFM \(0736\)](#)

## Directions

- [VA1\_AF\_8]
- [VA1\_AF\_9]
- [VA1\_AF\_10]

## Tips on use

- [VA2\_AF\_3]
- [VA2\_AF\_4]
- [VA2\_AF\_5]

## Notes

Deviations from applicable regulations must be agreed separately.  
The relevant test certificates must be observed when planning and carrying out work.

## Storage / Shelf life



If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.  
Store in well-sealed, original containers, out of the reach of children and in a dry, cool, well-ventilated room which is protected from direct sunlight and frost. No smoking is permitted in storage areas.

## Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.



---

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.