



Thickening Additive AFM

Additive for modifying the flowability of Silicone AFM

Availability	
Quantity per pallet	500
Size / Quantity	100 g
Container code	81
Art. no.	
0738	■

Range of use

- Reduction in flowability or increase in stability of Silicone AFM
- Production of skin moulds by brushing on uneven or perpendicular mould surfaces without run-off or sinking

Property profile

- Cross-linking and viscosity increasing
- Neutral colour

Possible system products

- [Silicone AFM / Hardener AFM \(0736\)](#)

Directions

Shake the container or stir its contents vigorously before use.
Mix the thickening additive AFM with the ready-mixed silicone AFM in the selected ratio using a spatula or stirrer until homogeneous.



Tips on use

Single-use pipettes (20 drops = 1 g) or disposable syringes can be used to measure out small quantities of additive. At low temperatures, the thickening additive AFM is viscous to solid and can be brought into a readily workable, liquid form by heating.
The product reacts with moisture in the air.
Re-seal containers immediately after use.

Notes


Deviations from applicable regulations must be agreed separately.
The relevant test certificates must be observed when planning and carrying out work.

Tools / Cleaning

Clean tools immediately after use with thinner and brush cleaner.

Storage / Shelf life

If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.
Store in well-sealed, original containers, out of the reach of children and in a dry, cool, well-ventilated room which is protected from direct sunlight and frost. No smoking is permitted in storage areas.



Safety data / Regulations

For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet.

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.