



Lack C

Cream-like, solvent-containing protective bitumen coating

Availability		
Quantity per pallet	96	22
Size / Quantity	5 l	20 l
Type of container	Tin bucket	Tin bucket
Container code	05	20
Art. no.	0814	■ ■

Application rate

At least 0.20 l/m² per coat
Application rate increases accordingly on rough surfaces.



Range of use

- For use as a primer on old bituminous substrates (with blinding material)
- Protective coating for concrete, masonry and render in the subsoil



Property profile

- Cream-like
- Contains solvents
- Resistant to moisture
- Resistant to heat and cold
- Resistant to bodies of water aggressive to concrete (DIN 4030 XA3)



Characteristic data of the product

Base	solvent-containing bitumen emulsion
Density (20 °C)	approx. 0.96 kg/l
Flash point °C	> +63 °C
Consistency	cream-like

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

Possible system products


- **Remmers PMBCs**

Preparation

- **Substrate requirements**
The substrate must be clean, solid and free of oils, grease and release agents.
Matt damp surfaces are permitted.

Directions

- **Conditions for use**
Temperature of the material, air and substrate: from min. +5 °C to max. +30 °C.





Ready to use, straight from the container.
Blind with quartz sand if necessary.

Tips on use

In the case of liquid-applied waterproofing materials, direct sunlight and/or wind exposure can cause accelerated skin formation and accompanying blistering.
Do not use in enclosed spaces.
Do not apply any further layers until the previous layer has hardened sufficiently.
Seal opened containers well and use contents as soon as possible.



<p>Notes</p>	<p>Current regulations and legal requirements must be taken into account and deviations from these must be agreed separately. The relevant test certificates must be observed when planning and carrying out work.</p>
<p>Tools / Cleaning</p> 	<p>Flat brush, lambskin roller FC, suitable spraying equipment</p> <p>Clean tools immediately after use with water. Remove dried-on material using V 101 Thinner (0978).</p> <p>Remmers tools</p> <ul style="list-style-type: none"> > Flächenstreicher (4540) > Farbrolle FC (4913) > Rollerbügel (4449) > Pro nylon roller (5045) > Nylon Roller Standard (5066) > Heizkörperpinsel (4541)
<p>Storage / Shelf life</p> 	<p>If stored unopened in its original container in a cool, dry place and protected against frost, the product will keep for at least 12 months.</p>
<p>Safety data / Regulations</p>	<p>For further information on the safety aspects of transporting, storing and handling the product and on disposal and environmental matters, please see the current Safety Data Sheet. Do not eat, drink or smoke when working.</p>
<p>Personal protective equipment</p>	<p>Respiratory protection with at least an A/P2 combination filter must be worn during spraying, together with safety goggles. Wear suitable protective gloves and clothing.</p>
<p>Disposal</p>	<p>Larger quantities of leftover product should be disposed of in the original containers in accordance with the applicable regulations. Completely empty, clean containers should be recycled. Do not dispose of together with household waste. Do not allow to enter the sewage system. Do not empty into drains.</p>

Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.