



Product is not yet approved in English (United Kingdom) (en\_GB).



# DS Protect Clip

## - DS Clip -

Clip for DS Protect and DS Protect AL



Availability	
Quantity per pallet	80
<b>Size / Quantity</b>	<b>50 pcs</b>
Type of container	Bag
Container code	01
<b>Art. no.</b>	
0818	■

**Application rate**                      Approx. 4 pcs/m

**Range of use**                            ■ Fastening and assembly aid for DS Protect  
 ■ Holder for DS Protect AL

**Property profile**                        ■ Self-sealing in connection area  
 ■ Flexible  
 ■ UV and temperature resistant

**Characteristic data of the product**

Heat resistance	+170 °C
-----------------	---------

The values stated represent typical characteristic data of the product and are not to be understood as binding product specifications.

**Certificates**                                > **Remmers International Guarantee**  
 Inasmuch as a Remmers International Guarantee (RIG) has been granted, only the conditions / requirements indicated in the written contract between die RIG specialist firm and Remmers shall apply.

**Additional information**                > **Instructions for use: DS Protect Clip**

**Possible system products**            > **DS Protect (0823)**  
 > **DS Protect AL (0819)**

**Directions**                                 See instructions for use.

**Notes**                                         Current regulations and legal requirements must be taken into account and deviations from these must be agreed separately.  
 The relevant test certificates must be observed when planning and carrying out work.

**Tools / Cleaning**

**Remmers tools**

- > **Collomix AR 170 (4247)**
- > **Collomix® HEXAFIX® Nachrüstadapter (4283)**
- > **Ankerrührer (4249)**
- > **Schöpfkelle (4103)**
- > **Schichtdickenkelle (4000)**
- > **Profile Trowel (5047)**



› Rundkelle (4114)

**Storage / Shelf life**

May be stored for an unlimited period if protected from direct sunlight.



Please note that the data and information given above have been calculated as guidelines in the laboratory and from real-life experience and are therefore not binding as a basic principle.

This information is therefore of a general nature only and describes our products and how they are used and worked with. In this respect, it must be borne in mind that the varied and diverse nature of the

prevailing working conditions, materials used and construction sites encountered means that not every individual case can be covered. In this respect, we therefore recommend either conducting tests or liaising with us in the event of any doubt. Unless we have provided express written assurance of the products' specific suitability or characteristics in respect of a contractually stipulated intended use, any technical application-related advice or instruction will never

be binding, even though it is provided to the best of our knowledge. In all other respects, our general terms and conditions of sale and delivery shall apply.

When a new version of this Technical Data Sheet is published, it shall replace the previous version.